

Vega 100 E1/T1 23-60 Channels Digital



Let's talk Voice over IP. Let's talk VegaStream. Our range of dedicated VoIP gateways is helping to drive down the total cost of business communications. VegaStream's technical know-how and non-stop support mean that VoIP simply works, first time, every time. We collaborate with service providers, technology and channel partners to enable easy integration with existing systems. VegaStream gives your business a voice.



Typical Vega 100 Gateway Applications

Service Provider Applications:

- > Customer premises gateway
- > PSTN gateway

Enterprise Applications:

- > Enterprise VoIP networking
- > Enterprise IP telephony gateway
- > For further details on these applications, please refer to www.vegastream.com

The Vega 100 digital gateway connects digital telephony equipment to IP networks. All Vega 100 gateways provide two E1 or T1 interfaces. Each interface can be independently configured as network or terminal-facing.

The Vega 100 gateways are available in four variants:

- > 23 VoIP channels (24 using CAS), with 2 T1 interfaces
- > 46 VoIP channels (48 using CAS), with 2 T1 interfaces
- > 30 VoIP channels with 2 E1 interfaces
- > 60 VoIP channels with 2 E1 interfaces

The Vega 100 gateway can, therefore, be connected to a PBX and the PSTN simultaneously. This configuration provides:

- > No disruption to the configuration of existing equipment
- > Flexibility and choice for call routing

Open, Non-Proprietary Interfaces

The Vega 100 gateway supports the following signaling schemes:

- > ETSI ISDN
- > NI1, NI2, AT&T 5ESS, DMS100
- > ISO QSIG Basic Call and QSIG feature transparency
- > Channel Associated Signaling (CAS) on the T1 product

All VegaStream gateways can support SIP, H.323 and T.38 fax.

The Vega 100 gateway has proven interoperability with a wide range of existing telecommunications and VoIP equipment. For a full list of certified interop partners, please contact sales@vegastream.com

Vega 100 E1/T1

23-60 Channels Digital

Software release 6

Interfaces

VoIP Protocols

- > H.323 version 4
- > SIP
- > Audio codecs:
 - > G.723.1 (5.3/6.4 kbps)
 - > G.729a (8 kbps)
 - > G.711 (a-law/ μ -law) (64 kbps)
- > Up to 60 VoIP channels

Telephony Interface

Primary Rate ISDN (User configurable NT/TE):

- > 2 x E1
 - Euro-ISDN
 - ISO QSIG
 - QSIG Feature Transparency (H.323)
- > 2 x T1
 - > NI1/NI2
 - > AT&T 5ESS
 - > DMS100
 - > CAS (RBS)
 - E&M wink start
 - Loop start
 - Ground start
 - > ISO QSIG
 - > QSIG Feature Transparency (H.323)
- > Fax Support – up to G3 fax, using T.38
- > Modem Support – up to V.90, using G.711

LAN Interface

10 BaseT, 100 BaseTX, full or half duplex

Features

Identification

- > Caller ID presentation
- > Caller ID screening guarantees connection only from authenticated call sources
- > H.323 gatekeeper registration
- > SIP Registration and Digest Authentication

Billing, Operations and Maintenance

- > HTTP web server – with access to user guide
- > Radius Accounting
- > Remote firmware upgrade:
 - > Auto code upgrade
 - > Auto configuration upgrade
- > SNMP MIB 1&2
- > TFTP/FTP support
- > VT100 – RS232/Telnet

Routing and Numbering

- > Dial Planner – sophisticated call routing capabilities, standalone or gatekeeper/proxy integration
- > Direct Dialing In (DDI)/Direct Inward Dialing (DID)

Call Quality

- > Adaptive jitter removal
- > Comfort noise generation
- > Silence suppression
- > 802.1p/Q VLAN tagging
- > Differentiated Services (DiffServ)
- > Type of Service (ToS)
- > QoS statistics reporting
- > Echo cancellation (G.168 up to 128ms)
- > NAT Traversal

Hardware

Certification

EMC (ClassB)	Safety	Telecoms (ISDN)
EN55022	EN60950	E1: TBR4
EN55024	IEC60950	T1: FCC Part 68
FCC Part 15	UL60950	T1: CS-03
AS/NZS3548	AS/NZS60950	
VCCI		

Environmental

- > 0°-40°C
- > 0-90% humidity (non-condensing)

Front Panel Display

LED:

- > ISDN: DSL Physicals
- > LAN: Speed, Activity, Half/Full Duplex

Management

- > HTTP web server – with access to user guide
- > SNMP MIB 1&2
- > VT100 – RS232C/Telnet

Physical Dimensions

- > 440mm (17.4") x 63mm (2.5") x 330mm (13")
width/height/depth
- > Industrial rackmount: 483mm (19"), 1.5U
- > Weight: 7.5kg

Power

- > 100-240V AC, 47-63 Hz, 1A-0.5A
- > -48V DC also available, 1.2A (Max)

Program Storage

Code and configuration data are stored in FLASH and executed from RAM.

Vega100/Draft3

Contact Details

Email: sales@vegastream.com

Web: <http://www.vegastream.com>

EMEA Office
VegaStream Limited
Berkshire Court
Western Road
Bracknell
Berks RG12 1RE
UK
+44 (0) 1344 784900

USA Office
VegaStream Inc.
10445 Pacific Center Court
San Diego
CA 92121
USA
+1 (877) 834 4470