Product Specifications

EN-C15

15" Flat Panel Computer



Utilizing our standard enclosure housing design, the EN-C15 offers a 15" XGA AMTFT LCD and three touchscreen choices: resistive, near field imaging and infrared. The system includes up to a 1 GHz Pentium III single board computer with up to 256M of DRAM standard, 10/100BaseT Ethernet, three serial ports and a parallel printer interface. A 2.5" hard drive is integral to the system, and a 3.5" floppy drive is accessible through the side of the enclosure.

The rugged, powder-coated aluminum enclosure has several flexible mounting options, including our "mini-mount" and standard mounting arm designs. Like most Computer Dynamics systems, the EN-C15 is available with our Ultra-HiBrite display option that provides true sunlight readability with 900-nit luminance.

Specifications

 Dimensions 18.3" (W) x 13.5" (H) x 4.2" (D) 465 mm x 343 mm x 107 mm -FJ45 15" 1024x768. 256k color Display **AMTFT LCD** Viewing area 12" (W) x 9" (H), 15" diagonal 305 mm x 229 mm • CPU Up to 1 GHz Pentium III Memory Up to 256M EDO DRAM; 512k cache standard Video C&T 65555 LCD/CRT controller Ethernet 32-bit PCI-bus Ethernet, 100BaseT or 10BaseT Hard drive 2.5" hard drive Floppy drive One 3.5" 2.88M floppy drive Serial ports Three serial ports, two configurable as RS-422/485 Parallel port One parallel port; supports SPP/EPP/ECP

PS/2 style connector

90-264 VAC, 47-63 Hz single phase

Options

Keyboard port

Power supply

• Operating temp.

DRAM
UHB
-H9F45 Ultra-HiBrite, 900-nit or greater display
Touchscreen
-CN7 Resistive
-CR7 Infrared
-NN7 Near Field Imaging

0 - 50°C

Ordering Information

 $EN-C15-<\!CPU\text{-speed}>-<\!DRAM>-<\!Display>-Options$

