Hirschmann Automation and Control GmbH






G 20 W 3 F schwarz/black

Industrial Connectors:Rectangular connectors G-series:Cable socket

| Description | Cable socket with PG 7 cable gland and solder contacts |
|--------------------|--|
| Type | G 20 W 3 F schwarz/black |
| Order No. | 932 185-100 |
| Type of contact | forked spring |
| Number of contacts | 2 + PE |
| Cable gland | PG 7 |
| Conductor size | 0.14 - 0.5 mm2 |
| Standard | DIN VDE 0627 / IEC 61984 |
| Housing Color | black |



| Technical data | |
|------------------------------|------------------|
| Rated voltage | AC/DC 250 V |
| Rated current | 6 A |
| Contact resistance | <= 4 mOhm |
| Type of termination | solder |
| Suitable cables | 4 mm to 7.5 mm |
| Material | |
| Contact surface material | Sn |
| Contact bearer material | PA |
| Housing material | PA |
| Environmental conditions | |
| Protection class (IEC 60529) | IP 65 |
| Pollution severity | 3 |
| Temperature range | -40 °C to +90 °C |
| Inflammability class | |
| Housing | 94 HB |
| Contact bearer | 94 HB |
| Approvals | |

| VDE | VDE |
|-----------------------------------|---------------------------------------|
| Packaging unit | |
| Packaging unit | 100 pieces |
| Scope of delivery and accessories | |
| Scope of delivery | 1 cable socket with PG 7 cable gland, |
| | 1 central screw M 3 x 30, |
| | 1 gasket, |
| | not assembled, in polythene bag |
| Accessories to order separately | can be plugged into G 30 E 3 M |