


## Dialogic® Diva® PRI/E1-30 Media Board

Dialogic® Diva® PRI/E1-30 Media Board streamlines network administration without sacrificing performance. It provides a simple, flexible, and cost-effective solution that allows one server to manage the fax, messaging, and remote access needs of an organization.

The Diva PRI/E1-30 is a board that supports one ISDN Primary Rate Interface (PRI) or E1 interface. It is available in a PCI and a PCI Express version.

The Diva PRI/E1-30 enables one server to support up to thirty concurrent communications with a mix of ISDN devices, V.90 modems, GSM mobile phones, and fax machines, making it an excellent choice for medium to large businesses. Because it is based on open-systems architecture, most industry-leading fax, unified messaging, computer telephony integration, and Voice over IP (VoIP) applications integrate easily when the Diva PRI/E1-30 is used.



Features	Benefits
<b>Supports standardized software interfaces</b>	Has the flexibility to work with many different software packages
<b>Multiple Diva PRI/E1-30 boards can be mixed in one system with other Dialogic® Diva® boards</b>	Provides easy upgrade and scalability
<b>Onboard 32-bit RISC CPU, 64 MB RAM and one Digital Signal Processor (DSP) per channel (24 for T1 and 31 for E1)</b>	Removes performance bottlenecks by performing important real-time tasks that would excessively burden the host server on DSP
<b>Group 3 fax, voice mail, and email including DTMS, ECM, RMR, MMR, MH, and 33.6 kbps fax</b>	Suitable for fax and unified messaging applications
<b>Modem up to V.90, V.42bis compression and V.42 error-correction</b>	Ensures fast and reliable transmission for modems and fax
<b>CAPI, TAPI, and Dialogic® Diva® Software Development Kit - Version 4.5 including high level functions</b>	Excellent for Interactive Voice Response (IVR) and contact center application
<b>Implements supplementary services</b>	Ensures that applications are compatible with major PBXs
<b>Echo cancellation (G.168) and voice compression in the DSP</b>	Provides the high performance and high voice quality required for VoIP environments
<b>Conforms to plug and play standards</b>	Easy installation and GUI-based configuration
<b>All multinational ISDN protocols</b>	Ready for worldwide use

## Technical Specifications

### Quick Reference

Voice resources	30
Fax resources	30
Conferencing resources	30
Maximum boards/system	8
CSP	Yes
Form factor	Full-size PCI or PCI Express
Resource bus	PCI rev 2.2 up to 66 MHz or PCI Express 1.0a x1 lane (3.3/12 V)
Connection	RJ-45
Network interface	PRI and E1 (TE and NT Mode)
Signaling	ETSI, NI-1, 4ESS, 5ESS, and all major ISDN protocols; QSIG, T1/RBS, E1/R2, SS7 (ITU-T ISUP), and many more
Operating system	Windows®, Linux. Details at <a href="http://www.dialogic.com/systemreleases">http://www.dialogic.com/systemreleases</a>
Volts	PCI: 3.3 V, 5 V or PCI Express: 3.3 V, 12 V
Required accessories	PRI/E1 cable (RJ-45/RJ-45)

### Hardware

- Active ISDN board for Primary Rate Interface (PRI) and E1 interface
- 1 X RJ-45 connector
- Bus type: PCI rev 2.2 up to 66 MHz or PCI Express 1.0a x1 lane (3.3/12 V)
- 64-bit RISC CPU, 300 MHz, 420 MIPS
- 31 x 33 MHz, 60 MIPS DSP
- 32 MB onboard SDRAM
- High-impedance mode for passive monitoring
- I/O addresses and interrupt are placed by the system
- Plug and play interface
- Scalable to 8 boards per system
- Power down management
- Physical dimensions:
  - 312.00 mm x 106.68 mm
  - 352.17 mm x 126.37 mm (including bracket and retainer)
- Production quality: ISO 9002

### Power Consumption and Environmental

- Power consumption: 0.97 A @ +5 V typical, 2,7 A @ +5 V maximum
- Operating temperature: 10°C to 50°C
- Storage temperature: 0°C to 70°C
- Maximum tolerance in voltage fluctuation: According to the respective PCI or PCI Express specification

### Driver Software

- Supported operating systems: Windows®, Linux. Details at <http://www.dialogic.com/systemreleases>
- D-channel and signaling protocols: ETSI-DSS1 (Euro-ISDN), NI-1 (North America National ISDN 1), 1TR6 (Germany), NET3 (Belgium), VN3/4/6 (France), 4ESS (AT&T), 5ESS (AT&T), 5ESS (Lucent), DMS100 (Nortel), T1 — Robbed Bit Signaling, INS-64 (Japan), INS-1500 (Japan), Australia on-ramp, QSIG, E1-R2 (China), E1-R2 (India), Channelized E1, External Signaling (transparent D-channel), Direct Access Mode (no signaling), Network Termination (NT Mode)
- B-channel protocols: HDLC, Synchronous PPP and MLPPP, X.75 (LAPB), Transparent, X.25, T.30, T.90NL, T.70NL, Rate adaptation (56 kbps), up to V.90, V.42, V.42bis, V.110, V.120, PIAFS
- Application interfaces: Microsoft®: WAN Miniport, COM Port, TAPI, CAPI 2.0, extended CAPI, Dialogic® Diva® API, Component API (VB6 and VB.NET), VoIP (SIP/RTP); Linux: TTY, CAPI 2.0, extended CAPI, Diva API, VoIP (SIP/RTP)
- Diagnostic tools: B-channel and D-channel trace program
- M-adaptor feature (patent pending): Combined Virtual Adapter, Internal Call Transfer, Explicit Call Transfer Emulation

## Technical Specifications (cont.)

### Driver Software (cont.)

- SNMP support: Windows®: v2c; Linux: Net-SNMP v1, v2c and v3
- Dialogic® Diva® SIPcontrol™ Software: VoIP and FoIP (T.38) gateway software. For up to 8 channels per system, the licenses are free of charge. If more than 8 channels are required, licenses can be ordered from Dialogic. Diva SIPcontrol can be downloaded from <http://www.dialogic.com>.

### Fax and Modem Features

- Fax Group 3 support
  - Up to 33.6 kbps with each B-channel (send and receive)
  - Fax compression MH, MR, MMR
  - Error Correction Mode (ECM)
  - Fax polling / fax on demand
  - Fax tone detection
  - Standard, fine, super-fine and ultra-fine resolution
- Support for fax class 1 and 2
- Fax Group 4 support (via third party application)
- Support for FoIP, T.38 (when using SIPcontrol)
  - Up to 33.6 kbps with each channel (send and receive)
- Remote access (via HDLC, V.90, GSM, V.120, X.75)
  - GSM support (V.110) up to 38.4 kbps
  - Communicates with analog modems up to V.90 (up to 56 kbps on each B-channel)

### Voice Features

- DTMF/MF transmission, detection and generation
- Voice Activity Detection (VAD)
- Generic tone detection and generation
- Fax signal detection
- Full-duplex voice, barge-in
- G.168 echo cancellation, up to 128 ms tail length
- Pitch control
- Audio tap
- ISDN supplementary services
  - Number identification services (CLIP, CLIR, COLP, COLR, KEY, MSN, DDI, SUB)
  - Call offering services (TP, CFU, CFB, CFNR)
  - Call completion services (CW, HOLD, ECT)
  - Charging services (AoC)
  - Three-party conference
  - Large conference
- Special Information Tone (SIT) detection
- DTMF clamping and filtering
- Silence detection
- Automatic Gain Control (AGC)
- Cross-board switching
- Onboard switching and conferencing via line interconnect (call tromboning)
- VoIP support (features available when used in VoIP installations)
  - G.711 voice coder (64 kbps,  $\mu$ -law, A-law)
  - G.726 voice coder (32 kbps)
  - GSM voice coder (13 kbps)
  - G.168 echo cancellation, up to 128 ms tail length
  - Adaptive jitter buffer
  - Voice Activity Detection (VAD)
  - Comfort Noise Generation (CNG)
  - Real-time Transport Protocol (RTP) framing

### Safety and EMC

Canada	ICES-003 Class B, CSA 60950-1
Europe	EN60950-1, EN55022, EN55024
United States	FCC Part 15 Class B UL60950-1

## Technical Specifications

### Telecommunications

United States	TIA-968
Canada	CS03

### Approvals, Compliance, and Warranty

Hazardous substances	RoHS compliance information at <a href="http://www.dialogic.com/rohs">http://www.dialogic.com/rohs</a>
Country-specific approvals	Global product approvals database at <a href="http://www.dialogic.com/declarations">http://www.dialogic.com/declarations</a>
Warranty	Warranty information at <a href="http://www.dialogic.com/warranties">http://www.dialogic.com/warranties</a>

## Ordering Information

Dialogic® Diva® Product	Order Code
PRI/E1-30	306-209
PRI/E1-30 – China	306-243
PRI/E1-30 – Australia	306-210
PRI/E1-30 – New Zealand	306-269
PRI/E1-30 PCI Express	306-304

To learn more, visit <http://www.dialogic.com>

### Dialogic Corporation

9800 Cavendish Blvd., 5th floor  
Montreal, Quebec  
CANADA H4M 2V9

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH PRODUCTS OF THE DIALOGIC CORPORATION (“DIALOGIC”). NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN A SIGNED AGREEMENT BETWEEN YOU AND DIALOGIC, DIALOGIC ASSUMES NO LIABILITY WHATSOEVER, AND DIALOGIC DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF DIALOGIC PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHT OF A THIRD PARTY.

Dialogic products are not intended for use in medical, life saving, life sustaining, critical control or safety systems, or in nuclear facility applications.

Dialogic, Diva and SIPcontrol are either registered trademarks or trademarks of Dialogic Corporation or its subsidiaries. Dialogic's trademarks may be used publicly only with permission from Dialogic. Such permission may only be granted by Dialogic's legal department at the address listed above. Any authorized use of Dialogic's trademarks will be subject to full respect of the trademark guidelines published by Dialogic from time to time, and any use of Dialogic's trademarks requires proper acknowledgement.

Microsoft and Windows are registered trademarks of Microsoft Corporation in the United States and/or other countries. Other names of actual companies and products mentioned herein are the trademarks of their respective owners.

Dialogic encourages all users of its products to procure all necessary intellectual property licenses required to implement their concepts or applications, which licenses may vary from country to country. In the United States, the use of the Dialogic® Diva® digital board to route facsimile transmissions using DID is likely to infringe certain claims of U.S. Patent Nos. 5,488,651 and 5,291,546 owned by Cantata Technology Inc.

None of the information provided in this datasheet other than what is listed under the section entitled Technical Specifications forms part of the specifications of the product and any benefits specified are not guaranteed.

Dialogic may make changes to specifications, product descriptions, and plans at any time, without notice.

Copyright © 2007 Dialogic Corporation All rights reserved.

08/07 10499-01