

# Network Appliance

Entry Desktop VIA based Network Appliance with 4 FE LAN



## >> Features:

- Supports 4 FE Realtek LAN ports
- Optional Hardware LAN Bypass function on ETH 0 & 1
- Supports 300MHz~1GHz VIA Eden™ EBGA low power processor
- 128MB or 256MB onboard memory
- Mini-PCI slot, Compact Flash socket
- Low power and fanless, Aluminum enclosure

## Specifications

**CPU:** VIA Eden™, 300MHz/1GHz

**Chipset:** VIA PLE133T, 66/100/133MHz FSB

**Memory:** 128MB or 256MB on board

**Network Interface:** Supports 4 x Realtek RTL8100C FE LAN ports

**Expansion Slot:** Onboard Mini-PCI slot

**Storage:** Onboard Type II Compact Flash socket

Internal HDD bay for 1 x 2.5" HDD (optional HDD bracket)

**USB:** One USB 1.1 ports on front panel

**Serial I/O:** One DB-9 console connector on front panel

One COM 2x5 pin connectors on board

**VGA:** Pin header on board

**LED Indicator:** Power/HDD indication LEDs

**Power Supply:** 20W power adaptor

## Environmental/Mechanical:

**Operating Temperature:** 5 ~ 40°C

**Storage Temperature:** -20 ~ 75°C

**Operating Humidity:** 5 ~ 95%

**Dimensions:** 33mm (H) x 156mm (W) x 225mm (D)

**Certification:** CE/FCC

## Ordering Information

### VTC483685

Entry Desk-top, VIA Eden™ 300MHz, 128MB memory, 4 FE LANs, without bypass\*

### VTC483686

Entry Desktop, VIA Eden™ 300MHz, 128MB memory, 4 FE LANs, without bypass\*

### VTC483687

Entry Desktop, VIA Eden™ 1GHz, 256MB memory, 4 FE LANs, without bypass\*

\*Remarks: Bypass function is optional

## Optional Accessories

### HDD Kit

2.5" HDD bracket

