RACK-3030

6U Height 20-Slot Full Size Industrial PC Chassis With Redundant Power Supply



RACK-3030W With 4 x 5.25" Drive Bay



RACK-3030W Tower Stand



ARH-6400F 400W ATX Redundant Power Supply

 Supports redundant power supply ◆ Four reset switches and PS/2 type KBD connectors for quad system applications

◆ Four 9cm cooling fans with filter







400W AT/ATX Power Supply



Internal View

ORDERING INFORMATION

Features: ♦ 6U height

• RACK-3030 C /ACE-940AP: 6U 20-slot rackmount chassis with ACE-940AP power supply

• RACK-3030R C/ARH-6400F: 6U 20-slot rackmount chassis with 400W ATX type redundant power supply

◆ Designed with easy removal of the driver bay

• RACK-3030 C ATX /ACE-840AP: 6U ATX Main board rackmount chassis with ACE-840AP power supply

C Color Code : B = Black; W = White

• SLIDE-18:18" Sliding

SLIDE-24 :24" Sliding

EXTENDER-6:6" extender for 18" or 24"slides

SPECIFICATIONS

- ♦ 6U height 19" Rack mounting chassis
- ◆ Four reset switches and PS/2 type KBD connectors for quad system applications
- ◆ Drive Bays : 7 x 3.5" HDD 2 x 5.25" Drive Bays
- Four 9cm cooling fans with filter on the front panel and two 6cm fans on the both side
- Built-in fan speed sensors board to detect fans speed
- ◆ Designed with anti-vibration card clamp to keep system stable
- ◆ Supports backplane : BP-20S, BP-20SD, BP-20ST, BP-20SQ, IP-19S, IP-18SD, PCI-19S, PCI-18SD, PCI-17SQ, PX-19S, PX-20S, PX-20S2, PXAGP-19S, PXAGP-19S2
- ◆ Supports PS/2 AT/ATX size power supply or 400W redundant power supply
- ◆ Optional Slides: 24" or 18"
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement 17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Colors: Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions: 431(W) x 266.6(H) x 516.7(D)mm; (17" x 10.5" x 20.3")
- ♦ Net/GW (kg): 19/26

Dimensions

