



Specifications

System	
Input Signal	VGA
On Screen Display Control	Brightness, Contrast, Phase, Sharpness, AutoTune, H/V-position
I/O Connector	VGA x 1, USB x 1
OS Support	Windows® XP, Windows® 7, Linux Fedora
Mechanical	
Construction	IP-67 Sealed Aluminum Alloy Chassis
Mounting	VESA 75
Dimension	10.47" x 7.56" x 2.36" (266mm x 192mm x 60mm)
Carton Dimension	13.86" x 12.91" x 7.72" (352mm x 196mm x 328mm)
Gross Weight	6.6 lb (3 kg)
Net Weight	4.4 lb (2 kg)
Environmental	
Operating Temperature	-4°F ~131°F (-20°C~55°C)
Storage Temperature	-22°F ~140°F (-30°C~60°C)
Storage Humidity	10%~95% @ 40°C; non-condensing
Vibration	1 g rms/ 5~500Hz/ Random operation
Shock	15 G peak acceleration (11 msec. Duration)
EMC	CE/FCC Class A, IEC 60945 ed.4
Power Supply	
DC Input	DC 9~30V
LCD	
Display type	8.4" TFT-LCD
Max Resolution	800 x 600
Max. Colors	262K colors
Luminance	450 nits
Viewing Angle	160°(H)/140°(V)
Back Light	LED
Back Light MTBF (hours)	50,000
Touchscreen	
Type	5-wire resistive
Light Transmission	80%
Lifetime (Times)	35 million activations

Features

- 8.4" SVGA TFT (800 x 600), 450 Nits
- IP-65 Water-Proof & Marine IEC60945 ed.4 Compliant
- Anti-Fog Design: LCD+ TS Bonding Technology
- Brightness Adjustment



Ordering Information

- **TF-FOX-81DHTT-A1-1010**
IP65 Display, 8.4", 800 x 600 450nits, Fanless, 9~30V DC in M12 Connector, R-TS

Optional Accessories

- **1757910004**
AC Adapter (100W)
- **1702031802**
AC adapter Power Cord (US type)
- **1702031803**
AC Adapter Power Cord (European type)
- **170203180E**
AC Adapter Power Cord (Japanese type)
- **1709151000**
(TF) EXT VGA Cable, DB15(M), M12 8P(F), 100cm, For FOX-81D
- **1700091001**
(TF) M12 Cable, 9P(F) D-SUB to M12(F), 100cm, For FOX-81D
- **M990FOX001**
(TF) Metal, M12 Waterproof Cap, Ass'y Screw 3-Pin F Connector, to F Pin, for FOX Serial, LTW, LTW12-03BFFA-SL8001