



## Features

- ◆ 19" 4U high, rackmount chassis compliant to EIA RS-310C standard
- ◆ Provides 250W power supply
- ◆ With height adjustable anti-vibration crowbar securing plug-in cards in place
- ◆ One pre-wired PC/AT keyboard connector on front panel
- ◆ 5.25" CD-ROM space x 3, 3.5" FDD space x 1 on front panel; 3.5" HDD space x 1
- ◆ High efficiency ball bearing cooling fan
- ◆ FCC/CE industrial Class A approval

## Specifications

### Chassis

Meets EIA RS-310C 19" 4U high, rackmount standard

### Drive Space

5.25" CD-ROM space x 3, 3.5" FDD space x 1 on front panel; 3.5" HDD space x 1

### Thermal Solution

High efficiency ball bearing cooling fan x 1 or optional x 2

### Altitude

15,000 feet

### Power Supply

250W power supply

### Temperature

0~+50°C (operating); 0~+70°C (storage)

### Humidity

5~95%; non-condensing

### Safety Standard

FCC/CE on chassis and FCC/CE/UL/TUV on power supply

### Dimensions (L x W x H)

51.0 x 43.27 x 17.7 cm

## Ordering Guide

- ◆ **RC-191B**  
19" 4U High, Full-size Rackmount Chassis
- ◆ **RC-191BA-14S**  
RC-191B Chassis w/HPCI-14S B/P, MPI-925A AT P/S
- ◆ **RC-191BB-14S**  
RC-191B Chassis w/HPCI-14S B/P, ZKS-250AE AT P/S

**This datasheet has been downloaded from:**

**[www.EEworld.com.cn](http://www.EEworld.com.cn)**

**Free Download**

**Daily Updated Database**

**100% Free Datasheet Search Site**

**100% Free IC Replacement Search Site**

**Convenient Electronic Dictionary**

**Fast Search System**

**[www.EEworld.com.cn](http://www.EEworld.com.cn)**