



## V5D

### High Performance 6U VMEbus Embedded Computer

#### Features

- Pentium® M processor LV 738 - 1.4 GHz and 2 Mbyte on-chip L2 cache
- 400 MHz Front Side Bus
- 855GME Graphics and Memory Controller Hub
- 6300ESB I/O Controller Hub
- DDR SDRAM: 512 Mbyte or 1 Gbyte with ECC on 266 MHz Memory Bus
- SVGA video - up to 1600 x 1200
- Ultra-DMA100 interface at the backplane
- Optional on-board Type I CompactFlash
- PCI Expansion interface for installing a PMC carrier
- Two Gigabit Ethernet RJ-45 ports
- Serial I/O: COM1—RS-232, COM2—configurable (RS-232/422/485)
- Optional Ultra 16-bit SCSI interface
- 32 Kbyte NVRAM
- PS/2 keyboard/mouse port
- Floppy drive interface
- Two USB 2.0 ports
- IEEE 1284 parallel port
- Temperature sensor
- Real-time clock with on-board battery

#### Benefits

V5D is the next generation in the V5x family of 6U VMEbus Single Board Computers offering an Intel® Pentium® M processor LV 738 that features 90nm technology with processing speed of 1.4 GHz. The Pentium M 738 includes on-chip 32 Kbyte L1 instruction and data caches and 2 Mbyte of L2 cache.

The V5D couples the Pentium M LV 738 with the Intel® 855GME Chipset which includes the 855GME Graphics and Memory Controller Hub (GMCH) and the 6300ESB I/O Controller Hub (ICH). The 855GME GMCH provides a 400 MHz Front Side Bus interface and a memory controller with a 64-bit 266 MHz memory interface that services up to 1 Gbyte of DDR SDRAM. It also includes an internal SVGA video controller with 2D and 3D graphics engines and a 350 MHz 24-bit RAMDAC that can drive an analog CRT monitor at resolutions up to 1600 x 1200.

The 6300ESB I/O Controller Hub provides a 400 MHz System Bus interface and two PCI bus interfaces as well as a USB 2.0 Controller and two Ultra-DMA100 interfaces to the backplane or one IDE backplane interface with an optional on-board Type I CompactFlash card (replaces FDOC which was used on prior generation of V5X boards).

The V5D features high-speed LAN connectivity with two Gigabit Ethernet ports on the front panel, and an Ultra 16-bit SCSI interface and floppy drive interface at the backplane.

The V5D includes a PC87417 LPC Server I/O, which provides two serial I/O ports, a parallel port, and a PS/2-style keyboard/mouse port to the front panel. COM1 is configured for RS-232 operations while COM2 is user-configurable to RS-232/422/485.

The V5D implements the Tundra® Universe IID VMEbus Bridge for handling data transfers to and from the VMEbus backplane. The Universe IID supports VITA 1.1 VME64x bus transfers and supports master or slave operation.



# V5D High Performance VMEbus Embedded Computer

## Specifications

### Processor

- Intel® Pentium® M processor LV 738 with core processing speed of 1.4 GHz
- High performance, low power consumption, Intel Architecture (IA)
- 32 Kbyte L1 instruction and data caches
- 2 Mbyte L2 on-chip cache
- 400 MHz Front Side Bus interface through the 855GME GMCH

### Memory - DDR SDRAM

- 512 Mbyte or 1 Gbyte of soldered DDR266 SDRAM (PC2100)
- 64-bit 266 MHz Memory Bus (72-bit with ECC)

### Flash ROM

- 1 Mbyte Firmware Hub (FWH) for BIOS code
- Multiple levels of write-protection

### Video

- Integrated SVGA video controller through 855GME Graphics and Memory Controller Hub
- Supports render core and display core frequencies up to 200 MHz
- 2D and 3D graphics engines
- 350 MHz 24-bit RAMDAC to drive analog CRT monitor at 1600 x 1200 pixel resolution

### PCI Bus

- Dual PCI interface through the 6300ESB ICH
- PCI Bus 2: 32-bit, 33 MHz—VME Backplane Bridge, Ultra- SCSI Controller, PCI Expansion site
- PCI Bus 1: 64-bit, 66 MHz—dedicated to Ethernet Controller

### PCI Bus Expansion

- JX1/JX2 Mictor connectors on 32-bit/33MHz PCI Bus 0
- Up to three PMC sites on PMC carrier cards attached to expansion site (TPMCC)

### VME Backplane Bridge

- Universe IID VMEbus Bridge
- VITA 1.1 VME64x Bus standard interface
- Master or slave operation
- Full system controller functionality

### Ethernet

- Intel® 82546GB Dual Port Gigabit Ethernet Controller with integrated MAC and PHY
- Two RJ-45 connectors on front panel

### Serial Ports

- COM1: full-duplex RS-232 interface
- COM2: configurable to full-duplex RS-232, async. RS-422, or half-duplex RS-485 interface

### EIDE Interface

- Two Ultra-DMA33/66/100 Bus interfaces at backplane (supports two external IDE drives) or one IDE backplane interface with optional on-board Type I CompactFlash module

### SCSI Interface

- Ultra SCSI Interface (optional)
- 16-bit interface at backplane

### Floppy Drive Interface

- Floppy drive interface at backplane through PC87417 LPC Server I/O

### USB I/O

- Two 2.0-compatible USB ports (front and rear I/O)
- Integrated USB Controller through the 6300ESB ICH

### Parallel Port

- IEEE 1284 Parallel port at the front panel from the PC87417 LPC Server I/O

### Keyboard/Mouse Port

- PS/2-style keyboard/mouse port at the front panel from the PC87417 LPC Server I/O

### NVRAM

- 32 Kbyte NVRAM

### RTC

- Real-time clock feature for timekeeping functions
- On-board Lithium Battery backup

### Temperature Sensor

- CPU die and ambient temperature
- Software readable from -55°C to +125°C

### Power Requirements

- +5 V, (±12V provided to PCI expansion only)

### Power Consumption

- Peak:\* 30 W
- Max. sustained:\* 26 W
- Idle:\*\* 23 W
- Inrush: 32 W
- VBATT: < 0.1 mW
- Total: TBD

\*Calculated values

\*\*Measured with Windows XP active

## Input/Output

I/O	Front Panel	P2	On-board	VME-TB51
COM1: RS-232 2	DB9			
COM2: RS-232 2/422/485	DB9			
Compact Flash			2 x 2.5	
LPT	Mini-DB 25			
Ethernet (ET H1, ET H2)	RJ-45			
PS/2 KBD/MSE	Mini-DIN (6-pin)			
PCI Expansion			2x (2 x 40)	
PIDE		√		2 x 20
SIDE		√		2 x 20
SVGA	HD-15			
USB0	Type A			
USB1		√		Type A *
SCSI (16-bit)		√		68 *
SCSI (8-bit)		√		DB50 / 2 x 25
Floppy Drive interface		√		2 x 17

\* Rear panel connectors, DB50— 8-bit SCSI, DB68 —16-bit SCSI, Type A— USB

### Mechanical

- VITA 1.1 VME64x Bus compliant (3-row or 5-row backplane connectors)
- VITA 1/IEEE 1101.1 air-cooled 6U form factor
- 233 x 160 x 20 mm
- Weight - 1.25 lbs

### MTBF

- Calculations are available in accordance with MIL-HDBK-217. Please contact GE Intelligent Platforms for latest values.

### Safety

- Designed to meet standard UL1950/60950

### Emissions

- Designed to meet FCC Part15, Class A certification

### Humidity (non-condensing)

- Operating: 5-95% @ 40°C
- Storage: 5-95% @ 40°C

### Altitude

- Operating: 4.5 km (15,000 ft.)
- Storage: 6 km (20,000 ft.)

### Shock

- C-Style: 20 g / 11 ms, 3 axes, up & down, 3 hits/direction

### Vibration

- C-Style: 0.04 g<sup>2</sup> / Hz @ 5 to 100 Hz, 60 minutes each axis

### Temperature

- Range: Standard
- Operating: 0°C to +70°C
- Storage: -40°C to +85°C



# V5D High Performance VMEbus Embedded Computer

## About GE Intelligent Platforms

GE Intelligent Platforms, a General Electric Company (NYSE: GE), is an experienced high-performance technology company and a global provider of hardware, software, services, and expertise in automation and embedded computing. We offer a unique foundation of agile, advanced and ultra-reliable technology that provides customers a sustainable advantage in the industries they serve, including energy, water, consumer packaged goods, government and defense, and telecommunications. GE Intelligent Platforms is a worldwide company headquartered in Charlottesville, VA and is part of GE Home and Business Solutions. For more information, visit [www.ge-ip.com](http://www.ge-ip.com).

## GE Intelligent Platforms Contact Information

Americas: **1 800 433 2682** or **1 434 978 5100**

Global regional phone numbers are listed by location on our web site at [www.ge-ip.com/contact](http://www.ge-ip.com/contact)

[www.ge-ip.com](http://www.ge-ip.com)



©2010 GE Intelligent Platforms, Inc. All rights reserved.  
All other brands or names are property of their respective holders.  
Specifications are subject to change without notice.



01.10 GFA-784A