

# FieldPAC<sup>™</sup> Technical Specifications

<b>CPU TYPE</b>	Pentium® MMX 166, 200 & 233 MHz.
<b>DRAM</b>	32 MB Std. 64 MB and 128 MB Opt.
<b>EXTERNAL L2 CACHE</b>	512 KB
<b>HARD DISK DRIVE</b>	2.5" 2 GB Std. — 4 GB Opt.
<b>FLOPPY DRIVE</b>	3.5-inch, 1.44 MB
<b>CD-ROM DRIVE</b>	Multi-Speed (24X Min.) CD-ROM
<b>PCMCIA/CARDBUS SLOTS</b>	Two Type II/One Type III
<b>DISPLAY SYSTEM</b>	14.1" Active Matrix Color TFT — 1024 x 768
<b>EXTERNAL DISPLAY SUPPORT</b>	640 x 480, 800 x 600, and 1024 x 768 Simultaneous External Display at 1024 x 768
<b>INTERFACES</b>	Two RS-232 Ports — 16550 UARTs Bi-directional, Enhanced Parallel Port
<b>KEYBOARD</b>	AT Compatible, 104/105-Key Sealed VersaPad Pointing Device
<b>SYSTEM INPUT POWER</b>	90 - 265 VAC, 47 to 63 Hz 12 VDC Via External Adapter
<b>EXPANSION</b>	One Open Slot — Full-Length, Full-Height User Definable ISA or PCI PCMCIA/CardBus — Two Type II/One Type III
<b>APPROVALS</b>	Safety UL, TÜV Emissions CE Mark, FCC Class A
<b>OPERATING TEMPERATURE</b>	0° to 50° C
<b>WEIGHT</b>	Basic System 15 lb. 6.8 kg.
<b>DIMENSIONS</b>	Height 3.0"    7.62 cm.(Display Closed) Height 16.0"   40.60 cm (Display Open) Depth 13.0"   33.00 cm. Width 18.0"   45.70 cm.

**For more information on these or any other Dolch product,**

---

[sales@voxttechnologies.com](mailto:sales@voxttechnologies.com)

**Vox Technologies +1-972-234-4343**