


➤ EPIC/CE



- Intel® ULV Celeron® 400 or LV Celeron® 733MHZ, 815 chipset
- PC/104 and PC/104plus expansion
- DUAL Ethernet
- 6x USB 2.0
- 4x COM, 21x GPIO
- 2x 24bit LVDS & DVO
- On-chip Graphics & Sound

Product Overview

The advantage of EPIC/CE is the combination of full PC/104 compliant IO expansion capacity with motherboard style frontside feature access. That way the CPU board itself, underneath the added IO, arrives with almost all front plate accessible functionality – avoiding cable handling & cable cost.

Each EPIC is a member of the EPIC board family.

EPIC modules from Kontron are characterized by the same pinout and interface for PC/104 & PC/104plus, 4xUSB, DUAL LAN, Keyboard/Mouse-socket, Compact-Flash™, CRT, LPT, Sound and COM1. This family feature allows to re-use chassis and maximizes design re-use.

This EPIC/CE hosts an Intel® ULV/LV Celeron® processor at 400/733 MHz. A SDRAM-SO-DIMM socket for up to 512 MByte allows the use of standard notebook memory and ATX power supply (or 5V only) is as well a standard feature. These homogeneous features facilitate easy upgrades within the EPIC product family.

The graphic controller is included in the chipset, that performs with up to 12 MByte UMA. Connection of displays is simplified when using these units which are complete with a JILI-Interface (JUMPTec® Intelligent LVDS Interface).

JILI automatically recognizes which display is connected and independently sets all video parameters.

All JREx are plug-and-work enabled to further reduce time-to-market.

Technical Information

EPICsized Single Board Computer

- **Processor:** Intel® ULV Celeron®, 400 MHz
LV Celeron® 733 MHz
- **Chipset:** Intel® 815, ICH4
- **On-chipGraphics:** Intel® Graphics engine,
up to 12 MByte UMA VRAM
2x 24 Bit LVDS
- **Graphicinterfaces** DVO, CRT and LCD (JILI)
- **RAM** 1x SDRAM-SODIMM
- **COM** 4x (1x RS232 DSUB, 3x RS232
with 1 x as RS422/485 internal)
- **GPIO** 21x (2mm DIN pins internal)
- **USB2.0** 6x (4x ext. overcurr. prot., 2x int.)
- **Ethernet** 2x 10/100 BaseT
- **Extensions** PC/104 (ISA) &
PC/104plus (PCI)
- **Sound** Jack-plugs (Line In/Out/Mic), 5.1 Sound
- **CompactFlashSocket** Type 1

- **EIDEharddisk interface** UDMA-133
- **FloppyDisk interface** ✓
- **LPTPrinter interface** ✓
- **Keyboard/Mouse** ✓ (PS2)
- **LAN/USBBoot** ✓
- **DarkBoot** ✓
- **Watchdog:** ✓
- **HWmonitor** ✓
- **RealTime Clock** ✓
- **Dimensions:** 115x165 mm
- **PowerSupply** ATX or 5V power supply

Plug 'n Play compatible to any other EPIC SBC and therefore exchangeable

- **Reset/ATX feature button** ✓ (8pin/2,54 mm)
- **Temperature (*):** Operation: 0° to 60° C
Storage: -10° to 85° C
- **Max. humidity:** Operation: 10% to 90%
Storage: 5% to 95%

(*) Ask about wider temperature ranges

Ordering Information

Article	Part.-No.	Description
EPIC/CE	04001-0000-40-1	Intel®ULV Celeron®processor with 400MHz, fan, ATX
EPIC/CE	04001-0005-40-1	Intel®ULV Celeron®processor with 400MHz, fan, 5V
EPIC/CE	04001-0000-73-1	Intel®LV Celeron®processor with 733MHz, fan, ATX
EPIC/CE	04001-0005-73-1	Intel®LV Celeron®processor with 733MHz, fan, 5V
		Longevity secured - will be available as lead free!
	common features:	Intel® 815/ICH4 chipset, DVO/VGA/LCD on-chip, 2xLAN,4x COM, 6xUSB, 21xGPIO, LPT, IDE, PC/104plus extension. SDRAM-DIMM-socket, Compact-Flash™ socket. Sound

Corporate Offices

Europe, Middle East & Africa

Kontron AG
Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 219
sales@kontron.com

North America

Kontron America Corporate Office
14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
sales@us.kontron.com

Asia Pacific

Kontron Asia Inc.
4F, No. 415, Ti-Ding Blvd.
Sec.2, NeiHu District
Taipei Taiwan 114
Tel.: +886-2-2799-2789
Fax: +886-2-2799-7399
sales@kontron.com.tw

Kontron Embedded Modules

Brunnwiesenstr. 16
94469 Deggendorf
Germany
Tel.: +49 (0)991/ 370 24-100
Fax: +49 (0)991/ 370 24-333
sales@kontron.com