







### **Features**

- ♦ 19" 2U high, rackmount chassis compliant to EIA RS-310C standard
- Detachable card cage for easy installation and maintenance
- ♦ Provides 6-slot PICMG1.3 full-size or PICMG Bus backplane (PCI x 3, ISA x 3), 250W AT/ATX power supply
- ♦ External: 5.25" space x 1 + 3.5" space x 1 Internal: 3.5" space x 1
- ♦ 8cm ball bearing cooling fan x 2
- Dual lockable latch doors
- ◆ FCC/CE industrial Class A approval

# Specifications

Meets EIA RS-310C 19" 2U high, rackmount standard; heavy-duty steel, SECC 1.2t (Japan)

External: 5.25" space x 1 + 3.5" space x 1

Internal: 3.5" space x 1

**Front Panel** 

Power switch, reset button; power and HDD active LED

8cm ball bearing cooling x 2 fan and removable air filter

15,000 feet

**Power Supply** 

250W AT or ATX power supply

 $0\sim+50^{\circ}$ C (operating);  $0\sim+70^{\circ}$ C (storage)

5~95%; non-condensing

**Safety Standard** 

FCC/CE on chassis and FCC/CE/UL/TUV on power supply

**Dimensions (L x W x H)** 

48.0 x 42.7 x 8.82 cm

## Ordering Guide

19" 2U High, Full-size Rackmount Chassis (notify AT or ATX)

19" 2U High, Full-size Rackmount Chassis w/PCIE-5SD B/P

RC-721B Chassis w/HPCI-6SD2 B/P

RC-721B Chassis w/HPCI-6SD2 B/P, ZKS-250AE AT P/S