IPC-603MB

Ultra Compact 2U Rackmount Chassis with Front-accessible I/O Cabling



Features

- The best embedded computing system for machinery applications
- Ultra compact 2U-high chassis supporting ATX/mATX motherboard
- Streamlined in-chassis airflow design supporting LGA775 Pentium® 4 CPU up to 3.8 GHz with suggested CPU cooler
- All I/O interfaces are in the front
- Shock resistant disk drive bay design to hold one slim CD-ROM and one internal 3.5" HDD
- Specially designed riser card supporting up to three half-sized PCI cards
- Equipped with 1U-high 300W ATX PFC power supply
- · Easy-to-replace air filters

 ϵ


Specifications

		Front-accessible	Internal	
Drive Bay	Slim CD-ROM	1	-	
	3.5"	-	1	
Cooling	Fan	2 (47 CFM each)		
	Air Filters	3 (85 x 80 mm)		
Miscellaneous	Notification LEDs	PWR & HDD (internal)		
	Riser card (9696070000)*	Supports up to three half-sized PCI add-in cards		
Environment		Operating	Non-Operating	
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-20 ~ 60 °C (-4 ~ 140 °F)	
	Humidity	10 ~ 85% @ 40° C, non-condensing	$10 \sim 95\%$ @ 40° C, non-condensing	
	Vibration (5 ~ 500 Hz)	1 Grms	2 G	
	Shock	10 G (with 11 ms duration, half sine wave)	30 G	
	Acoustic Noise	Less than 52 dB sound pressure at 5 \sim 28 °C (41 \sim 82 °F)		
	Altitude	0 to 3,048 m (0 ~ 10,000 ft)		
Physical Characteristics	Dimensions (W x H x D)	482 x 88 x 310 mm (19" x 3.46" x 12.2")		
	Weight	8 kg (17.6 lb)		

^{*} The riser card is specially designed to support Advantech AIMB-500 and AIMB-700 series motherboards. There might be compatibility issues with other vendor's motherboards.




The front view of IPC-603MB



3-slot PCI riser card to support 3 half-sized PCI cards

The inside view of IPC-603MB



Power supply

Part Number	Specifications Specification Specificatio					
	Watt	Input	Output	Mini-load	Safety	MTBF
1757000160 (ATX, PFC)	300 W	AC 100 ~ 240 V (full-range)	+5 V @ 25 A, +3.3 V @ 14 A +12 V @ 16 A, -12 V @ 1 A -5 V @ 0.5 A, +5 Vsb @ 2 A	+5 V @ 3 A, +12 V @ 2 A -5 V @ 0.05 A, -12 V @ 0.05 A +3.3 V @ 1A, +5 Vsb @ 0.1 A	UL/TUV/CB/CCC	100,000 hours @ 25 °C

Accessories

Part Number	Description
96SDVR-8X-I-QS-B	Black slim-type DVDRW-ROM 24X/8X/24X
96SCD-24X-I-OD-B	Black slim-type CD-ROM 24X
1750000257	2U-high Socket 478 P4 CPU cooler up to 3.2 GHz (89 W)
1750000332	2U-high LGA775 P4 CPU cooler up to 3.8 GHz
1759200650	Fan 80 x 80 x 25 mm
1990001176	Fan filter 80 x 85 x 5 mm

Ordering Information

Part Number	Power Supply	Riser Card	Motherboard	Regulation
IPC-603MB-30Z	1757000160	9696070000 (for AIMB series only)	Not included (for AIMB series only)	CE