

MB-i7413

Micro ATX Pentium 4/Celeron FSB800Mhz Industrial Motherboard with 4 x COM,SATA, Audio & Dual LAN



Features

- * Support Intel Pentium 4 CPU, Supporting Hyper-Threading Technology with FSB533/800 Mhz
- * Support Intel Pentium 4 CPU with FSB400Mhz System Bus
- * Dual Channel 4 x 184Pin DIMM Slot up to 4GB DDR 400/333/266 SDRAM
- * Dual Intel 10/100Mbps LAN
- * 3 x RS-232, 1 x RS232/422/485
- * AGP 4X/8X Slot
- * 8 x USB2.0

System

Model	MB-i7413VL	MB-i7413VL2
CPU	Intel Pentium 4 socket 478 CPU up to 3.4Ghz	
	FSB400/533/800Mhz	
Cache	2nd level 1MByte	
Memory	4 x 184Pin DIMM up to 4GB DDR SDRAM	
Chipset	Intel 865GV + ICH5	
BIOS	Phoenix-AWARD PnP Flash BIOS	
ATA / IDE	2 x Ultra DMA100, Support 4 IDE drives	
SATA / IDE	2 x Serial ATA 150, Support 2 IDE drives	
Expansion Bus	1 x 4X/8X AGP Slot	
	3 x 32bit/33Mhz PCI Slot	
Watchdog Timer	255-level Reset	

I/O

Model	MB-i7413VL	MB-i7413VL2
Serial port	1 x DB9 port (COM1)	1 x DB9 port (COM1)
	1 x RS-232 port (COM2)	2 x RS-232 ports (COM3/4)
		1 x RS-232/422/485 port (COM2)
Parallel port	SPP/EPP/ECP mode	
Floppy	Support 2 Floppy disk drives	
IrDA	None	1 x SIR IrDA 1.1 compliant
USB port	6 x USB 2.0 compliant	8 x USB 2.0 compliant
Digital I/O	None	8bit Digital Input/Output
KB & MS	1 x PS2 K/B and Mouse	

Ethernet

Model	MB-i7413VL	MB-i7413VL2
Chipset	Intel 82562EZ 10/100base-T	Dual 1000base-T
		(Intel 82562EZ + 82551QM)
Optional	Dual 1000base-T(Intel 82547GI + 82541PI)	

Audio

Codec / Interface	Realtek ALC655 AC97 Codec, support Mic-in / Line-in / Line-out
-------------------	----------------------------------------------------------------

Display


Graphics Chipset	Intel 865GV Extreme Graphics2 Engine up to 64Mbyte UMA Video RAM
Graphics Interface	CRT support QXGA up to 2048 x 1536
SCDB-1180 (Optional)	LCD support 18/24/36/48bit LVDS up to 1600 x 1200 LCD support 18/24/36/48bit TTL up to 1600 x 1200
	TV-out support NTSC/PAL up to 1024 x 768
SCDB-1181 (Optional)	DVI support 12 bit up to 1024 x 768
	TV-out support NTSC/PAL up to 1024 x 768

Others

Hardware Monitor	Voltage and Temperature Sensing
	Power management support for ACPI 1.1

Mechanical & Environmental

Operating Temperature	0 ~ 60°C
Operating Humidity	0% ~ 90%, Non-condensing
Dimension (W x L)	244 x 244 mm (9.6" x 9.6")



Ordering Information

MB-i7413VL	Micro ATX, Intel Pentium 4/Celeron FSB800Mhz Industrial Motherboard with 2 x COM, SATA, Audio, Single Fast LAN
MB-i7413VL2	Micro ATX, Intel Pentium 4/Celeron FSB800Mhz Industrial Motherboard with 4 x COM, SATA, Audio, Dual Fast LAN
MB-i7413VLG2 (optional)	Micro ATX, Intel Pentium 4/Celeron FSB800Mhz Industrial Motherboard with 4 x COM, SATA, Audio, Dual Gigabit LAN
Cable Kit	CBK-09-7412-00

Page 5-0