



A8N-VM CSM

- Support AMD Socket 939 Athlon 64FX / Athlon 64 X2 / Athlon 64
- NVIDIA GeForce 6150 + nForce 430
- Dual-channel DDR400
- PCI Express architecture
- Integrated GeForce6 GPU
- Dual VGA Output:DVI-D & RGB
- NVIDIA Gigabit LAN with NVIDIA ActiveArmor Firewall
- 4 x SATA II (RAID 0, RAID 1, RAID 0+1, RAID 5)
- 1394a Support
- High Definition Audio

[Vergroting](#)
[Nieuws](#)

■ Specification

| | |
|--------------------------|--|
| CPU | Socket 939 for AMD Athlon 64FX / Athlon 64 X2 / Athlon 64 - AMD64 architecture enables simultaneous 32- and 64-bit computing AMD Cool 'n' Quiet Technology |
| Chipset | NVIDIA GeForce 6150 + nForce 430 |
| Front Side Bus | 2000 / 1600 MT/s |
| Geheugen | 4 x 184-pin DIMM Sockets support max. 4GB DDR400/DDR333/DDR266 ECC/ non-ECC, un-buffered memory Dual Channel Architecture |
| VGA | Integrated GeForce 6 GPU High Definition Video Processing, max. resolution 1920 x 1440 for RGB display Dual VGA output: DVI-D and RGB (*DVI-D can not be converted to output RGB signal to CRT.) |
| Uitbreidingsleuven | 1 x PCI Express x16 1 x PCI Express x1 2 x PCI |
| Opslag/RAID | 4 x Serial ATA I/II 3Gb/s: : RAID 0, RAID 1, RAID 0+1, RAID 5 2 x UltraDMA 133/100/66/33 NVIDIA MediaShield storage management technology |
| LAN | Integrated Gbit MAC with Marvell 88E1111 external PHY - NVIDIA ActiveArmor Firewall for secure networking |
| Audio | High Definition Audio, ADI AD1986A 5.1channel CODEC Support Jack-Sensing and S/PDIF out interface |
| IEEE 1394 | VIA 6037 IEEE 1394 controller, supports 2x1394 ports |
| USB | 8 USB2.0 ports |
| Speciale mogelijkheden | ASUS Q-Fan ASUS C.P.R.(CPU Parameter Recall) ASUS EZ Flash* ASUS CrashFreeBIOS2* ASUS MyLogo2 SFS (Stepless Frequency Selection) from 200MHz to 240MHz at 1MHz increment (*EZ Flash & CrashFreeBIOS2 only support VGA/RGB output, but does not support VGA/DVI-D output.) |
| Achterpaneel I/O-poorten | 1 x VGA/DVI out 1 x VGA/RGB out 4 x USB 1 x IEEE 1394 1 x 5.1 channel Audio I/O 1 x RJ45 1 x PS/2 Mouse 1 x PS/2 Keyboard 1 x Parallel |
| Interne I/O-connectoren | 2 x USB 2.0 connector supports additional 4 USB 2.0 ports 1 x IEEE 1394 connector 1 x TV out connector 1 x S/PDIF output connector Front panel audio connector CPU Fan / Chassis Fan connectors Chassis Intrusion connector CD audio-in connector 24-pin ATX power connector 4-pin ATX 12V Power connector 1 x COM connector |
| Support CD | Drivers ASUS PC Probe II ASUS LiveUpdate Utility AMD Cool 'n' Quiet Utility Anti-virus software (OEM version) |
| Accessories | 1 x Ultra DMA 133/100/66 cable 2 x SATA cable 2 x SATA power cable 1 x IDE cable 1 x FDD cable 1 x I/O Shield User's manual |
| BIOS | 4Mb Flash ROM, AMI BIOS, PnP, DMI2.0, WfM2.0, SM BIOS 2.3, ACPI 2.0 |
| Form Factor | uATX Form Factor, 9.6"x 9.6"(24.5cm x 24.5cm) |