



FSCA Type



FSCT Type

UL Standard: 514A  
 CSA Standard: C22.2 No. 18  
 Fed Spec: W-C-586D  
 NEMA: FB-1

Listed File No. E 3397

Certified File No. LR11852

**FEATURES-SPECIFICATIONS**

**Applications**

- Accommodates wiring devices and provides opening to splice, tap, or pull conductors
- Provide access to conductors for maintenance and future system changes

**Features**

- Tapered threads (NPT with integral bushings)
- Internal grounding screw
- Available single and two gang styles
- Suitable for use in wet locations when used with gasket covers
- Cast iron is suitable for concrete use
- For use with FS-style covers see pages F41-F43

**Material/Finish**

**Copper-free Aluminum**

(less than 4/10 of 1%)

- Electrostatically applied powder coating


**Duraloy Iron**

- Tri-coat finish of electrozinc, chromate sealant, and electrostatically applied powder coating


FSCA TYPE CAST DEVICE BOX – SHALLOW										
CATALOG NUMBER		HUB SIZE	DIMENSIONS							VOLUME CU. IN.
KILLARK ALUM.	DURALOY IRON		A	B	C	D	E	F	G	
FSCA-1	FSCA-1M	1/2"	7/8" (22)	2" (51)	11/16" (17)	4-5/8" (117)	2-7/8" (73)	—	—	18.0
FSCA-2	FSCA-2M	3/4"	7/8" (22)	2" (51)	11/16" (17)	4-5/8" (117)	2-7/8" (73)	—	—	18.0

FSCT TYPE CAST DEVICE BOX – SHALLOW										
CATALOG NUMBER		HUB SIZE	DIMENSIONS							VOLUME CU. IN.
KILLARK ALUM.	DURALOY IRON		A	B	C	D	E	F	G	
FSCT-1	FSCT-1M	1/2"	7/8" (22)	2" (51)	11/16" (17)	4-5/8" (117)	2-7/8" (73)	—	—	18.0
FSCT-2	FSCT-2M	3/4"	7/8" (22)	2" (51)	11/16" (17)	4-5/8" (117)	2-7/8" (73)	—	—	18.0

**Dimensions**



FSCA



FSCT