



Optima

Universal Programming System

1-800-3-DATAIO
www.dataio.com



- **Compact hardware design complete with interchangeable 48-pin DIP TOP.**
- **48 universal analog/digital pindrivers – Expandable to 84 pindrivers.**
- **Universal device support for memory, microcontroller and logic devices.**
- **Industry-standard TaskLink for Windows software enhances the quality and efficiency of your device programming operation.**
- **Partnerships with major semiconductor companies ensure a wide range of device support, especially for new devices.**
- **Low-voltage programming supports voltages down to 1.8 volts allowing you to program the newest devices on the market.**
- **Common architecture with the Data I/O® Multisyte™ and PS2/300™ allows a customer to migrate programming processes into the manufacturing environment.**
- **The addition of production-quality TOPs provides flexible, highly reliable support for SOICs, TSOPs, PGAs, QFPs, µBGAs and other packages.**
- **Adding FlashTOPs™ turns this single-site programmer into a four site Flash Memory programmer.**
- **Comes standard with one year of device support updates.**

The Optima™ family of device programmers combines high-speed analog/digital design techniques with proven algorithms to deliver the highest quality programming results. Interchangeable TOPs and upgradeable pin drivers give you more flexibility for today's as well as tomorrow's programmable devices.

Flexible, Reliable Support for the Latest Devices and Packages

The Optima provides universal, highly flexible device programming support for today's memory, microcontroller and logic devices from all the major manufacturers, from Altera to Xilinx. It comes standard with the TOP 48 which can support all DIP devices up to 48 pins. With additional TOPs and "DIP-To-Package" adapters, all other package styles can be supported.

With TOPs support, you can always be sure your devices are programmed reliably — no matter what package you use. The innovative TOPs design minimizes lead lengths between the programming pindrivers and the devices being programmed, ensuring clean signals, lead coplanarity, and optimum programming accuracy and repeatability.


Easy, Efficient Control with TaskLink for Windows

To streamline system setup and control, the Optima programmer features powerful TaskLink™ for Windows® software. TaskLink's intuitive user interface guides you through every programming step, from device selection to data file download and parameter setup. You can also pre-configure programming parameters for specific jobs and save them as Task or Kit files, making repeat programming easier and more efficient. TaskLink can even capture production statistics, helping you analyze and improve the quality and productivity of your programming processes.

Optima Light

For devices up to 48 pins, the lower cost Optima Light offers all of the same functionality of Optima. It can be upgraded to Optima at any time.

For complete information on any Optima universal programming system, please visit our Web site or contact your local Data I/O sales representative.



Optima

Universal Programming System

1-800-3-DATAIO
www.dataio.com



Specifications

Device Support

- Memory: Flash, PROMS, EPROMS, EEPROMS
- Logic: FPGAs, PLDs, PALs, EPLDs, CPLDs
- Microcontrollers
- Low-voltage support

Package Support

- 48-Pin DIP socket standard
- PLCC, SOIC, TSOP, PGA, QFP, μ BGA and others with optional TOPs or adapters

(Optima Light only supports devices up to 48 pins)

Standard Features/Accessories

- TaskLink for Windows
- One year of software and device support updates
- 12 month warranty
- Power supply

Optional Features

- Various TOPs and adapters
- Data I/O or third party "DIP-To-Package" adapters
- Optima Light upgrade software

System Requirements

- Microsoft Windows 95B, 98, Windows NT, 2000
- 75 MB hard disk space
- CD Rom drive
- Parallel port
- Mouse
- VGA monitor

Operational Requirements

- Operating voltages: 100-250 VAC \pm 10%
- Frequency range: 50-60 Hz
- Power consumption: 25 VA max

Size

- 8.3 \times 3.5 \times 2.8 inches (21 \times 9 \times 7 cm)

Weight

- 3.5 lbs. (1.6 kg)

Data I/O Corporation: 10525 Willows Road NE, P.O. Box 97046, Redmond WA 98073-9746, USA
(425) 881-6444 · (800) 332-8246 · <http://www.dataio.com>

Data I/O GmbH: Lochhamer Schlag 5, 82166 Graefelfing, Germany · 089 858580 · <http://www.dataio.de>

Data I/O Japan: Saisho Building 7F, 8-1-14, Nishigotanda, Shinagawa-ku, Tokyo 141-0031, Japan · 03-3779-2151

Data I/O Canada: 6725 Airport Road, Suite 102, Mississauga, Ontario L4V 1V2 · (905) 678-0761

®™ Data I/O and UniSite are registered trademarks of Data I/O Corporation. TaskLink, Octal, Quad, Dual, Optima and Plus 48 are trademarks of Data I/O Corporation. Data I/O Corporation acknowledges the trademarks of other organizations for their respective products or services mentioned in this document. Specifications subject to change without notice.

©2002 Data I/O Corporation