

## Control Panels

### Type CP - Standard Contactor System

#### APPLICATIONS

Designed to fulfill the control requirements of most heating process heating applications where rugged reliable service with additional safety contactor backup protection is desired.

#### STANDARD FEATURES

Heavy gauge gasketed enclosure finished in grey acrylic resin with integral "Dead Front" switch, "Off-On" selector switch, "Power-On" pilot light, illuminated reset button, and digital indicating electronic temperature controller. Internally mounted components include circuit breaker with mechanism, control transformer with fused primary lines and fused/grounded secondary lines, mercury type control magnetic contactor(s) suitable for extended wear with frequent cycling, safety magnetic contactor(s), electronic over-temperature controller, fuses, and terminal strips.



#### ENCLOSURE OPTIONS

- NEMA XII** Gasketed enclosure suitable for most indoor industrial applications. Enclosure is finished with factory applied and baked acrylic resin.
- NEMA IV** Gasketed enclosure with stainless steel hardware suitable for most outdoor non-hazardous industrial applications. Enclosure is finished with factory applied and baked acrylic resin.
- NEMA VII** Aluminum Cast and machined enclosure rated for Hazardous Locations - Class 1, Group D, Div. 1 and 2. Contact Gaumer Company Inc. for other locations.

#### OTHER OPTIONS

- XL** Oversized Enclosure
- XXL** Double Oversized Enclosure
- XTIC** Additional Electronic Digital Temperature Control
- XOTC** Additional Over-Temperature Control Temp Range 0°F to 400(800)(1500)°F
- CR** Control Relay with one (1) set "Dry Contacts"
- MtrStr** Pushbutton Station, Pilot Lights, and Motor Starter
- Htr** Enclosure Heater with adjustable thermostat.
- UL** UL Listed

# Control Panels

## Type CP - Standard Contactor System

### NEMA XII

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
6	240	15	20	1	24	16	8	CP12-020-2-1C	CP12-15A-2-1C
12	480	15	20	1	24	16	8	CP12-020-4-1C	CP12-15A-4-1C
10	240	24	30	1	24	16	8	None	CP12-24A-2-1C
20	480	24	30	1	24	16	8	None	CP12-24A-4-1C
12	240	30	40	1	24	16	8	CP12-040-2-1C	CP12-32A-2-1C
25	480	30	40	1	24	16	8	CP12-040-4-1C	CP12-30A-4-1C
26	480	32	40	2	24	24	8	None	CP12-32A-4-2C
20	240	45	60	1	24	16	8	CP12-060-2-1C	CP12-48A-2-1C
40	480	48	60	1	24	16	8	CP12-060-4-1C	CP12-48A-4-1C
40	480	48	60	3	24	24	8	None	CP12-48A-4-3C
40	480	48	60	2	24	24	8	None	CP12-48A-4-2C
22	240	53	70	1	24	16	8	CP12-070-2-1C	CP12-53A-2-1C
44	480	53	70	1	24	16	8	CP12-070-4-1C	CP12-53A-4-1C
25	240	60	80	1	24	16	8	None	CP12-60A-2-1C
50	480	60	80	1	24	16	8	None	CP12-60A-4-1C
52	480	64	80	2	24	24	8	None	CP12-64A-4-2C
52	480	64	80	4	24	24	8	None	CP12-64A-4-4C
30	240	72	90	1	24	20	8	CP12-090-2-1C	CP12-72A-2-1C
60	480	72	90	3	24	24	8	None	CP12-72A-4-3C
60	480	72	90	1	24	20	8	CP12-090-4-1C	CP12-72A-4-1C
32	240	78	100	2	24	24	8	CP12-100-2-2C	CP12-77A-2-2C
65	480	80	100	5	36	30	8	None	CP12-80A-4-5C
65	480	80	100	2	24	24	8	CP12-100-4-2C	CP12-80A-4-2C
80	480	96	125	2	24	24	8	None	CP12-96A-4-2C
80	480	96	125	3	24	24	8	None	CP12-96A-4-3C
80	480	96	125	4	24	24	8	None	CP12-96A-4-4C
80	480	96	125	6	30	24	8	None	CP12-96A-4-6C
41	240	100	125	1	24	24	8	None	CP12-100A-2-1C
83	480	100	125	1	24	24	8	None	CP12-100A-4-1C
88	480	106	150	2	24	24	10	None	CP12-106A-4-2C
50	240	120	150	3	30	24	10	CP12-150-2-3C	CP12-120A-2-3C
100	480	120	175	2	24	24	10	None	CP12-120A-4-2C
100	480	120	150	5	36	30	10	None	CP12-120A-4-5C
100	480	120	150	3	30	24	10	CP12-150-4-3C	CP12-120A-4-3C
104	480	128	175	8	42	36	10	None	CP12-128A-4-8C
104	480	128	175	4	36	30	10	None	CP12-128A-4-4C
120	480	144	200	3	30	24	10	None	CP12-144A-4-3C
120	480	144	200	2	24	24	10	None	CP12-144A-4-2C
120	480	144	200	6	42	36	10	None	CP12-144A-4-6C
66	240	158	250	3	36	30	10	CP12-250-2-3C	CP12-159A-2-3C
130	480	160	200	10	60	36	12	None	CP12-160A-4-10C
130	480	160	200	5	42	36	10	None	CP12-160A-4-5C
130	480	160	250	3	36	30	10	CP12-250-4-3C	CP12-160A-4-3C
150	480	180	250	3	36	30	10	None	CP12-180A-4-3C
160	480	192	250	4	42	36	10	CP12-250-4-4C	CP12-192A-4-4C
160	480	192	250	6	60	36	10	None	CP12-192A-4-6C
160	480	192	250	8	60	36	10	None	CP12-192A-4-8C

# Control Panels

## Type CP - Standard Contactor System

### NEMA XII

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
160	480	192	250	12	60	48	12	None	CP12-192A-4-12C
166	480	200	250	2	30	24	10	None	CP12-200A-4-2C
180	480	216	300	4	42	36	10	None	CP12-216A-4-4C
180	480	216	300	3	42	36	10	None	CP12-216A-4-3C
200	480	240	350	4	42	36	10	None	CP12-240A-4-4C
200	480	240	300	10	60	36	10	None	CP12-240A-4-10C
200	480	240	300	5	42	36	10	None	CP12-240A-4-5C
208	480	256	350	16	60	48	12	None	CP12-256A-4-16C
208	480	256	350	8	60	36	12	None	CP12-256A-4-8C
220	480	265	350	5	60	36	12	None	CP12-265A-4-5C
240	480	288	400	6	60	36	12	None	CP12-288A-4-6C
240	480	288	400	4	42	36	10	None	CP12-288A-4-4C
240	480	288	400	12	60	48	12	None	CP12-288A-4-12C
250	480	300	400	3	42	36	10	None	CP12-300A-4-3C
250	480	300	400	5	60	36	12	None	CP12-300A-4-5C
260	480	320	400	10	60	48	12	None	CP12-320A-4-10C
260	480	320	400	20	84	72	16	None	CP12-320A-4-20C
260	480	320	400	6	60	36	12	CP12-400-4-6C	CP12-320A-4-6C
300	480	360	500	6	60	48	12	None	CP12-360A-4-6C
300	480	360	450	5	60	36	12	None	CP12-360A-4-5C
320	480	384	500	8	60	48	12	None	CP12-384A-4-8C
320	480	384	500	6	60	48	12	None	CP12-384A-4-16C
320	480	384	500	12	60	60	12	None	CP12-384A-4-12C
332	480	400	500	4	42	36	10	None	CP12-400A-4-4C
360	480	432	600	6	60	48	12	None	CP12-432A-4-6C
352	480	432	600	8	60	48	12	None	CP12-432A-4-8C
400	480	480	600	10	60	60	12	None	CP12-480A-4-10C
400	480	480	600	20	84	72	16	None	CP12-480A-4-20C
400	480	480	600	8	60	48	12	CP12-600-4-8C	CP12-480A-4-8C
415	480	500	650	16	84	72	16	None	CP12-512A-4-16C
415	480	500	650	5	60	48	12	None	CP12-500A-4-5C
440	480	530	700	10	60	60	12	None	CP12-530A-4-10C
480	480	576	800	12	72	72	12	None	CP12-576A-4-12C
480	480	576	800	8	60	60	12	None	CP12-576A-4-8C
500	480	600	800	10	60	60	12	None	CP12-600A-4-10C
500	480	600	800	6	60	48	12	None	CP12-600A-4-6C
530	480	640	800	10	60	60	12	CP12-800-4-10C	CP12-640A-4-10C
530	480	640	900	12	72	72	12	None	CP12-640A-4-12C
600	480	720	900	10	60	60	12	None	CP12-720A-4-10C
600	480	720	1000	12	72	72	12	None	CP12-720A-4-12C
640	480	768	1000	16	84	72	16	None	CP12-768A-4-16C
664	480	800	1000	8	60	60	12	None	CP12-800A-4-8C
704	480	864	1200	12	72	72	12	None	CP12-864A-4-12C
704	480	864	1200	16	84	72	12	None	CP12-864A-4-16C
800	480	960	1200	20	84	72	16	None	CP12-960A-4-20C
800	480	960	1200	16	84	72	16	None	CP12-960A-4-16C
800	480	1000	1200	10	60	60	12	None	CP12-1000A-4-10C

# Control Panels

## Type CP - Standard Contactor System

### NEMA XII

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
880	480	1060	1600	20	84	72	16	None	CP12-1060A-4-20C
960	480	1152	1600	16	84	72	16	None	CP12-1152A-4-16C
1000	480	1200	1600	12	72	72	12	None	CP12-1200A-4-12C
1000	480	1200	1600	20	84	72	16	None	CP12-1200A-4-20C
1064	480	1280	1600	20	84	72	16	None	CP12-1280A-4-20C
1200	480	1440	2000	20	84	72	16	None	CP12-1440A-4-20C
1328	480	1600	2000	16	84	72	16	None	CP12-1600A-4-16C
1660	480	2000	3200	20	84	72	16	None	CP12-2000A-4-20C

### NEMA IV

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
6	240	15	20	1	24	20	8	CP4-020-2-1C	CP4-15A-2-1C
12	480	15	20	1	24	20	8	CP4-020-4-1C	CP4-15A-4-1C
10	240	24	30	1	24	20	8	None	CP4-24A-2-1C
20	480	24	30	1	24	20	8	None	CP4-24A-4-1C
12	240	30	40	1	24	20	8	CP4-040-2-1C	CP4-32A-2-1C
25	480	30	40	1	24	20	8	CP4-040-4-1C	CP4-30A-4-1C
26	480	32	40	2	24	24	8	None	CP4-32A-4-2C
20	240	45	60	1	24	20	8	CP4-060-2-1C	CP4-48A-2-1C
40	480	48	60	2	24	24	8	None	CP4-48A-4-2C
40	480	48	60	1	24	20	8	CP4-060-4-1C	CP4-48A-4-1C
40	480	48	60	3	24	24	8	None	CP4-48A-4-3C
22	240	53	70	1	24	20	8	CP4-070-2-1C	CP4-53A-2-1C
44	480	53	70	1	24	20	8	CP4-070-4-1C	CP4-53A-4-1C
25	240	60	80	1	24	20	8	None	CP4-60A-2-1C
50	480	60	80	1	24	20	8	None	CP4-60A-4-1C
52	480	64	80	4	24	24	8	None	CP4-64A-4-4C
52	480	64	80	2	24	24	8	None	CP4-64A-4-2C
30	240	72	90	1	24	20	8	CP4-090-2-1C	CP4-72A-2-1C
60	480	72	90	1	24	20	8	CP4-090-4-1C	CP4-72A-4-1C
60	480	72	90	3	24	24	8	None	CP4-72A-4-3C
32	240	78	100	2	24	24	8	CP4-100-2-2C	CP4-77A-2-2C
65	480	80	100	2	24	24	8	CP4-100-4-2C	CP4-80A-4-2C
65	480	80	100	5	30	24	8	None	CP4-80A-4-5C
80	480	96	125	2	24	24	8	None	CP4-96A-4-2C
80	480	96	125	4	30	24	8	None	CP4-96A-4-4C
80	480	96	125	3	30	24	8	None	CP4-96A-4-3C
80	480	96	125	6	30	24	8	None	CP4-96A-4-6C
41	240	100	125	1	24	24	8	None	CP4-100A-2-1C
83	480	100	125	1	24	24	8	None	CP4-100A-4-1C
88	480	106	150	2	30	24	10	None	CP4-106A-4-2C
50	240	120	150	3	30	24	10	CP4-150-2-3C	CP4-120A-2-3C
100	480	120	150	5	36	30	10	None	CP4-120A-4-5C
100	480	120	150	3	30	24	10	CP4-150-4-3C	CP4-120A-4-3C
100	480	120	175	2	30	24	10	None	CP4-120A-4-2C

# Control Panels

## Type CP - Standard Contactor System

### NEMA IV

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
104	480	128	175	4	36	30	10	None	CP4-128A-4-4C
104	480	128	175	8	42	36	10	None	CP4-128A-4-8C
120	480	144	200	2	30	24	10	None	CP4-144A-4-2C
120	480	144	200	3	30	24	10	None	CP4-144A-4-3C
120	480	144	200	6	42	36	10	None	CP4-144A-4-6C
66	240	158	250	3	36	30	10	CP4-250-2-3C	CP4-159A-2-3C
130	480	160	250	3	36	30	10	CP4-250-4-3C	CP4-160A-4-3C
130	480	160	200	10	60	36	12	None	CP4-160A-4-10C
130	480	160	225	3	36	30	10	None	CP4-160A-4-3C
130	480	160	200	5	42	36	10	None	CP4-160A-4-5C
150	480	180	250	3	36	30	10	None	CP4-180A-4-3C
160	480	192	250	4	42	36	10	None	CP4-192A-4-4C
160	480	192	250	4	42	36	10	CP4-250-4-4C	CP4-192A-4-4C
160	480	192	250	12	60	48	12	None	CP4-192A-4-12C
160	480	192	250	8	60	36	10	None	CP4-192A-4-8C
160	480	192	250	6	60	36	10	None	CP4-192A-4-6C
166	480	200	250	2	30	24	10	None	CP4-200A-4-2C
180	480	216	300	3	42	36	10	None	CP4-216A-4-3C
180	480	216	300	4	42	36	10	None	CP4-216A-4-4C
200	480	240	300	10	60	36	10	None	CP4-240A-4-10C
200	480	240	300	5	60	36	12	None	CP4-240A-4-5C
200	480	240	350	4	42	36	10	None	CP4-240A-4-4C
208	480	256	350	16	60	60	12	None	CP4-256A-4-16C
208	480	256	350	8	60	48	12	None	CP4-256A-4-8C
220	480	265	350	5	60	36	12	None	CP4-265A-4-5C
240	480	288	400	4	42	36	10	None	CP4-288A-4-4C
240	480	288	400	12	60	48	12	None	CP4-288A-4-12C
240	480	288	400	6	60	36	12	None	CP4-288A-4-6C
250	480	300	400	3	42	36	10	None	CP4-300A-4-3C
250	480	300	400	5	60	36	12	None	CP4-300A-4-5C
260	480	320	400	20	84	72	16	None	CP4-320A-4-20C
260	480	320	400	10	60	48	12	None	CP4-320A-4-10C
260	480	320	400	6	60	36	12	CP4-400-4-6C	CP4-320A-4-6C
300	480	360	500	6	60	48	12	None	CP4-360A-4-6C
300	480	360	450	5	60	36	12	None	CP4-360A-4-5C
320	480	384	500	8	60	60	12	None	CP4-384A-4-8C
320	480	384	500	16	84	72	16	None	CP4-384A-4-16C
320	480	384	500	12	60	60	12	None	CP4-384A-4-12C
332	480	400	500	4	42	36	10	None	CP4-400A-4-4C
360	480	432	600	6	60	48	12	None	CP4-432A-4-6C
352	480	432	600	8	60	60	12	None	CP4-432A-4-8C
400	480	480	600	10	60	60	12	None	CP4-480A-4-10C
400	480	480	600	20	84	72	16	None	CP4-480A-4-20C
400	480	480	600	8	60	48	12	CP4-600-4-8C	CP4-480A-4-8C
415	480	500	650	16	84	72	16	None	CP4-512A-4-16C
415	480	500	650	5	60	48	12	None	CP4-500A-4-5C
440	480	530	700	10	60	60	12	None	CP4-530A-4-10C

# Control Panels

## Type CP - Standard Contactor System

### NEMA IV

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
480	480	576	800	12	72	72	12	None	CP4-576A-4-12C
480	480	576	800	8	60	60	12	None	CP4-576A-4-8C
500	480	600	800	10	60	60	12	None	CP4-600A-4-10C
500	480	600	800	6	60	48	12	None	CP4-600A-4-6C
530	480	640	900	12	72	72	12	None	CP4-640A-4-12C
530	480	640	800	10	60	60	12	CP4-800-4-10C	CP4-640A-4-10C
600	480	720	1000	12	72	72	12	None	CP4-720A-4-12C
600	480	720	900	10	60	60	12	None	CP4-720A-4-10C
640	480	768	1000	16	84	72	16	None	CP4-768A-4-16C
664	480	800	1000	8	60	60	12	None	CP4-800A-4-8C
704	480	864	1200	16	84	72	16	None	CP4-864A-4-16C
704	480	864	1200	12	72	72	16	None	CP4-864A-4-12C
800	480	960	1200	16	84	72	16	None	CP4-960A-4-16C
800	480	960	1200	20	84	72	16	None	CP4-960A-4-20C
800	480	1000	1200	10	60	60	12	None	CP4-1000A-4-10C
880	480	1060	1600	20	84	72	16	None	CP4-1060A-4-20C
960	480	1152	1600	16	84	72	16	None	CP4-1152A-4-16C
1000	480	1200	1600	20	84	72	16	None	CP4-1200A-4-20C
1000	480	1200	1600	12	72	72	12	None	CP4-1200A-4-12C
1064	480	1280	1600	20	84	72	16	None	CP4-1280A-4-20C
1200	480	1440	2000	20	84	72	16	None	CP4-1440A-4-20C
1328	480	1600	2000	16	84	72	16	None	CP4-1600A-4-16C
1660	480	2000	3200	20	84	72	16	None	CP4-2000A-4-20C

### NEMA VII

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
6	240	15	20	1	18	12	8	CP7-020-2-1C	CP7-15A-2-1C
12	480	15	20	1	18	12	8	CP7-020-4-1C	CP7-15A-4-1C
10	240	24	30	1				None	CP7-24A-2-1C
20	480	24	30	1				None	CP7-24A-4-1C
12	240	30	40	1	18	12	8	CP7-040-2-1C	CP7-32A-2-1C
25	480	30	40	1	18	12	8	CP7-040-4-1C	CP7-30A-4-1C
26	480	32	40	2				None	CP7-32A-4-2C
20	240	45	60	1	18	12	8	CP7-060-2-1C	CP7-48A-2-1C
40	480	48	60	3				None	CP7-48A-4-3C
40	480	48	60	1	18	12	8	CP7-060-4-1C	CP7-48A-4-1C
40	480	48	60	2				None	CP7-48A-4-2C
22	240	53	70	1	18	12	8	CP7-070-2-1C	CP7-53A-2-1C
44	480	53	70	1	18	12	8	CP7-070-4-1C	CP7-53A-4-1C
25	240	60	80	1				None	CP7-60A-2-1C
50	480	60	80	1				None	CP7-60A-4-1C
52	480	64	80	2				None	CP7-64A-4-2C
52	480	64	80	4				None	CP7-64A-4-4C
30	240	72	90	1	18	18	8	CP7-090-2-1C	CP7-72A-2-1C
60	480	72	90	3				None	CP7-72A-4-3C



# Control Panels

## Type CP - Standard Contactor System

### NEMA VII

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
60	480	72	90	1	18	18	8	CP7-090-4-1C	CP7-72A-4-1C
32	240	78	100	2	24	16	8	CP7-100-2-2C	CP7-77A-2-2C
65	480	80	100	2	24	16	8	CP7-100-4-2C	CP7-80A-4-2C
65	480	80	100	5				None	CP7-80A-4-5C
80	480	96	125	6				None	CP7-96A-4-6C
80	480	96	125	3				None	CP7-96A-4-3C
80	480	96	125	4				None	CP7-96A-4-4C
80	480	96	125	2				None	CP7-96A-4-2C
41	240	100	125	1				None	CP7-100A-2-1C
83	480	100	125	1				None	CP7-100A-4-1C
88	480	106	150	2				None	CP7-106A-4-2C
50	240	120	150	3	24	16	8	CP7-150-2-3C	CP7-120A-2-3C
100	480	120	150	3	24	16	8	CP7-150-4-3C	CP7-120A-4-3C
100	480	120	150	5				None	CP7-120A-4-5C
100	480	120	175	2				None	CP7-120A-4-2C
104	480	128	175	8				None	CP7-128A-4-8C
104	480	128	175	4				None	CP7-128A-4-4C
120	480	144	200	2				None	CP7-144A-4-2C
120	480	144	200	3				None	CP7-144A-4-3C
120	480	144	200	6				None	CP7-144A-4-6C
66	240	158	250	3	36	24	8	CP7-250-2-3C	CP7-159A-2-3C
130	480	160	225	3	24	16	8	None	CP7-160A-4-3C
130	480	160	225	3				None	CP7-160A-4-3C
130	480	160	200	10				None	CP7-160A-4-10C
130	480	160	200	5				None	CP7-160A-4-5C
150	480	180	250	3				None	CP7-180A-4-3C
160	480	192	250	4	36	24	8	CP7-250-4-4C	CP7-192A-4-4C
160	480	192	250	6				None	CP7-192A-4-6C
160	480	192	250	12				None	CP7-192A-4-12C
160	480	192	250	4				None	CP7-192A-4-4C
160	480	192	250	4				CP7-250-4-4C	CP7-192A-4-4C
160	480	192	250	8				None	CP7-192A-4-8C
166	480	200	250	2				None	CP7-200A-4-2C
180	480	216	300	4				None	CP7-216A-4-4C
180	480	216	300	3				None	CP7-216A-4-3C
200	480	240	300	10				None	CP7-240A-4-10C
200	480	240	350	4				None	CP7-240A-4-4C
200	480	240	300	5				None	CP7-240A-4-5C
208	480	256	350	16				None	CP7-256A-4-16C
208	480	256	350	8				None	CP7-256A-4-8C
220	480	265	350	5				None	CP7-265A-4-5C
240	480	288	400	12				None	CP7-288A-4-12C
240	480	288	400	4				None	CP7-288A-4-4C
240	480	288	400	6				None	CP7-288A-4-6C
250	480	300	400	5				None	CP7-300A-4-5C
250	480	300	400	3				None	CP7-300A-4-3C
260	480	320	400	20				None	CP7-320A-4-20C

# Control Panels

## Type CP - Standard Contactor System

### NEMA VII

Rated kW	Rated Volt	3Ph Amps	CirBrkr Size	No. of Circuits	Height (inches)	Width (inches)	Depth (inches)	Gaumer Catalog Number (Obsolete)	Gaumer Catalog Number
260	480	320	400	10				None	CP7-320A-4-10C
280	480	336	400	6	(2)36	24	8	CP7-400-4-6C	CP7-320A-4-6C
300	480	360	450	5				None	CP7-360A-4-5C
300	480	360	500	6				None	CP7-360A-4-6C
320	480	384	500	12				None	CP7-384A-4-12C
320	480	384	500	16				None	CP7-384A-4-16C
320	480	384	500	8				None	CP7-384A-4-8C
332	480	400	500	4				None	CP7-400A-4-4C
360	480	432	600	6				None	CP7-432A-4-6C
352	480	432	600	8				None	CP7-432A-4-8C
400	480	480	600	20				None	CP7-480A-4-20C
400	480	480	600	8				None	CP7-480A-4-8C
400	480	480	600	10				None	CP7-480A-4-10C
415	480	500	650	5				None	CP7-500A-4-5C
415	480	500	650	16				None	CP7-512A-4-16C
440	480	530	700	10				None	CP7-530A-4-10C
480	480	576	800	12				None	CP7-576A-4-12C
480	480	576	800	8				None	CP7-576A-4-8C
500	480	600	800	6				None	CP7-600A-4-6C
500	480	600	800	10				None	CP7-600A-4-10C
530	480	640	900	12				None	CP7-640A-4-12C
530	480	640	800	10				None	CP7-640A-4-10C
600	480	720	1000	12				None	CP7-720A-4-12C
600	480	720	900	10				None	CP7-720A-4-10C
640	480	768	1000	16				None	CP7-768A-4-16C
664	480	800	1000	8				None	CP7-800A-4-8C
704	480	864	1200	12				None	CP7-864A-4-12C
704	480	864	1200	16				None	CP7-864A-4-16C
800	480	960	1200	16				None	CP7-960A-4-16C
800	480	960	1200	20				None	CP7-960A-4-20C
800	480	1000	1200	10				None	CP7-1000A-4-10C