Dell OptiPlex GX620 and GX520



The GX620 and the GX520 are designed for the enterprise customer who is looking for performance, stability and flexibility in the workplace. The GX620 and GX520 extend industry-leading solutions through customer driven innovation, environmental responsibility and excellent customer choice, by offering seven different chassis choices sharing one single image, helping to provide excellent image stability and a low ownership cost. The GX520 provides new integrated desktop innovations for customers seeking a robust mainstream business solution while the GX620 offers all the benefits of the GX520 plus maximum flexibility, security and investment protection including Intel's new Pentium D Dual Core processors.

Direct Detect[™] keeping the pulse on the health of your system Provides guick and convenient status of your hard drive activity and network connectivity **Usability at your fingertips** • USB ports are conveniently located on the front of the system with easy access and spacing for side by side installation of USB devices Innovative BTX Design Dell's innovative BTX chassis, power supply and motherboards are designed for thermal efficiency providing improved reliability and quieter operation, as compared to previous OptiPlex models. Innovative HyperCool[™] System • Dell's HyperCool thermal management technology utilizes variable speed fans that provide optimal cooling with less power and enables quieter operation as compared to previous OptiPlex models. A Solution For Every Space • The GX620 offers the Ultra Small Form Factor and the Small Form Factor chassis with an innovative All-in-One solution for space constrained environments. • The GX520 includes this offer on the Small Form Factor chassis.



Environmental Peace of Mind

- Environmentally conscious design is RoHS compliant
- Waste reduction via customer selectable documentation and media at the point of purchase
- EnergyStar compliant straight from the factory
- Asset recovery and disposal services available

Dell Services help make OptiPlex[™] desktops Easier to Deploy and Easier to Manage

- Image Management Helps reduce image management complexity and costs by assisting customers with image development, testing and validation.
- Custom Factory Integration Key services include custom image load, asset tagging and management and custom hardware installation.
- Deployment Dell can arrange for custom logistics and delivery as well as installation of new systems and removal of old hardware.

GET MORE OUT OF NOW.

Visit www.dell.com for more information

OptiPlex GX620



OptiPlex GX520



System		
Processor Type	Intel® 945G chipset, Intel® Pentium® D processor with Dual Core architecture, Intel® Pentium® 4 processor with 800MHz front side bus and Hyper-Threading and up to 2MB L2 cache or Celeron D® processor with 533MHz and 256K L2 cache	Intel® 945G chipset with Intel® Pentium® 4 processor with 800 MHz front side bus and Hyper-Threading and Celeron D® proces- sor with 533MHz and 256K L2 cache
Processor Features	Intel® Pentium® D 800MHz FSB socket T with Dual Core technology XD, EM64T, 2x1MB L2 cache, and EIST* (8xx series) Intel® Pentium® 4 800MHz FSB socket T with HT, XD, EM64T, 2MB L2 cache and EIST* (6xx series) Intel® Pentium® 4 800MHz FSB socket T with HT, XD, EM64T, and 1MB L2 cache (5xx series) Intel® Celeron® D533 MHz FSB Socket T with XD & EM64T (3xx series)	Intel® Pentium® 4 800MHz FSB socket T with HT, XD, EM64T, and 1MB L2 cache (5xx series) Intel® Celeron® D 533 MHz FSB Socket T with XD and EM64T (3xx series)
Operating Systems	Dell recommends Microsoft® Windows® XP Professional; Microsoft Windows® XP Professional and Microsoft Windows XP Home Edition	Dell recommends Microsoft® Windows® XP Professional; Microsoft Windows® XP Professional and Microsoft Windows XP Home Edition
Memory	4 DIMM slots (2 DIMM slots on USFF chassis); Non-ECC dual channel shared ² DDR2 SDRAM system memory (533Mhz) up to 4GB ³	2 DIMM slots Non-ECC dual channel shared ² DDR2 SDRAM system memory (400 and 533Mhz) up to 2GB
Video Graphics Controller	Integrated Intel® Graphics Media Accelerator 950®; DVI Adapter card; 128MB ATI Radeon™ X600SE with DVI and TV-out	Integrated Intel® Graphics Media Accelerator 950®
Hard Drive	40GB ⁴ , 80GB ⁴ , 160GB ⁴ and 250GB ⁴ 7200RPM Serial ATA	40GB ⁴ , 80GB ⁴ and 160GB ⁴ 7200RPM Serial ATA
Network Controller	Broadcom® 5751 Gigabit Ethernet LAN solution 10/100/10001 Ethernet with Remote Wake Up and PXE support	Broadcom® 5751 Gigabit Ethernet LAN solution 10/100/10001 Ethernet with Remote Wake Up and PXE support
Standard I/O Ports	Eight USB 2.0 (two front and six rear), USFF offers 7 USB 2.0 (2 front and 5 rear), one Ethernet (RJ45), one nine-pin serial (16550 com- patible), one parallel (25-hole, bi-directional), 1 VGA out, (DVI-I out on USFF) Optional Second serial port (Not available on USFF), stereo line-in, microphone-in (front), speakers/line-out and headphone (front)	Eight USB 2.0 (two front and six rear), one Ethernet (RJ45), one nine-pin serial (16550 compatible), one parallel (25-hole, bi-directional), 1 VGA out, Optional Second serial port, stereo line-in, microphone-in (front), speakers/line-out and headphone (front)
Chassis		
Dimensions	Small Form Factor 12.4" x 3.6" x 13.4" (31.63cm x 9.26cm x 34cm) Desktop 15.6" x 4.5" x 13.7" (39.59cm x 11.43cm x 34.77cm) Mini-Tower 16.2" x 7.3" 17" (41.14cm x 18.96cm x 43.18cm) Ultra Small Form Factor 10.3" x 3.5" x 9.9" (26.3cm x 8.9cm x 25.28cm)	Small Form Factor 12.4" x 3.6" x 13.4" (31.63cm x 9.26cm x 34cm) Desktop 15.6" x 4.5" x 13.7" (39.59cm x 11.43cm x 34.77cm) Mini-Tower 16.2" x 7.3" 17" (41.14cm x 18.96cm x 43.18cm)
Power Supply	Small Form Factor 275W; Desktop 280W; Mini-Tower 305W; Ultra small form factor 220W (External)	Small Form Factor 220W; Desktop 220W; Mini-Tower 230W
Peripherals		
Monitors	15" E153FPb TFT Flat Panel 17" E773c/s UltraSharp™ 17" 1704FP TFT Flat Panel 17" E173FPb TFT Flat Panel 17" M783 UltraSharp™ 19" 1906FP TFT Flat Panel 19" E193FPb TFT Flat Panel 19" M993 UltraScan UltraSharp™ 20" 2001FP TFT Flat Panel 15" 1505FP HAS TFT Flat Panel UltraSharp™ 20" 2005FPW TFT Flat Panel UltraSharp™ 24" 2405FPW TFT Flat Panel	15" E153FPb TFT Flat Panel 17" E773c/s UltraSharp™ 17" 1704FP TFT Flat Panel 17" E173FPb TFT Flat Panel 17" M783 UltraSharp™ 19" 1906FP TFT Flat Panel 19" E193FPb TFT Flat Panel 19" M993 UltraScan UltraSharp™ 20" 2001FP TFT Flat Panel 15" 1505FP HAS TFT Flat Panel UltraSharp™ 20" 2005FPW TFT Flat Panel UltraSharp™ 20" 2005FPW TFT Flat Panel UltraSharp™ 20" 2005FPW TFT Flat Panel
All In One Solutions	UltraSharp™ 1706FP All In One (SF Chassis); UltraSharp™ 1906FP All In One (SF Chassis); UltraSharp™ 1706FP All In One (USFF chassis)	UltraSharp™ 1706FP All In One (SF Chassis); UltraSharp™ 1906FP All In One (SF Chassis)
Keyboard (105 Keys)	Dell Enhanced QuietKey™ USB, Enhanced Performance USB, Smart Card keyboard USB	Dell Enhanced QuietKey™ USB, Enhanced Performance USB, Smart Card keyboard USB
Mouse	Dell USB two-button and Dell USB optical two-button scroll	Dell USB two-button and Dell USB optical two-button scroll
Speakers	Internal Dell Business Audio speaker, Dell A215, Dell A425, AS500 and AS500PA sound bar available with select FP monitors	Internal Dell Business Audio speaker, Dell A215, Dell A425, AS500 and AS500PA sound bar available with select FP monitors
Storage Devices		
Removable Media Storage Devices	USB Floppy Drive, CD-ROM, CDRW ^{s#} , CD-RW/DVD Combo, DVD-ROM ^{s#} and DVD+/-RW ^s	USB Floppy Drive, CD-ROM, CDRW ^{SI} , CD-RW/DVD Combo, DVD-ROM ^{SI} and DVD+/-RW ⁵
USB Storage Keys	Dell USB Memory Key 128MB, 256MB, and 512MB and USB 2.0 full speed compliant and bootable	Dell USB Memory Key 128MB, 256MB, and 512MB and USB 2.0 full speed compliant and bootable
Security		
Security	Trusted Platform Module 1.2 (TPM 1.2) Chassis intrusion switch	Optional Chassis intrusion switch
Environmental, Ergo	nomics & Regulatory Service & Support	
Standards	TCO99, Blue Angel, Green PC, Energy Star, BSMI, C-TICK, CE, FCC, IRAM, NEMKO, NFPA 99, SABS, SASO, TCO, TUV, UL, VCCI, USB 2.0	TC099, Blue Angel, Green PC, Energy Star, BSMI, C-TICK, CE, FCC, IRAM, NEMKO, NFPA 99, SABS, SASO, TCO, TUV, UL, VCCI, USB 2.0
Base Service	Three-Year Limited Warranty [®] and Next Business Day On-Site Service ⁷ (US Only)	Three-Year Limited Warranty ^e and Next Business Day On-Site Service ⁷ (US Only)
Optional Service	Three-Year Same Day Four-Hour On-Site Response Service ⁷ , 5 days x 10 hours a day, Three-Year Same Day Four-Hour On-Site Response Service ⁷ , 7 days x 24 hours a day	Three-Year Same Day Four-Hour On-Site Response Service ⁷ , 5 days x 10 hours a day, Three-Year Same Day Four-Hour On-Site Response Service ⁷ , 7 days x 24 hours a day

*EIST not available on 520 # not available on SF or USFF

1. The term Gigabit Ethemet does not connote an actual operating speed of 1 GB/sec. For high speed transmission, connection to a Gigabit Ethemet server and network infrastructure is required. 2. Up to 224MB of system memory may be allocated to support graphics, depending on system memory size and other factors. 3 The total amount of usable memory available will be less than 4 GB, depending on the actual system configuration 4. For hard drives, GB means 1 billion bytes; actual capacity varies with preloaded material and operating system and will be less. 5. Discs burned with this drive may not be compatible with some existing drives and players; using DVD+R media provides maximum compatibility. 6. For a copy of Dell's guarantees or limited warranties, please write Dell USA LP, Attr. Warranties, One Dell Way, Round Rock, TX 78682. For more information, visit www.dell.com/us/en/gen/services/service_plans.htm. 7. Service may be provided by third-party. Technician will be dispatched if necessary following phone based troubleshooting. Subject to parts availability, gorgaphical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. US. only. Dell Optifiex is a trademark of Dell Inc. Intel, Intel inside logo and Pentium are registered trademarks of their products. Dell



Microsoft Corporation. Uther trademarks and trade names are used to identify the entities claiming the marks and names of their products. Dell SS_OPT_GX620_BreakBack_052005