




104-1641CLDNA(B)

PC/104 SBC with CPU/Memory/LVDS/VGA /ADCII/LAN/Audio



Features


- AMD LX800 500MHz CPU
- Onboard 256MB DDR memory
- Supports 1 x 10/100Mbps Ethernet interface
- Supports 2 x USB2.0, 1 x LPT, 4 x COM
- Supports VGA/LCD/LVDS dual-display

Specifications

System	
Processor	AMD LX800 500MHz CPU
Chipset	AMD Geode™ CS5536
Memory	Onboard 256MB DDR memory
Hardware Monitor	Monitors system status, voltage, temperature and fan speed
Watchdog Timer	1 255 seconds or 1 255 minutes
Expansion Interface	PC/104-Plus
Storage	
IDE	1 x Ultra-ATA100 interface
Serial ATA	N/A
Floppy	N/A
CF	N/A
DOC/DOM	1 x AOC
I/O Interface	
USB	2 x USB2.0 port
Serial Port	4 x RS-232(1 x RS-232/422/485, 1 x RS-422/485)
Parallel Port	N/A
IrDA	N/A
GPIO	8-channel digital I/O TTL level interface
Audio	AC'97
Keyboard/Mouse	1 x PS/2

Display	
Chipset	AMD Geode™ CS5536
Memory	Integrated in LX800, 16MBshared memory
Resolution	
Dual Display	VGA/LVDS/18/24-bit TTL, LCD
Ethernet	
Chipset	1 x 10/100Mbps Ethernetinterface
Speed	10/100Mbps
Connector	1 x RJ45
Mechanical and Environmental	
Dimensions	116mm x96mm
Operating Temperature	-40°C~85°C
Storage Temperature	N/A
Operating Humidity	5%-90%, non-condensing
Power	
Power Supply	Single 5V power supply
Power Consumption	4.5W
Operating System	
Windows OS	Windows XP
Embedded OS	Linux

Board Diagram



Available Accessories

Part Number	Name	Description	Qty.
—	Setup Guide/RoHS	AMI/BIOS Setup Guide (for Core/8)	1
2360-012641	VGA cable/RoHS	2x5 Pin connector (2.0mm pitch) to 15P female right angle connector, length: 300mm/RoHS	1
2360-012651	DC Power supply cable/RoHS	2x5 Pin connector to one male power 4 Pin (5.08mm pitch), length: 250mm/RoHS	1
2360-011231	Serial port cable/RoHS	DB9 connector to 10 Pin (2x5) connector (2.0mm pitch), length: 300mm/RoHS	4
2360-014781	Dual USB ports with bracket/RoHS	Two USB ports to one 10 Pin (2x5) connector (2.0mm pitch), length: 550mm/RoHS	1
2360-008781	HDD flat cable/RoHS	40 Pin to 44 Pin (2.0mm pitch), length: 550mm/RoHS	1
2360-017481	Multi-functional converter cable/RoHS	Buzzer reset button dual PS/2 connector to 2x5 Pin 2.0mm pitch female connector, length: 250mm	1
2360-002581	Audio cable with bracket/RoHS	Three audio jacks to one 10 Pin (2x5) connector (2.0mm pitch), length: 300mm/RoHS	1
—	Driver CD/Protective film/RoHS	Chinese and English/104-1641CLDNA(B)	1
—	User Manual/Chinese and English/RoHS	104-1641CLDNA(B)	1
2330-000011	Jumper/RoHS	Pitch: 2.0mm, black, sealed tail	6
0090-000201	LED panel/RoHS	P10-RJ45LED	1
1090-004411	LED panel(PCBA)/RoHS	P10-RJ45LED	1
2331-004681	Pin header/RoHS	2x5 Pin 2.0mm pitch	1
2331-006301	Network socket/RoHS	Straight pin RJ45-8P with indicator lamp/without spring piece	1
1090-500321	LED panel/related data/RoHS	P10-RJ45LED	1
2360-012771	Serial port cable/RoHS	2x5 Pin (2.0mm pitch) to 2x5 Pin (2.0mm) connector, length: 300mm	1

Ordering Information

Part Number	Model Number	Description
0030-011281	104-1641CLDNA(B)	Motherboard/RoHS
0030-011280	104-1641CLDNA(B)	Motherboard