

# D.C. Power Supply



**GPS-SERIES (ANALOG TYPE)**



**GPS-SERIES**

## FEATURES

- \* Light and Compact Design
- \* 0.01% High Regulation
- \* Constant Voltage and Constant Current Operation
- \* Series or Parallel Operation Function

- \* Remote Control for External Programmable
- \* Internal Select for Continuous or Dynamic Load
- \* Low Ripple and Noise
- \* Overload and Reverse Polarity protection

## SPECIFICATIONS

CONSTANT VOLTAGE OPERATION	Regulation	Line regulation $\leq 0.01\% + 3mV$ Load regulation $\leq 0.01\% + 3mV$ (rating current $\leq 3A$ ) $\leq 0.01\% + 5mV$ (rating current $> 3A$ )
	Ripple & Noise	$\leq 0.5mV_{rms}$ 5Hz ~ 1MHz (rating current $\leq 3A$ ) $\leq 1mV_{rms}$ 5Hz ~ 1MHz (rating current $> 3A$ )
	Recovery Time Temp. Coefficient Output Range	$\leq 100\mu S$ (50% Load change, Minimum load 0.5A) $\leq 300 ppm / ^\circ C$ 0 to rating voltage continuously adjustable
CONSTANT CURRENT OPERATION	Regulation	Line regulation $\leq 0.2\% + 3mA$ Load regulation $\leq 0.2\% + 3mA$
	Ripple Current Output Range	$\leq 3mA_{rms}$ 0 to rating current continuously adjustable (Hi / Lo range switchable)
METER	Analog	V-meter and I-meter each one 2.5 class
	Digital	Dimensions 50 x 50 mm 3 1/2 digits 0.5" LED display Accuracy $\pm (0.5\% \text{ of rdg} + 2 \text{ digits})$
INSULATION	Chassis and Terminal Chassis and AC Cord	20M $\Omega$ or above (DC 500V) 30M $\Omega$ or above (DC 500V)
POWER SOURCE		AC 100V/120V/220V/240V $\pm 10\%$ , 50/60Hz
ACCESSORIES		Instruction manual x 1, Power cord x 1 Test lead GTL-105 x 1 ( $\leq 3A$ ) or GTL-104 x 1 ( $\leq 10A$ )
DIMENSIONS		128(W) x 145(H) x 285(D) mm

## ORDERING INFORMATION

Model	Output Volts(V)	Output Amps(A)	Weight (kg)
GPS-1830 54W D.C. Power Supply	0 ~ 18	0 ~ 3	4
GPS-1850 90W D.C. Power Supply	0 ~ 18	0 ~ 5	5.5
GPS-3030 90W D.C. Power Supply	0 ~ 30	0 ~ 3	5
GPS-6010 60W D.C. Power Supply	0 ~ 60	0 ~ 1	4
GPS-1830D 54W D.C. Power Supply	0 ~ 18	0 ~ 3	4
GPS-1850D 90W D.C. Power Supply	0 ~ 18	0 ~ 5	5
GPS-3030D 90W D.C. Power Supply	0 ~ 30	0 ~ 3	5