



Electrical specifications

Input

Voltage 90 - 264 VAC (wide range)
 Current 1.5Arms Max.
 Frequency 47 - 63 Hz

Output

Voltage (Vo) 12V ... 19V
 Tolerance 5%
 Power (Po) 72Wmax
 Hold up time 12ms min. at full load, 115 VAC
 Over voltage protection..... Build-in
 Over current protection 120% of full load or CC mode
 Short circuit protection Built-in
 Efficiency 80% typ. at full load and 115 VAC
 Ripple/Noise(Vp-p) 1% (20MHz bandwidth)

Output Electronic Specifications

Model No.	Po	Vo	Io max
VAN70-120	60W	12V	5A
VAN70-150	72W	15V	4.8A
VAN70-160	72W	16V	4.5A
VAN70-170	72W	17V	4.23A
VAN70-180	72W	18V	4A
VAN70-190	72W	19V	3.78A
VAN70-480	70W	48V	1.45A

Features

- Two type IEC C6,C8 inlet socket
- Wide range AC voltage input
- Constant current output built-in
- Level B EMI filter
- Fully enclosed plastic case
- Fully regulated output
- High efficiency
- High quality

Environmental

Operating temperature

0 deg. C to +40 deg. C ambient

Storage temperature

-20 deg. C to +80 deg. C ambient

EMI

Meet FCC class B, CISPR 22 class B, VCCI class B

Safety

CE
 CB
 FCC
 UL/CUL



益航電子股份有限公司
 FAIRWAY ELECTRONIC CO., LTD.

3FL-2, No. 502, Yuanshan Rd., Chung Ho City,
 Taipei Hsien, Taiwan, R.O.C.
 TEL: 886-2-8227-6630 FAX: 886-2-2222-6752
 Web: <http://www.fairway.com.tw>
 E-mail: sales@fairway.com.tw