

CMI203



Features

- Mini-ITX system supports IBASE Mini-ITX motherboards
- Available in black color
- Supports 2x PCI slots
- With motherboard's I/O shields and extra 2x USB ports
- LEDs for Standby and Power
- One 3.5" HDD drive bay
- Optional 250W power supply
- Wall mount kit included

Specifications

System Mainboard	IBASE Mini-ITX motherboards
Construction	SECC
Chassis Color	Black
I/O Connectors	Flexible IBASE Mini-ITX motherboard's I/O shields, extra 2x USB ports, Standby LED, Power LED, ATX power On/Off/Reset, DC 12V output connectors
Expansion Slots	2x PCI slots
Storage	1x 3.5" HDD drive bay
Power Supply	Output Power: DC 180W or 250W (ATX Power) Input Voltage: 90~264VAC full range
Mounting	Desktop or wall mount
Dimensions	345mm(W) x 225mm(D) x 100mm(H)

Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	Non-Operating : 1.0 grms / 5~500Hz / random Operating : 0.25 grms / 5~500Hz / random

Ordering Information

CMI203-180	Chassis for Mini-ITX, w/ 180W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & iIO LCM)
CMI203-250	Chassis for Mini-ITX, w/ 250W PSU, 3.5" HDD holder, 2x PCI-E (optional IP241, IP118-R riser card & iIO LCM)

Remarks:

1. For optional daughter boards and riser cards, please refer to page 19-20.
2. Use only CPU/heatsink with height fitting the chassis-not touching the chassis top cover.
3. ODM/OEM is available.