


# VTC1357324



## Features & Benefits

- 1 Front bezel for data security and protection
- 2 Two(2) external 5.25-inch optical bay supported
- 3 One(1) external 3.5-inch optical bay supported
- 4 Front access dual USB port
- 5 Power on/off, system reset and LEDs for HDD & LAN
- 6 Four(4) internal 3.5-inch HDD supported
- 7 Three(3) hot-swap middle fans for optimized cooling - [Upgradable to six(6)]
- 8 Riser card mounting bracket
- 9 One(1) rear fans for optimized cooling
- 10 Three(3) PCI slots via riser card



# Specifications

Materials : Heavy-duty cold-rolled steel	
Finish :	Inside / Body : Zinc-plated with bright chromate
	Outside / Front : Texture-coated
Dimensions : (W x D x H)	mm : 482.6 x 575.4 x 88.2
	inches : 19 x 22.7 x 3.5
Cooling :	Middle: 2 x 80x25mm easy-swap fans (+ optional 4 x 40x28mm)
	Rear: 1 x 80x25mm fan
Power Supply :	● Descriptions
	30X 300W ATX PFC 46E 460W EPS-12V PFC
Expansion : 3 x PCI slot via riser card (full height) 7 x PCI slot low profile	
Controls : Power on/off and system reset + 2 x USB ports	
Indicators : Power, LAN, and HDD LED's	
Speakers : 0.4W built-in	
System Board : Up to 12"(W) x 10.5"(D) size ATX/SSI CEB compliant motherboards	

Drive Bay :	External	5.25"	2
		3.5"	1
		2.5" hot-swap	0
	Internal	3.5"	4
		Slim CD-Rom/DVD-Rom	0
	Slim FDD		0
Temperature : 0°C(32°F) ~ 50°C(122°F)			
Humidity : 5%~95% non-condensing			
Gross Weight : 15 kgs / 33 lbs			
Packaging Dimension (W x D x H) :		mm : 580 x 760 x 240	
Cubic Feet : 3.8			
Reference Container Loading :		20'	275
		40'	550
		40' H	618

# Mechanical Drawing

