



## Features

- Supports Intel® Pentium® III / Celeron® processor up to 1.4GHz
- 36-bit Dual channel TTL/LVDS interface
- TV-Out Function
- 10/100Mbps Fast Ethernet
- Four USB ports

## Specifications

### System

<b>CPU</b>	Socket 370 based Pentium® III(.13 μ) / Celeron (.18 μ) Processor up to 1.4GHz with FSB 66/100/133MHz
<b>System Memory</b>	168-pin DIMM x 1, Max. 512MB (PC-100/133)
<b>Chipset</b>	VIA VT8606 + VT82C686B
<b>I/O Chipset</b>	VIA 82686B + Winbond W83977TF
<b>BIOS</b>	Award 256KB FLASH ROM
<b>Ethernet</b>	Realtek 8139DL, RJ-45 10/100Base-T connector x 1
<b>SSD</b>	Type II CompactFlash slot
<b>Watchdog timer</b>	Generate a system reset
<b>Expansion Interface</b>	PC/104 socket x 1, PCI slot x 1
<b>Battery</b>	Lithium battery
<b>H/W status monitoring</b>	Supports power supply voltages and temperatures monitoring
<b>Power supply voltage</b>	+5V, +12V. ATX / AT
<b>Board Size</b>	8" (L) x 5.75" (W) (203mm x 146mm)
<b>Gross Weight</b>	1.2lb. (0.5kg)
<b>Operating temperature</b>	32 ~ 140 (0 ~ 60 )

### I/O

<b>MIO</b>	IDE (Ultra DMA33) x 1, FDD x 1, K/B+Mouse x 1, RS-232/422/485 x 1, RS-232 x 3, Parallel x 1
<b>IrDA</b>	One IrDA Tx/Rx header
<b>Audio</b>	Realtek ALC201 AC-97 2.2 CODEC
<b>USB</b>	Two 4x2 pin headers support 4 USB 1.1 ports

### Display

<b>Chip</b>	VIA VT8606
<b>Memory Size</b>	Shared memory up to 32MB
<b>Resolution</b>	up to 1280 x 1024@ 32bpp colors for CRT up to 1024 x 768@ 18bpp colors for LCD
<b>LCD Interface</b>	up to 36-bit TTL/LVDS TFT/DSTN LCD
<b>TV-out</b>	Support NTSC and PAL standard
<b>Supports CRT and LCD / CRT and TV simultaneous display</b>	

## Packing List

<b>Jumper Cap</b>	9657666600
<b>Short Copper and support</b>	9657000300
<b>Quick Installation Guide</b>	
<b>Utility CD</b>	