

VTC18340

Intel® Pentium® 4 / Pentium® 4M / Celeron® 1U Rackmount
Network Security Appliance with 3 Ethernet Ports



- ◆ 1U Rackmount network platform
- ◆ Support Intel® Pentium® 4 / Pentium® 4-M Processor up to 2.8GHz+
- ◆ 184-pin DIMM x 2, support Max. 2GB memory
- ◆ Built-in 10/100 LAN port x 3
- ◆ Internal 3.5" HDD Bay

Specifications

Construction

- ◆ 1U Rackmount chassis, heavy-duty steel

Dimension

- ◆ 426(W) x 228.6(D) x 43.5(H) mm (16.8" x 9" x 1.72")

Processor

- ◆ Support Intel® Pentium® 4 / Pentium® 4-M Processor up to 2.8GHz+

Chipset

- ◆ Intel® 845GV/ ICH4/ FWH

Memory

- ◆ 184-pin DIMM x 2, support Max. 2GB memory
- ◆ Support DDR 200 / 266 / 333

Storage

- ◆ On internal 3.5" HDD bay
- ◆ Optional Compact Flash Module (EBK CF)/ DOM Module

Cooling System

- ◆ 40mm fan x 2 for system cooling
- ◆ Power LED x 1
- ◆ Power on / off switch x 1 (Rear)
- ◆ Act / Link, 10 / 100 LED x 3 on RJ-45

Ethernet

- ◆ 10 / 100 Base-TX port x 3
- ◆ Intel® LAN S82551QM x 2
- ◆ Intel® LAN S82562EM x 1
- ◆ RJ-45 with LED x 3

System Console Port

- ◆ COM port x 2 (1x rear, 1x front)
- ◆ RS-232 DB - 9 connector
- ◆ USB x 2 (Rear)

Power Supply

- ◆ 250W ATX power supply
- ◆ AC/DC 90 ~ 264V full range @ 47 ~ 63 Hz

Color

- ◆ PANTONE 295U

Environment

- ◆ Operating temperatures : 0°C to 40°C
- ◆ Storage temperatures : -20°C to 80°C
- ◆ Relative humidity : 10% to 90% (Non-condensing)

Certification

- ◆ CE
- ◆ FCC

Ordering Information

| Model Name | Chassis | Ethernet port | COM port | USB port | Compact Flash | LCM Module | Power Supply |
|------------|---------|----------------------------|----------|----------|---------------|------------|--------------|
| VTC18340 | 1U | 82551QM x 2 82562EM x 1 | 2 | 2 | Optional | No | ATX 250W |