

PAC-1060A

PAC-106/107

5-slot Full-Size Industrial PC Chassis

6-slot Full-size Industrial PC Chassis

Compact Chassis series



Compact Size 6-slot Chassis Design Flexible Drive Bay Design !

FEATURE

- ◆ Designed for full / half size cards
- ◆ One 8cm cooling fan with removable filter
- ◆ Specially design for HDD / FDD, easily to do installation

SPECIFICATIONS

◆ Drive Bays:

Model	3.5" FDD	5.25" Drive	3.5" HDD
PAC-106	1	-	1
PAC-107	1	1	1

- ◆ One 8cm cooling fan with removable filter
- ◆ Supports backplane: BP-6S, IP-6S, PCI-6S
- ◆ Supports power supply: ACE-716 series power supply
- ◆ Vibration: 5~17Hz, 0.1" double amplitude displacement
17~640 Hz, 1.5G acceleration part to part
- ◆ Shock: 10G acceleration peak to peak (11ms)
- ◆ Color: White (PANTONE 413C)
- ◆ Dimensions:
 - PAC-106 : 166 (W) x 175.5 (H) x 393 (D) mm (6.5" x 6.9" x 15.5")
 - PAC-107 : 166 (W) x 224.5 (H) x 393 (D) mm (6.5" x 8.8" x 15.5")
- ◆ Net/GW(kg): 5/7kg (PAC-106), 6/9kg (PAC-107)

ORDERING INFORMATION

- **PAC-106W/ACE -P**
6-slot compact chassis with ACE- P power supply
- **PAC-107W/ACE-P**
6-slot compact chassis with ACE- P power supply
- Power Supply
- **Standard Version**
- **PAC-106W/ACE-716A**
6-slot compact chassis with ACE-716A power supply
- **PAC-107W/ACE-716A**
6-slot compact chassis with ACE-716A power supply

Pentium® 4 Solution Available!!



SPECIFICATIONS

- ◆ Design to mount on Desktop and Wall mount
- ◆ Drive Bays : 1x5.25" drive bay, 1x3.5" HDD drive bay
- ◆ Optional 5.25" Drive bay : FCD-501, FCD-502, FCD-503
- ◆ One 8cm ball bearing cooling Fan
- ◆ Removable filter
- ◆ Designed with fan fault detecting system
- ◆ Front panel equipped with two USB ports
- ◆ Optional Backplane :

	ISA/PCI/PCISA	AGP/PCI/PIAGP
PCI-5S	1/3/2	-
PIAGP-5S(R)	-	1/3/1

- ◆ Standard equipped with Power Supply :
ACE-816A 150W with ATX Power Supply
ACE-916A 150W with AT power supply
UPF200-AA 200W with ATX Power Supply (Support P4 system)
- ◆ Optional Power Supply :
ACE-816AP/815C/815T ATX Power Supply
ACE-916AP AT Power Supply

UPF200-AA	+3.3V	+5V	+12V	-5V	-12V	+5Vsb
Min Load	0.5A	1A	1A	-	-	-
Max Load	9A	21A	10A	0.3A	0.8A	2A
Remark	+3.3V & +5V total 110W					
	+3.3V & +5V & +12V total 180W					

- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement
17~640 Hz, 1.5G acceleration part to part
- ◆ Shock : 10G acceleration part to part (11ms)
- ◆ Color : Dark Blue (PANTONE 433C)
- ◆ Dimension : 166mm(W)x192mm(H)x393mm(D)

ORDERING INFORMATION

- **PAC-1060A/ACE-816A :**
5-Slot Industrial compact chassis with ACE-816A ATX Power Supply
- **PAC-1060A/ACE-916A :**
5-Slot Industrial compact chassis with ACE-916A AT Power Supply
- **PAC-1060A/UPF200-AA :** P4 Solution
5-Slot Industrial compact chassis with UPF200-AA ATX Power Supply, support P4 system