

# ➤ DIMM-PC/lite DIMM-PC/lite-IE DIMM-PC/lite-IU



original size

**Intel®**  
**Communications**  
**Alliance**  
Associate Member  
SILVER

## ➤ Full PC functionality at the size of a business card

- No active cooling required
- Comes along with all common PC interfaces
- Extreme compact size (40 x 68mm)

## ➤ Product Overview

The DIMM-PC/lite-I is an extremely compact PC module to be plugged into customized base boards. The new DIMM-PC/lite-I, based on STPC Elite 100 MHz, features 486 performance with an integrated floating point unit, 32 Mbyte DRAM and 32 MByte IDE compatible Flash. Due to the extremely low power design no active cooling is required. The integrated high functionality of a x86 CPU Module comes along with all common PC interfaces (2x serial TTL, Printer, Keyboard, Floppy) and the DIMM-PC/lite-IU with one USB 1.1 port to address modern expansion devices.

Ethernet and x86-CPU on just 68x40 mm is ideal for space limited applications. The DIMM-PC® is widely used where stable performance is required but space and power consumption is limited. If your task is Embedded Internet and Embedded Connectivity - the DIMM-PC® is your solution. The DIMM-PC/lite is a very inexpensive choice and the cost effectiveness of this device is unbeatable. This DIMM-PC® brings you

....always a Jump ahead!

## ➤ Technical Information

<b>Processor</b>	STPC ELITE 100MHz
<b>SDRAM</b>	32 Mbyte on board
<b>IDE compatible Flash Disk</b>	32 Mbyte on board
<b>USB</b>	optional 1x USB 1.1 port, OHCI
<b>Ethernet</b>	10 MBit Ethernet
<b>IDE Hard Disk Interface</b>	on external device
<b>Serial Ports</b>	2x TTL (16550 compatible)
<b>Floppy Interface</b>	single drive
<b>Real Time Clock</b>	integrated witch chipset
<b>Keyboard Controller</b>	integrated witch chipset

<b>Other Features</b>	E²PROM BIOS Setup, JRC support, I²C Bus, Keyboard Controller, RTC, Watchdog, JIDA Support, Floppy Interface, alphanumerical LCD Support, 1x Enhanced Printer Port
<b>E²PROM</b>	for CMOS Setup
<b>Power Supply</b>	5V
<b>One Parallel Port</b>	LPT1, EPP support
<b>Power Consumption</b>	3 Watt @ 5V (approximately)
<b>Dimensions</b>	68 x 40 mm (2,7 x 1,6")
<b>Temperature</b>	operation: 0° to 60°C, storage: -25° to 85°C
<b>Humidity</b>	operation: 10% to 90%, non operating: 5% to 95% (non condensing)
licensed DR-DOS already pre-installed	

(\*) see manual for details

## ➤ Ordering Information

Article	Part.-No.	Description
DIMM-PC/lite-I	08016-3232-10-0	with STPC Elite 100 MHz
DIMM-PC/lite-IE	08016-3232-10-1	with STPC Elite 100 MHz and 10 Mbit Ethernet
DIMM-PC/lite-IU	08016-3232-10-2	with STPC Elite 100 MHz and 1x USB 1.1 port
DIMM-PCKit3	08005-0000-03-5	Starter Kit for DIMM-PC® with PC/104 interface (without DIMM-PC®)
DIMM-PC/VGA2	08014-0000-00-0	VGA controller for CRT and LCD flatpanel
DIMM-PC/ETH+COM	08006-0000-04-0	Ethernet controller and two serial interfaces
DIMM-PC/COMBO	08014-0000-01-0	VGA, Ethernet and two serial interfaces
DIMM-PC/Socket-CPU	SPCDIMM	Socket for DIMM-PC®, 144 Pin (90 pcs. Packed)
DIMM-PC/Socket-I/O	SIODIMM	Socket for DIMM-PC® I/O module 144 Pin (90 pcs. Packed)
JRC1	96047-0000-00-0	Remote Control Software with serial cable (License charge to be paid only once!)

## ➤ Corporate Offices

Europe, Middle East & Africa  
Brunnwiesenstr. 16  
94469 Deggendorf - Germany

US/ Canada  
6260 Sequence Drive  
San Diego, CA 92121-4371

Asia Pacific  
5F-1, 341, Sec 4, Chung Hsiao E.  
Rd, Taipei, Taiwan

Tel.: +49 (0)991/ 370 24-100  
Fax: +49 (0)991/ 370 24-102

Tel.: (858) 677-0877  
Fax: (858) 677-0898

Tel: +886 2 2781 5791  
Fax: +886 2 2741 7379

sales-kem@kontron.com

sales@us.kontron.com

sales@kontron.com.tw