

➤ *cool/MONSTER/PM*



- All-In-One half size Pentium® M PISA® Slot-CPU
- FAST
Intel® Celeron® M and Intel® Pentium® M performance up to 1.8 GHz
- COMMUNICATION
4xCOM, LAN, USB 2.0, 2xIDE - PISA® for ISA and PCI IO back planes
- MULTIMEDIA
DUAL Screen support, Sound

Product Overview

The coolMONSTER/PM is an „all in one“ Intel® Pentium® M based slot PC with consistent half size slot design, while Intel® ULV Celeron® M is the ultra low Power option. Despite the very compact half size format it's possible to integrate the PISA® (PISA®=PCI+ISA) bus and a full featured set of interfaces. Beside all standard interfaces (four COM ports, one as RS232 or RS485, EPP/ECP parallel port, floppy, EIDE, USB and IRDA port), a SoundBlaster compatible sound chip and a high speed on chip video controller

(Intel® Extreme Graphics 2 engine) is available. It can operate CRT monitors and LCD flat panels in parallel even with different screen content.

Two EIDE ports, one with 40-pin connector, the other with 44-pin 2 mm connector, are available to support various mass storage devices. Additionally the coolMONSTER is equipped with an Ethernet 10/100Base-T interface (Twisted Pair). With Kontron You stay...always a Jump ahead!

Technical Information

Full PISA® Bus compliant Industry Standard

| | |
|------------------------------|--|
| Processor | Intel® Pentium® M Intel® (ULV) Celeron® M (all Dothan Core) |
| Chipset | Intel® 855GME, ICH4 |
| On chip Graphics | Intel® Extreme Graphics 2 engine, 2x 32 MByte VRAM UMA |
| Graphic interfaces | CRT, LCD (JILI) and DVO |
| RAM | DDR-RAM-DIMM for up to 1 GByte |
| COM | 4x RS232 (16 Byte FIFO), one switchable to RS485 |
| USB 2.0 | 3x, (third USB via feature-connector) |
| 10/100 BaseT Ethernet | 1x (RJ45) |
| Extensions | ISA & PCI IO (Backplane) |
| Kontron IP Features | E²PROM BIOS Setup, LAN Boot, JRC support, I²C Bus, RTC, Watchdog, JIDA Support |
| Sound | AC'97 compatible Stereo audio CODEC, Line in, Line out stereo, Mic in mono, 3D audio effects, full duplex |
| EIDE interface | 2x (1x 40 pin, 1x 44 pin) |

| | |
|---|--|
| Floppy interface | yes |
| Printer interface | yes |
| Keyboard/Mouse | yes/PS2 |
| LAN/USB Boot | yes |
| DarkBoot | yes |
| Watchdog | yes |
| HW monitor | yes |
| Real Time clock | yes |
| Dimensions | 175 x 125 mm (6,9 x 4,9") |
| Power Supply | 5V only |
| Plug'n Play compatible to any to other PISA SBC and therefore exchangeable | yes |
| Temperature (*) | Operation: 0° to 60°C Storage: -10° to 85°C |
| Humidity | Operation: 10% to 90% Storage: 5% to 95% |

(*) Ask about wider temperature ranges

Ordering Information

| Article | Part.-No. | Description |
|----------------|-----------------|--|
| coolMONSTER/PM | 07030-0000-08-1 | Intel® processor with 800MHz (soldered), 0KB L2, fanless |
| coolMONSTER/PM | 07030-0000-10-2 | Intel® ULV Celeron® M 373 processor with 1 GHz (soldered), 512KB L2, fanless |
| coolMONSTER/PM | 07030-0000-18-2 | Intel® Pentium® M 745 processor with 1.8 GHz (soldered), 2MB L2, fan |
| coolMONSTER/PM | 07030-0000-15-3 | Intel® Celeron® M processor 370 1.5GHz (socketed), 1MB L2, fan |
| | common features | Intel 855GME/ICH4 chipset, DDR-RAM-DIMM socket, 4xRS232C, LPT, FDC, IDE, USB 2.0, onchip Video Controller with 2x 32MB VRAM UMA for CRT and LCD, Sound, 10/100 MBit Ethernet, with PISA®-Bus, Half Size, without Memory. |

Corporate Offices

Europe, Middle East & Africa

Kontron AG
Oskar-von-Miller-Str. 1
85386 Eching/Munich
Germany
Tel.: +49 (0)8165/ 77 777
Fax: +49 (0)8165/ 77 219
sales@kontron.com

North America

Kontron America Corporate Office
14118 Stowe Drive
Poway, CA 92064-7147
USA
Tel.: +1 888 294 4558
Fax: +1 858 677 0898
sales@us.kontron.com

Asia Pacific

Kontron Asia Inc.
4F, No. 415, Ti-Ding Blvd.
Sec.2, NeiHu District
Taipei Taiwan 114
Tel.: +886-2-2799-2789
Fax: +886-2-2799-7399
sales@kontron.com.tw

Kontron Embedded Modules GmbH

Brunnwiesenstr. 16
94469 Deggendorf
Germany
Tel.: +49 (0)991/ 370 24-100
Fax: +49 (0)991/ 370 24-333
sales@kontron.com