

G4E600-D-G

Intel 845E chipset
Socket 478-based Intel® ATX board

PROCESSOR (Socket 478-based Intel®)

- Intel® Pentium® 4 Processor with Hyper-Threading Technology
- Intel® Pentium® 4 Processor (478-pin)
 - 533MHz system data bus
 - 400MHz system data bus
- Intel® Celeron® Processor (478-pin)
 - 400MHz system data bus

CHIPSET

- Intel® 845E chipset
 - Intel® 82845E Memory Controller Hub (MCH)
 - Intel® 82801DB I/O Controller Hub (ICH4)

SYSTEM MEMORY

- Two 184-pin DDR SDRAM DIMM sockets
- 2.5V unbuffered PC1600 (DDR200) or PC2100 (DDR266) SDRAM DIMM
- Supports maximum of 2.GB system memory using 64Mbit, 128Mbit, 256Mbit, or 512Mbit technology
 - Double-sided x16 DDR SDRAM DIMM is not supported
- Supports ECC function

BIOS

- Award BIOS, Windows® 98SE/2000/ME/XP Plug and Play compatible
- Supports SCSI sequential boot-up
- Flash EPROM for easy BIOS upgrades
- Supports DMI 2.0 function

ENERGY EFFICIENT DESIGN

- Supports ACPI specification and OS Directed Power Management
- Supports ACPI STR (Suspend to RAM) function
- Wake-On-Events include:
 - Wake-On-Keyboard/Mouse
 - Wake-On-USB Keyboard
 - Wake-On-Ring (through internal or external modem)
 - Wake-On-LAN
 - RTC timer to power-on the system
- System power management supported
- CPU stopped clock control
- Hardware supports SMI green mode
- Microsoft®/Intel® APM 1.2 compliant
- Soft Power supported - ACPI v1.0a specification
- AC power failure recovery

DAMAGE FREE INTELLIGENCE

- Monitors CPU/system temperature and overheat alarm
- Monitors 5VSB(V)/VBAT(V)/1.5V/3.3V/5V/±12V/CPU voltages and failure alarm
- Monitors CPU/system/second fan speed and failure alarm
- Automatic chassis/second fan speed on/off control
- Read back capability that displays temperature, voltage, and fan speed
- Opened chassis alarm

ONBOARD AUDIO FEATURES

- 18-bit stereo full-duplex codec with independent variable sampling rate
- High quality differential CD input
- True stereo line level outputs

ONBOARD LAN FEATURES

- Uses Intel® 82562EX 10/100Mbps PLC
- Integrated IEEE 802.3, 10BASE-T, and 100BASE-TX compatible PHY
- Supports IEEE 802.3u auto-negotiation
- Automatic detection of "unplugged mode"
- 1:1 transmit transformer ratio support
- 10 BASE-T auto-polarity connection

PCI IDE INTERFACE

- Supports ATA/33, ATA/66 and ATA/100 hard drives
- PIO Mode 4 Enhanced IDE (data transfer rate up to 14MB/sec.)
- Bus mastering reduces CPU utilization during disk transfer
- Supports ATAPI CD-ROM, LS-120 and ZIP

ACCELERATED GRAPHICS PORT (A.G.P.)

- Supports 1.5V AGP with up to 1066MB/sec. bandwidth For 3D graphics applications

ATX DOUBLE DECK PORTS

- 4 USB 2.0/1.1 ports
- 1 RJ45 LAN port
- 2 DB-9 serial port
- 1 DB-25 parallel port
- 1 mini-DIN-6 PS/2 mouse port
- 1 mini-DIN-6 PS/2 keyboard port
- 3 audio jacks: line-out, line-in and mic-in

CONNECTORS

- 1 connector for 2 additional external USB 2.0/1.1 ports
- 1 connector for an external game/MIDI port
- 3 internal audio connectors (CD-in and AUX-in, and TAD)
- 1 connector for IrDA interface
- 2 IDE connectors
- 1 floppy connector
- 2 ATX power supply connectors
- 1 Wake-On-LAN connector
- 1 Wake-On-Ring connector
- 1 opened chassis alarm connector
- 3 connectors for CPU, chassis, and second fan

EXPANSION SLOTS

- 1 AGP slot that supports 1.5V AGP
- 5 PCI slots (1 shared with CNR slot)
- 1 CNR slot

COMPATIBILITY

- PCI 2.2, CNR 1.0 "A" type and AC '97 compliant
- Intel AGP version 2.0

CIRCUIT BOARD (PCB)

- 4 layers, ATX form factor
- 30.5cm (12.05") x 24.4cm (9.6")

SAFETY

- UL, cUL, FCC Class B, CE