

ROCHESTER Analog Power Transducers

POWER MEASUREMENT FOR CONTROL, MONITORING, AND DATA ACQUISITION




ANALOG POWER TRANSDUCERS

AMETEK Power Instruments offers a wide range of Rochester Analog Power Transducers for meeting all of your power measurement needs. The transducers consist of two families of products; the Process and the Ultra series. Each one is designed to provide an exact fit for your monitoring application.

The Process Transducers are ideally suited for industrial applications, with a wide selection of input current and voltages, multiple analog output choices, and a wide range of power supply options. The Ultra Transducers with their industry standard footprint and wiring connections work best for utility applications in generation, transmission and distribution. The Ultra Transducers come with UL approval and the most popular input and output selections.

Together, we have the widest selection of transducers available, making it easy to choose the one that best fits your needs.



Rochester Analog Power Transducers

- Utility Transducers
 - Utility standard footprint and wiring connections

Scientific Columbus Analog Power Transducers

- DL Transducers
 - Highest accuracy available (0.1% of reading)
- XL Transducers
 - High accuracy, wide range of measurements
- XLG Transducers
 - Compact packaging
 - UL recognized

Digital Power Transducers

- DPMS
 - 34 power measurements
- Software configurable, any circuit type
- Analog and digital outputs
- RS-232/485 communications with Modbus and DNP
- DPMS-PM
- Same as above, but with digital display



FEATURES AND BENEFITS

- Broad family of products
- Direct drop-in replacements for older models
- Field proven reliable design
- Models for any circuit type, input, output, and power





SPECIFICATIONS

Process Transducers

Transducer Functions and Models

Voltage	(VCC-1B, VCC-30B)
Current	(CCC-1B, CCC-30B)
Watts	(PCE-15, 20, 25, 30)
VARS	(VCE-15, 20, 25, 30)
Watt / VAR	(WV-15, 20, 25, 30)
Watthour	(WWH-15, 20, 25, 30)
VARhour	(VVH-15, 20, 25, 30)
Power Factor	(PFN-1B)
Phase Angle	(PFA-1B)
Voltage Angle	(PAN-1B)
Frequency	(FCN, FCX)

Features and Options Available

- Circuit Type
 - 1-1/2, 2, 2-1/2, or 3 element
- Voltage Input Ranges
 - 85-150, 170-300, 300-550, 50-90 VAC
- Current Input Ranges
 - 0-1, 0-2, 0-5, 0-10 Amps
- Power Input
 - Self powered
 - External: 120, 240, or 480 VAC
- Analog Outputs
 - 0-1, 0-5, 0-10, 0-20, 4-20, 4-12-20 mA
 - DC voltage outputs
- Frequency
 - 50, 60, 400 Hz
- · Calibration Adjustments
 - Standard <u>+</u>10% adjustment
 - W1: 50-125% adjustment
 - W2: 75-200% adjustment Certain selections are not available with each model type
- Surge Withstand
 - ANSI C37.90.1-1974 and BEAMA No. 219
- High Accuracy
 - 0.25% accuracy full scale

Ultra Transducers

Transducer Functions and Models

Voltage	(UltV10, 30)
Current	(UltA10, 30)
Watts	(UltW10, 20, 25, 30)
VARS	(UltR10, 20, 25, 30)
Watt / VAR	(UltC10, 20, 25, 30)

Features and Options Available

- Circuit Type
 - 1-1/2, 2, 2-1/2, or 3 element
- Voltage Input Ranges
 - 0-150, 0-300 VAC
- Current Input Ranges
 - 0-5, 0-10 Amps
- Power Input
 - Self powered
 - External: 120 VAC
- Analog Outputs
 - 0-1, 4-20, 4-12-20 mA (Certain selections are not available with each model type)
- Surge Withstand
 - ANSI 37.90.1-1989
- High Accuracy
 - 0.20% rated output for volts and current
 - 0.10% reading + 0.05% rated output for Watts, VARs (0-1 mA)
 - 0.20% of rated output for Watts, VARs (4-20 mA)



For customer support call:

POWER INSTRUMENTS

255 North Union Street Rochester, NY 14605 Tel: 585.263.7700 Fax: 585.262.4777 power.sales@ametek.com

HEADQUARTERS

AMETEK Power Instruments 50 Fordham Road Wilmington, MA 01887 Tel: 978.988.4903 Fax: 978.988.4990 www.ametekpower.com power.sales@ametek.com

EUROPEAN HEADQUARTERS

Unit 20, Ridgeway Donibristle Industrial Estate Dalgety Bay, Dunfermline, KY119JN Scotland U.K. Tel: 44.1383.825630

Fax: 44.1383.825715 power.sales@ametek.com

ASIA PACIFIC HEADQUARTERS

10 Ang Mo Kio Street 65 #05-12 Techpoint Singapore 569059 Tel: 65.6484.2388 Fax: 65.6481.6588











