


Vega 10

1 Port FXS

Home VoIP Gateway



Let's talk Voice over IP. Let's talk VegaStream. Our range of dedicated VoIP gateways is helping to drive down the total cost of business communications. VegaStream's technical know-how and non-stop support mean that VoIP simply works, first time, every time. We collaborate with service providers, technology and channel partners to enable easy integration with existing systems. VegaStream gives your business a voice.



Typical Vega 10
Gateway Applications

Service Provider Applications:

> Residential VoIP Gateway

Enterprise Applications:

> Small Office / Home Office VoIP
Gateway

For further details on these
applications, please refer to
www.vegastream.com

The Vega 10 VoIP Gateway connects standard analog telephones to IP networks and is designed for residential deployment. With the Vega 10 VoIP gateway, service providers and enterprises can offer VoIP telephony services to the home user over a residential broadband connection.

The Vega 10 supports 1 analog FXS port for connection to an existing analog telephone, fax machine or other analog terminal and an Ethernet interface for connection to a home or office Local Area Network.

The Vega 10 VoIP Gateway supports key enterprise and service provider requirements for installation, management, telephony features and security.

Ease of installation and large-scale manageability

The Vega 10 can be easily installed by the home user and remotely provisioned, configured and managed by the service provider or enterprise. Software and configuration can be managed securely and remotely.

The Vega 10 can be configured for individual country requirements such as analog line impedance and Calling Line ID standards.

Telephony Features

The Vega 10 offers the home user a full range of telephony features including call waiting, caller ID, call transfer, conferencing and visual and audible message waiting indicator. Enterprise customers can deliver their PBX feature set to home workers and service providers can gather additional revenue from value added features.

Security

The Vega 10 supports secure encryption for communication and provisioning to ensure service provider and enterprise communication and integrity is not compromised.

Vega 10

1 Port FXS

Home VoIP Gateway

Interfaces

VoIP Protocols

- > SIP
- > Audio codecs:
 - G.723.1 (5.3/6.4 kbps)
 - G.729a (8 kbps)
 - G.726 (16/24/32/40 kbps)
 - G.711 (a-law/ μ -law) (64 kbps)

Telephony Interface

- > 1 FXS port with splitter to two RJ-11 FXS connectors
- > 8 configurable impedance settings including N.America 600ohms and European CTR21

LAN Interface

- 1 Ethernet 10baseT interface (RJ-45 connector)

Features

Telephony Features

- > Flash Hook initiated features (Call Waiting, Cancel Call Waiting, Call Forwarding: No Answer / Busy / All, Do Not Disturb, Call Transfer, Three-way conference calling, Call Return, Call Back on Busy, Speed Dialing)
- > Message Waiting Indicator tones
- > Visual Message Waiting Indicator
- > Caller ID generation (Name and number) – Bellcore, DTMF, ETSI
- > Caller ID blocking
- > Call Waiting Caller ID with Name / Number
- > Music On Hold Client
- > Streaming Audio Server
- > Flexible dial plan and call routing features (Call blocking with toll restriction, Distinctive Ringing, Selective / Anonymous Call Rejection)
- > Off-hook warning tone
- > Delayed Disconnect
- > Hotline and warm line

Provisioning, Administration and Maintenance

- > Web browser administration and configuration using integral web server
- > Telephony key pad configuration with interactive voice prompts
- > Automated provisioning and upgrade using https, http and tftp
- > Asynchronous notification of upgrade availability
- > Non-intrusive, in-service upgrades
- > Report generation and event logging
- > Log and debug records

Call Quality

- > Differentiated Services (DiffServ)
- > Type of Service (ToS)
- > Fax Tone Detection Pass-through
- > In-band and Out-of-band DTMF (RFC2833)
- > Adaptive jitter buffer
- > Echo cancellation (G.165/G.168)
- > Voice Activity Detection with Silence Suppression

Security

- > SIP Proxy Redundancy
- > Re-registration with Primary SIP Proxy Server
- > SIP Support in Network Address Translation Records (including STUN)
- > Encrypted Calling by pre-standard implementation of Secure RTP
- > Password Protected Admin and User Access
- > Provisioning, Configuration and Authentication
 - > https with factory installed client certificate
 - > http digest encrypted authentication via MD5 (RFC 1321)
 - > Up to 256-bit AES or RC4 Encryption

Hardware

Certification

- FCC Part 15 Class B
- CE Mark

Environmental

- 5° to 45°C
- 10 to 90% humidity (non-condensing)

Display

- LED:
 - > LAN activity
 - > Gateway status

Physical Dimensions

- > 110mm (7.2") x 93mm (3.6") x 35mm (1.38") width/height/depth
- > Weight: 0.49kgs

Power

- > DC input voltage +5 VDC at 2A max
- 5 watts power consumption
- > Power Adapter 100-240v, 50-60Hz.(26-34VA) AC Input

Vega10/Draft3

Contact Details

Email: sales@vegastream.com
Web: <http://www.vegastream.com>

EMEA Office
VegaStream Limited
Berkshire Court
Western Road
Bracknell
Berks RG12 1RE
UK
+44 (0) 1344 784900

USA Office
VegaStream Inc.
10445 Pacific Center Court
San Diego
CA 92121
USA
+1 (877) 834 4470