- VOLTAGE: 90 264 VAC FULL RANGE
- FREQUENCY: 47 63 Hz
- INPUT CURRENT: 18.0 /9.0A (90 / 180 VAC)
- INRUSH CURRENT: 30A/60A MAX. FOR 115/230 VAC PER MODULE

OUTPUT CHARACTERISTICS:

OUTPUT VOLTAGE	OUTPUT CURRENT		REGULATION		OUTPUT
	MIN. [A]	MAX. [A]	LOAD	LINE	RIPPLE & NOISE MAX. [P-P]
5V	10	100	± 5%	± 1%	50mV
12V	4.0	72	± 6%	± 1%	100mV
+5VSB	0	2.1	± 5%	± 1%	50mV

REMARKS: MAX. TOTAL OUTPUT: 1020W

SPECIFICATION:

- TEMPERATURE RANGE: OPERATING 0 --- 40
- HOLD UP TIME: 16 ms MINIMUM AT FULL LOAD & NORMAL INPUT VOLTAGE
- DIELECTRIC WITHSTAND: INPUT / OUTPUT 1500 VAC FOR 1 SECOND INPUT TO FRAME GROUND 1500 VAC FOR 1 SECOND
- EFFICIENCY: 68% TYPICAL
- POWER GOOD SIGNAL: ON DELAY 100 ms TO 500 ms
- OVER LOAD PROTECTION: 130 +/- 20%
 OVER VOLTAGE PROTECTION: +5V → 5.74V ~ 7V, 12V → 14.3V ~ 15.6V,
 5VSB → 5.74 ~ 7V
- SHORT CIRCUIT PROTECTION: Shut down and latch off
- EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B
- SAFETY: MEET UL 1950, CSA 22.2 MP/ 950, TÜV IEC 950
- REMOTE ON / OFF CONTROL

THE UNIT SHALL ACCEPT A LOGIC OPEN COLLECTOR LEVEL WHICH WILL DISABLE / ENABLE ALL THE OUTPUT VOLTAGE (EXCLUDE +5V STANDBY), AS LOGIC LEVEL IS LOW, OUTPUTS VOLTAGE WERE ENABLE, AS LOGIC LEVEL IS HIGH. OUTPUTS VOLTAGE WERE DISABLE.

- N + 1 REDUNDANCY FUNCTION
- HOT-SWAPPABLE FUNCTION
- CURRENT / BALANCE LOAD SHARING DESIGN
- 12V / 5V REMOTE SENSING
- ISOLATION: BUILT-IN IN EACH POWER MODULE
- COOLING: TWO 40mm DC FANS IN EACH MODULE & TWO 80mm DC FANS IN POWER CHASSIS
- DIMENSION: 230 (D) x 164 (W) x 244.3 (H) mm

Revision: A01

