

Server WHQL Testing Services Enterprise Platforms and Services Division

Intel® Server Board S5000VSASCSI

Server Test Submission (STS) Report

For the Microsoft® Windows® Logo Program (WLP)

Rev 1.0

June 23, 2006

This report describes the Intel® S5000PSLSATA Server Platform Windows* Logo Program test run conducted by Intel Enterprise Platforms and Services Division (EPSD).

Purpose of this WLP Submission:

System First Time submission for the Microsoft* Designed for Windows Logo submission for the Intel $^{\$}$ Server Board S5000VSASCSI

Submission Type:	Reason for test run	Check one
First Time Submission	Initial Microsoft Designed for Windows logo submission. New product submission.	
System Update	Hardware update. (For example, update submission test run with new processor speeds.)	
BIOS Update	BIOS and/or Firmware update. (For example, update submission test run with new BIOS to support additional processor speeds.)	
OS Update	OS update. (For example, update submission test run to add Microsoft Designed for Windows Server 2003 logo to product.)	

Revision History and Disclaimers

Revision History		
Revision	Date	Comments
1.0	1.0 6/28/2006 STS Report for Windows Server 2003 Submission for Intel® Server Board S5000VSASCS	

THIS TEST REPORT IS PROVIDED "AS IS" WITH NO WARRANTIES WHATSOEVER, INCLUDING ANY WARRANTY OF MERCHANTABILITY, NONINFRINGEMENT FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY WARRANTY OTHERWISE ARISING OUT OF ANY PROPOSAL, SPECIFICATION OR SAMPLE.

Information in this document is provided in connection with Intel® products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by the sale of Intel products. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, life saving, or life sustaining applications.

Intel retains the right to make changes to its test specifications at any time, without notice.

The hardware vendor remains solely responsible for the design, sale and functionality of its product, including any liability arising from product infringement or product warranty.

Intel, Pentium, Itanium and Xeon are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

* Other names and brands may be claimed as the property of others.

Copyright © 2004, Intel Corporation. All rights reserved.

Contents

Revision History and Disclaimers	2
Introduction	4
Overview of Contents	
Terms and Definitions	
Server Board Submission Information	5
Intel Server Board Submission Report: Completion of WLP	5
Submission Information	5
Submission ID	5
Submission Type	5
Product Category	
Product Detail	
General Product Information	5
Characterization (optional)	
Server Board Configuration Information	
Processor	
System Memory	
Power Management	
BIOS	
Bus Types	
Integrated Components	
Onboard Integrated Devices and Drivers	
Product Data for HCL: Completion of WLP	
Product Data	8
Hardware Compatibility Tests Used	9
Errata and Contingencies	10
Submission Readme File	10
Testing Exceptions for S5000VSASCSI Windows Server 2000	
Testing Exceptions for S5000VSASCSI Windows Server 2003	
Testing Exceptions for S5000VSASCSI Windows Server 2003 64 Bit	
Additional Information	
Appendix A – Submission History	14

Introduction S5000VSASCSI

Introduction

This report provides an overview of the testing conducted on the Intel® Server Board S5000VSASCSI by Intel EPSD and provides details about this testing run.

Overview of Contents

Section	Content
Introduction	Brief descriptions of the sections in the report. Table listing terms and definitions.
Server Product Submission Information	Submission information, ID # and final server board configuration upon completion of WLP including HW, Driver version, BIOS version, and Board AA number
НСТ	All HCT's used during testing
Errata and Contingencies	All Microsoft* errata or contingencies used during testing

Terms and Definitions

Term	Definitions
EPSD	Enterprise Platforms and Services Division
HCL	Windows Hardware Compatibility List. Changed to Windows Server Catalogue. You can view the catalogue at: http://www.microsoft.com/windows/catalog/server/
нст	Hardware Compatibility Tests. For latest Server HCTs visit: http://www.microsoft.com/whdc/hwtest/system/default.mspx
STS	Server Test Submission Report published by EPSD
WHDC	Windows* Hardware and Driver Central. Provides technical information, development and testing kits, newsletters and support information. http://www.microsoft.com/whdc/default.mspx
WHOS	Windows Hardware Online Service – Secure online web site used to submit products for logo qualification and review submission history. https://winqual.microsoft.com/
WHQL	Windows* Hardware Qualification Lab. For more information visit the WHDC home page at: http://www.microsoft.com/whdc/whql/default.mspx
WLP	Windows Logo Program. For further information see: http://www.microsoft.com/whdc/winlogo/default.mspx
WTS	Workstation Test Submission Report published by EPSD

Server Board Submission Information

Intel Server Board Submission Report: Completion of WLP

Data in this section reflects system submission information at the time of WLP Update submission.

Submission Information

Submission ID					
Submission ID / Master ID	1141214				
Submission Type	Submission Type				
	Check Submission Type	Comments			
First-Time Hardware and Driver Test Submission	V				
System Update Test Submission					
Product Category					
Hardware Category	PC System or Server				
Operating System family	Windows Server 2003 (32 & 64 Bit) and Windows 2000 (Supported Status only for 2000) families				
Product Detail					
General Product Information					
Equipment Type	Server				
Primary Target Market	Business/Corporate				
Compliance	All applicable requirements				
Characterization (optional)					
	Check appropriate options Comments				
Web Server	\square				
SQL Database Server					
File Server	\square				

June 23, 2006 5

Server Board Configuration Information

Processor		
Quantity	2 (physical processors installed)	
Front Side Bus Speed	1067 MHz	
Family/Model	Dual-Core Intel [®] Xeon [®] processors	
Speed	1.60, 1.86, 2.00, 2.33, 2.66, 3.00, 3.20, and 3.73 GHz	
System Memory		
Amount Installed	16 GB	
Memory Type	FB DDR2-533 (2 GB FBDIMMs, ECC)	
Power Management		
ACPI Sleep States (S1, S2, S3, S4)	S1, S4	
Server Board Product		
System uses logo'd motherboard	NO (Server boards are NOT eligible for logo under the Microsoft* Motherboard logo program)	
Board AA #/Fab	PBA	
Board Manufacturer	Intel Corporation	
Board Model	Intel [®] Server Board S5000VSA	
Northbridge* Chipset Manufacturer	Intel Corporation	
Northbridge Chipset Model	Intel [®] 5000V Memory Controller Hub	
Southbridge* Chipset Manufacturer	Intel Corporation	
Southbridge Chipset Model	Intel® ESB2-E I/O Controller	
BIOS		
BIOS Manufacturer	AMI*	
BIOS Version	S5000.86B.02.00.0051	
BIOS Date	6/5/2006	
BIOS URL (For Updates)	htttp://support.intel.com/support/motherboards/server/S5000VSA/	

Bus Types			
	Check all that Apply		Check all that Apply
PS/2	\checkmark	AGP*	
1394		PCCard* (16-bit)	
CF (Compact Flash)		CardBus* (32-bit)	
PCI	\checkmark	USB	
Mini-PCI		USB 2.0	
AMR		InfiniBand*	
ACR		Bluetooth*	
COM (Serial)	\checkmark	PCI Express	\checkmark
Integrated Components			
	Check all that Apply		Check all that Apply
Audio		Display	\checkmark
IDE	\checkmark	Networking	
SCSI	\checkmark	RAID	
Modem		Bluetooth*	

Onboard Integrated Devices and Drivers

Data in this section reflects system configuration at the time of WLP submission. The latest drivers for the Intel[®] Server Board S5000VSASCSI are available for download at: ttp://support.intel.com/support/motherboards/server/S5000VSA/

Technology	os	Version
Intel® S5000/ESB2-E Chipset The chipset contains two main components: the Memory Controller Hub (MCH) for the host bridge and the I/O controller hub for the I/O sub-system. The chipset uses the Enterprise South Bridge (ESB2-E) for the I/O controller hub.	Windows Server 2003 Windows Server 2003 – 64Bit	7.4.0.1005 7.4.0.1005
Embedded SATA RAID (ESB2-E) Controller SW RAID mode	Windows Server 2003 Windows Server 2003 – 64Bit	4.11.0407.2006 4.11.0407.2006
LSI 22320-R Controller	Windows Server 2003 Windows Server 2003 – 64Bit	1.10.02 1.10.02
LAN 2 X Intel PRO/1000-EB Server Network Connection Supports 10/100/1000 and I/O Accelerated Technology (Intel 82563GB Controller)	Windows Server 2003 Windows Server 2003 – 64Bit	9.3.39.0 9.3.39.0

I/O Accelerated Technology	Windows Server 2003 Windows Server 2003 – 64Bit	1.2.52.0 1.2.52.0
Display ATI* ES1000 SVGA PCI video controller with 16 MB of video memory	Windows Server 2003 Windows Server 2003 – 64Bit	8.24.3.0 8.24.3.0
Intel® ESG-SHV backplane (Null driver)	Windows Server 2003 Windows Server 2003 – 64Bit	5.00.6055.2 5.00.6055.2

Product Data for HCL: Completion of WLP

Data in this section reflects product data for HCL at time of WLP submission.

Product Data			
Product Name	Intel [®] Server Board S5000VSASCSI		
Additional Product Names			
Supported Platforms	1		
	Check Tested	Comments	
Windows 2000 Server	\checkmark		
Windows 2000 Advanced Server			
Windows Server 2003, Web Edition			
Windows Server 2003, Standard Edition			
Windows Server 2003, Enterprise Edition	V		
Windows Server 2003, Enterprise Edition 64 Bit	Ø		

Hardware Compatibility Tests Used

Microsoft* Windows Hardware Driver Central Server Testing Home Page: http://www.microsoft.com/whdc/hwtest/system/default.mspx.

Please check this website regularly for test kit updates.

Operating Systems	Notes	Hardware Compatibility Tests (HCT)
Windows* 2000	HCT 12.1.01 Test Procedures for Systems, Servers and Cluster Servers (Windows 2000)	HCT 12.1.01 Test Kit (Windows 2000) (35.4 MB)
	http://download.microsoft.com/download/whistler/ Docs/Docs/W982KMeXP/EN- US/HCT9502_Systems.exe	http://download.microsoft.com/download/whistler/Tools/Tools/W98NT42KMeXP/EN-US/HCT9502UPD.EXE
	Logo'd Components Index Full Install	Logo'd Components Index Full Install (~9.8 MB)
		http://download.microsoft.com/download/whistler/Instal I/20.0/W982KMeXP/EN-US/logoidx.exe
	391 NDIS Intermediate Drivers Instructions	Beta NDIS Test Update (ndt391.exe) (2MB)
	http://download.microsoft.com/download/whistler/ Install/20.1/W982KMeXP/EN- US/NDISIntermedDriver.exe	http://download.microsoft.com/download/whistler/Instal I/12.2/W982KMeXP/EN-US/ndt391.exe
	386 NDIS Intermediate Drivers Instructions	NDIS Test Update for Windows 98 SE, Windows Me, and Windows 2000 (ndt386.exe) (2.02MB)
	http://download.microsoft.com/download/whistler/ Install/20.1/W982KMeXP/EN- US/NDISIntermedDriver.exe	http://download.microsoft.com/download/whistler/Instal l/12.2/W982KMeXP/EN-US/ndt386.exe
Windows Server 2003	HCT 12.1.0 Test Procedures and Readme files for Windows XP SP1 and Windows Server 2003 (4.95MB)	HCT 12.1.01 (Windows XP SP1 and Windows Server 2003) Test Kit (4.95MB)
	http://www.microsoft.com/whdc/hwtest/search/de tails.aspx?ID=725	http://www.microsoft.com/whdc/hwtest/search/details.a spx?ID=724
	Logo'd Components Index Full Install	Logo'd Components Index Full Install (~9.8 MB)
		http://download.microsoft.com/download/whistler/Instal I/20.0/W982KMeXP/EN-US/logoidx.exe

Errata and Contingencies

Microsoft* System HCT Errata list is available at:

http://www.microsoft.com/whdc/hwtest/search/results.aspx?type=errata&key=system&kit=-1

Operating System	Identification Number	Title
Windows Server 2003	772	LAN Device Wake test is not required on network devices in mobile systems, multifunction, broadband, LAN emulation, wireless LAN, server LAN, or bus-powered USB network devices
Windows Server 2003	1522	PCI Compliance Test fails when the interrupt line in the North Bridge is defined as Read Only
Windows Server 2003	1306	The PCI Compliance test fails for MSI capability

Submission Readme File

Effective May 1, 2002, the new Microsoft standardized Readme form will be required for all hardware submissions that include any of the following testing exceptions:

- Test failures
- Tests not run
- Missing test logs
- Inconclusive test results

All testing exceptions must be identified with a valid Errata ID, Incident ID, or Contingency ID provided by WHQL. The new Microsoft standardized Readme file is available for download at: http://download.microsoft.com/download/whistler/install/1.0/w98nt42kmexp/en-us/readme.exe

Testing Exceptions for S5000VSASCSI Windows Server 2000

As of November 1st, 2004, Windows 2000 logs are no longer required for submission. Windows will only get a "Supported" status when submitted along with Windows Server 2003.

Testing Exceptions for S5000VSASCSI Windows Server 2003

Data in this section reflects product data and test exceptions listed in section 2 of the S5000VSASCSI Readme file at time of WLP First-Time submission ID Number 1141214.

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x86	Errata	1522	
Failing test name	PCI Compliance Test		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)	514.520: DEVICE INFO: Intel(R) 5000 Series Chipset PCI Express x4 Port 3 - 25E3 514.520: DEVICE INFO: PCI\VEN_8086&DEV_25E3&SUBSYS_00000000&REV_92\3&61aaa01&0&18 514.520: +TEST+SEV2: FAIL: 4.52.3 - If the device uses an interrupt, the Interrupt Line field must be implemented as read/write.		
Additional information (for example, test system in a multiple system configuration)			

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x86	Errata	1306	
Failing test name	PCI Compliance		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)	514.520: DEVICE INFO: Intel(R) 6311ESB/6321ESB PCI Express Upstream Port - 3500 514.520: DEVICE INFO: PCI\VEN_8086&DEV_3500&SUBSYS_00000000&REV_01\4&25c5d7df&0&0010 514.520: +TEST+SEV2: FAIL: - A PCI-Express device that generates interrupts must have an MSI or MSI-X capability.		
Additional information (for example, test system in a multiple system configuration)			

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x86	Errata	772	
Failing test name	Wake Device Server		

Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)	
Additional information (for example, test system in a multiple system configuration)	This test is not required for servers with Gb Ethernet devices, such as the Intel® PRO/1000 EB

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x86	Errata	772	
Failing test name	LAN Device Wake Up		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)			
Additional information (for example, test system in a multiple system configuration)	This test is not required for servers with Gb Ethernet devices, such as the Intel® PRO/1000 EB		

Testing Exceptions for S5000VSASCSI Windows Server 2003 64 Bit

Data in this section reflects product data and test exceptions listed in section 2 of the S5000VSASCSI Readme file at time of WLP First-Time submission ID Number 1141214.

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x64	Errata	1522	
Failing test name	PCI Compliance Test		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)	514.520: DEVICE INFO: Intel(R) 5000 Series Chipset PCI Express x4 Port 3 - 25E3 514.520: DEVICE INFO: PCI\VEN_8086&DEV_25E3&SUBSYS_00000000&REV_92\3&61aaa01&0&18 514.520: +TEST+SEV2: FAIL: 4.52.3 - If the device uses an interrupt, the Interrupt Line field must be implemented as read/write.		
Additional information (for example, test system in a multiple system configuration)			

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x64	Errata	1306	
Failing test name	PCI Compliance		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)	450.454: DEVICE INFO: Intel(R) 6311ESB/6321ESB PCI Express Upstream Port - 3500 450.454: DEVICE INFO: PCI\VEN_8086&DEV_3500&SUBSYS_00000000&REV_01\4&25c5d7df&0&0010 450.454: +TEST+SEV2: FAIL: - A PCI-Express device that generates interrupts must have an MSI or MSI-X capability.		
Additional information (for example, test system in a multiple system configuration)			

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x64	Errata 772		
Failing test name	Wake Device Server		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)			
Additional information (for example, test system in a multiple system configuration)	This test is not required for servers with Gb Ethernet devices, such as the Intel® PRO/1000 EB		

Operating system (Windows XP, Windows 2000, etc.)	Failure type (Contingency, Errata, Incident)	ID number	
Windows Server 2003 EE x64	Errata	772	
Failing test name	LAN Device Wake Up		
Applicable error message (Type N/A if the error message or failing text is excessive or if there is no text)			
Additional information (for example, test system in a multiple system configuration)	This test is not required for servers with Gb Ethernet devices, such as the Intel® PRO/1000 EB		

Additional Information

No additional information entered in section 3 of the S5000VSASCSI Readme file at time of WLP submission ID 1141214.

Appendix A – Submission History

Microsoft "Designed for Windows*" logo submission history for the Intel® Server S5000VSASCSI:

Submission ID	Туре	Date	OS Qualified	Processor Speeds	Board Revision	BIOS Version
1141214	First-Time	6/28/06	Windows 2003 EE 32 & 64 Bit	1.60, 1.86, 2.00, 2.33, 2.66, 3.00, 3.20, and 3.73 GHz	501	\$5000.86B.02.00.51 6/5/2006