IAC-F694

Dual CPU Sockets 370 full-size Celeron/PIII SBC with VGA/Dual-LAN



FEATURES

- Support Intel Pentium III/Celeron Socket 370 CPU (66/100/133 MHz FSB)
- VIA 694X/686B chipset
- Three DIMM sockets, support up to 1.5GB SDRAM
- On board two Intel 82559 chips, support Dual-10/100 Base-T Ethernet, on-board RJ45 connector, support Wake-On-LAN function
- Two PCI IDE ports that support up to four IDE devices and Ultra DMA-33/66/100
- One FDD port, support up to two floppy devices and two COM port

ORDERING INFORMATION

IAC-F694A	Dual CPU with VGA / Dual LAN
IAC-F694B	One CPU with VGA / Dual LAN

OPTIONAL

3 11 3 1	CPU Fan High-quality CPU Fan
----------	------------------------------

SPECIFICATIONS

- CPU: Intel® Pentium® III / Celeron ™Processor in Socket 370 (66/100/133 MHz)
- Chipset: VIA 694X/686B chipset
- BIOS: Phoenix® licensed BIOS
- System Memory: Three 168-pin DIMM sockets, support up to 1.5GB SDRAM
- AGP VGA Controller: ATI Rage SL, shared memory 8MB
- Ethernet: Two Intel 82559 chip, support Dual-10/100
 Base-T Ethernet, on-board RJ-45 connector, support
 Wake-On-LAN function
- Flash Memory Disk: Reserved socket for DiskOnChip from M-System, support up to 144MB flash memory disk
- IDE Interface: 2 PCI IDE port that support up to 4 IDE devices and Ultra DMA-33/66/100
- Floppy Drive Interface: 1 FDD port, support up to 2 floppy devices
- Serial Port: 2 COM port, 1 x RS-232 and 1 x RS-232/422/485
- Parallel Port: 1 multi-mode parallel port (SPPEPP/ECP)
- Universal Serial Bus: Support 2 USB ports
- IR Interface: Support 1 IrDA header
- Digital I/O: 4-bit digital I/O header
- Keyboard Connector: 5-pin header
- Keyboard / Mouse Connector: On board 6-pin Mini-Din PS/2 mouse & keyboard
- RTC: Internal RTC with Li battery
- Watchdog Timer: 16-level time-out intervals
- Operating Temperature: 0°C ~ 60°C
- Storage Temperature: -20°C ~ 70°C
- **Humidity:** 5% ~ 95% RH, non-condensing
- Dimensions: 338.5 x 122 mm (13 1/4" x 4 5/6")
- **Net Weight:** 300g (0.66 pounds)