


KI0203

KI-2015-BBOA/NI RT

Capacitive sensors


Made in USA

Product characteristics

Capacitive sensor
 Plastic thread M30 x 1.5
 Cable
 Increased immunity to conducted radio frequency interference
 Sensing range 15 mm; adjustable 3...15 mm; [nf] non-flush mountable

Electrical data

Electrical design		AC/DC
Operating voltage	[V]	20...250 AC/DC
Protection class		II
Reverse polarity protection		no

Outputs

Output function		normally closed
Voltage drop	[V]	< 10 AC / < 8 DC
Minimum load current	[mA]	5
Leakage current	[mA]	< 2.5 (250 V AC) / < 1.7 (110 V AC) / < 1.5 (24 V DC)

Current rating

- Current rating (continuous)	[mA]	250 (...50 °C) / 200 (...70 °C)
- Current rating (peak)	[mA]	î: 1.5 A (20 ms / 0.5 Hz)
Short-circuit proof		no
Overload protection		no
Switching frequency	[Hz]	25 AC / 40 DC

Monitoring range

Sensing range	[mm]	15, adjustable 3...15 mm
Real sensing range (Sr)	[mm]	15 ± 10 %
Operating distance	[mm]	0...12.1

Accuracy / deviations

Correction factors		water = 1 / glass approx. 0.4 / ceramics approx. 0.2 / PVC approx. 0.2
Hysteresis	[% of Sr]	1...15
Switch-point drift	[% of Sr]	-15...15

Environment

Ambient temperature	[°C]	-25...70
Protection		IP 65

Tests / approvals

EMC		IEC 60947-5-2: 1997 + A1: 1999 + A2: 2003
MTTF	[Years]	302

Mechanical data

KI0203

KI-2015-BBOA/NI RT

Capacitive sensors

Mounting	non-flush mountable
Housing materials	PBT
Weight [kg]	0.14

Displays / operating elements


Output status indication	LED	red
--------------------------	-----	-----

Electrical connection

Connection	PVC cable / 2 m; 2 x 0.5 mm ²
------------	--

Wiring

Core colors
 BN brown
 BU blue



Note: miniature fuse to IEC60127-2 sheet 1, ≤ 2 A (fast acting)

Accessories

Accessories (included)	2 lock nuts; screwdriver
------------------------	--------------------------

Remarks

Remarks	Recommendation: check the unit for reliable function after a short circuit.
---------	---

Pack quantity [piece]	1
-----------------------	---