## **VCU-05 Video Control Unit**

Part Number 100-2415-01



Not just a camera controller, the VCU-05 can accept and switch any standard video source. The VCU-05 contains a 8 x 1 video switcher for direct selection of any video input and also passes all eight channels to interface to cabin video distribution system. The VCU-05 functions can be controlled via basic keyline and/or external RS-485 data bus control. Weighing in at 3.5 lbs. max., the VCU-05 also is able to interface the camera system to a Securaplane® aircraft security system.

## **Controls**

- Camera/Video Switched Output Select
- System On/Off
- Input Configuration (No of Inputs)
- CMZ zoom camera control (See CMZ Features, pg. 3.4)
- Security System Interface

## **Specifications:**

 $\begin{tabular}{lll} \begin{tabular}{lll} \begin{tabular}{lll} \begin{tabular}{llll} \begin{tabular}{lllll} \begin{tabular}{llllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{lllll} \begin{tabular}{llllll} \begin{tabular}{llllll}$ 

Finish Black powder coat/gold

Chem-Film

Power Requirements 28 VDC

 Power Consumption
 45w max, 25w typ. (6 cameras)

 Video Output
 NTSC, 1 v p-p at 75 ohms

 Mating Connector
 J1: MS27473E18A32S

 J2: MS27473E18A32P
 J3: MS27473E20A41P

Video Inputs 8

Video Outputs 9, one switched

Control Method RS485 or Keyline to GND

