



C6320



C6330

## C6320, C6330 | Control cabinet Industrial PC

C6320, C6330	C6320-0040	C6330-0040
<b>Housing</b>	3-slot Industrial PC for space-saving control cabinet installation	3-slot Industrial PC for space-saving control cabinet installation
	mounting sheet at the rear wall	mounting sheet at the rear wall
	1 slot for plug-in cards with a length of up to 190 mm	1 slot for plug-in cards with a length of up to 190 mm
	drives and plug-in cards easily accessible	drives and plug-in cards easily accessible
	all connectors at one side	all connectors at one side
	detailed PC configuration information on the housing	detailed PC configuration information on the housing
	protection class IP 20	protection class IP 20
	operating temperature 0...55 °C	operating temperature 0...55 °C
	weight of the basic configuration 4 kg (8.8 lbs)	weight of the basic configuration 4.6 kg (10.1 lbs)
	compact dimensions (W x H x D) 93 x 196 x 226 mm (3.6" x 7.7" x 8.8") without mounting plate	compact dimensions (W x H x D) 107 x 196 x 226 mm (4.2" x 7.7" x 8.8") without mounting plate
<b>Features</b>	processor Intel® Core™ Duo 2.0 GHz	processor Intel® Core™ Duo 2.0 GHz
	slot motherboard for Intel® Core™ Duo or Core™2 Duo	slot motherboard for Intel® Core™ Duo or Core™2 Duo
	3-slot passive backplane, 1 PCI slot available	3-slot passive backplane, 1 PCI slot available
	512 MB DDR2RAM, expandable to 3 GB	512 MB DDR2RAM, expandable to 3 GB
	on-board graphic adapter, Intel® GMA950, DVI-I connector	on-board graphic adapter, Intel® GMA950, DVI-I connector
	on-board dual Ethernet adapter with 1 x 10/100BASE-T and 1 x 10/100/1000BASE-T connector	on-board dual Ethernet adapter with 1 x 10/100BASE-T and 1 x 10/100/1000BASE-T connector
	hard disk, 2½-inch, 80 GB	hard disk, 2½-inch, 80 GB
	–	CD/DVD-ROM drive slimline
	4 serial ports RS232 on-board, 1 of these RS232 ports is led out with D-sub 9 connector; 8 USB 2.0, 3 of these USB ports are led out	4 serial ports RS232 on-board, 1 of these RS232 ports is led out with D-sub 9 connector; 8 USB 2.0, 3 of these USB ports are led out
	24 V DC power supply	24 V DC power supply
<b>Processor options</b>	processor Intel® Core™2 Duo 2.16 GHz	processor Intel® Core™2 Duo 2.16 GHz
<b>Further information</b>	for further options, technical drawings, documentations, etc. see <a href="http://www.beckhoff.com/C6320">www.beckhoff.com/C6320</a>	for further options, technical drawings, documentations, etc. see <a href="http://www.beckhoff.com/C6330">www.beckhoff.com/C6330</a>