

# CMB-677/674/672

## Mini-ITX Chassis with 1 PCI-Express slot & 300W ATX PSU .



### Product Information

- [Overview](#)
- [Features](#)
- [Product Image](#)
- [Ordering Guide](#)
- [Datasheet](#)

### Overview

Mini-ITX barebone system which support Intel Core 2 Quad / Core 2 Duo / Pentium D / Pentium 4 / Celeron D processor , Such as COMMELL's LV-678 , LV-677 , LV-674 & LV-672 Mini-ITX MB.

### [BackToTop](#)

### Features

Form Factor	Mini-ITX barebone system
Construction	Heavy-Duty steel
Mini-ITX Board	Inside Motherboard can be : LV-678 : Intel Core 2 Quad / Core 2 Duo LV-674 : Intel Core 2 Duo / Pentium D / Celeron D LV-672 : Intel Pentium 4 / Celeron D LV-677E : Intel Core 2 Duo / Core Duo / Core Solo
Drive Bay	External 1 x Slim CD-ROM & 1 x Slim FDD Space Internal 2 x 3.5" HDD Space
Riser card	1 x PCI-Express riser card
Thermal Control	One 12 cm system cooling Fan
Front Panel	System Reset switch Power On/Off and HDD activity 2 x USB ports
Rear Side I/O	Depend on Mini-ITX I/O plate .
Environment	Operating Temperature: 0 ~ 50C
Power supply	300W ATX power supply
Dimension	305 x 284 x 119 mm

Weight	5.65 kgw , (With Case , Motherboard , power supply)
--------	---