

# RACK-230A

1U Chassis



RACK-230AW



The Internal Configuration

ACE-890 Series Power Supply

## SPECIFICATIONS

- ◆ 1U height 19" Rack mounting chassis
- ◆ Designed for full / half size CPU card
- ◆ Drive Bays : 1 x 3.5" FDD  
1 x 3.5" HDD
- ◆ Four 4cm cooling fans
- ◆ One USB port on front panel
- ◆ Supports backplane : PCI-2SD-R13, IP-2SD-R11
- ◆ Supports one full size ISA or PCI add-on card
- ◆ Supports power supply : ACE-890 series power supply
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement  
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions : 431(W) x 44(H) x 486(D)mm; (17" x 1.7" x 19.1")
- ◆ Net/GW (kg) : 6/9

## ORDERING INFORMATION

- RACK-230A [C] / ACE-890A / [B]
- 1U rackmount chassis with ACE-890A power supply & B backplane
- [C] Color Code : B: Black W: White [B]: PCI-2SD-R13 or IP-2SD-R11 Backplane

# RACK-232

1U Chassis

RACK-232W



RACK-232B



Install 3.5" HDD or Half-size Board

## SPECIFICATIONS

- ◆ 1U height 19" Rack mounting chassis
- ◆ Designed for full / half size CPU card
- ◆ Drive Bays: 1 x 3.5" FDD  
1 x 5.25" Drive 1 x 2.5" HDD (With Anti-Shock designed)  
1 x 3.5" HDD (Share with add-on card space)
- ◆ Four 4cm cooling fans
- ◆ One USB port on front panel
- ◆ Supports backplane: PCI-2SD-R13, IP-2SD
- ◆ Supports one half size ISA or PCI add-on card, share with one 3.5" HDD space
- ◆ Supports power supply : ACE-890 series power supply
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement  
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions : 431(W) x 44(H) x 488(D)mm; (17" x 1.7" x 19.2")
- ◆ Net/GW (kg) : 6/9

## ORDERING INFORMATION

- RACK-232 [C] / ACE-890A / [B]
- 1U rackmount chassis with ACE-890A power supply & B backplane
- [C] Color Code : B: Black W: White [B]: PCI-2SD-R13 or IP-2SD-R11 Backplane

# RACK-235


1.5U Chassis



RACK-235W

RACK-235B

### PCI-4SD



### PCI-4SD2



## SPECIFICATIONS

- ◆ 1.5U height 19" Rack mounting chassis
- ◆ Drive Bays: 1 x 3.5" FDD  
2 x 3.5" HDD
- ◆ Two 6cm cooling fans with filter
- ◆ Standard equipped with PCI-4SD backplane
- ◆ Supports PICMG bus full size CPU card
- ◆ Supports backplane: PCI-4SD: 1xPICMG, 1xISA & 2xPCI  
PCI-4SD2: 1xPICMG, 3xPCI
- ◆ Supports power supply : ACE-890 series power supply
- ◆ Vibration : 5~17Hz, 0.1" double amplitude displacement  
17~640Hz, 1.5G acceleration peak to peak
- ◆ Shock : 10G acceleration peak to peak (11ms)
- ◆ Colors : Black (PANTONE Black C) or White (PANTONE 413C)
- ◆ Dimensions : 431(W) x 65(H) x 486(D)mm; (17" x 2.6" x 19.1")
- ◆ Net/GW (kg) : 6/10

Most Compact design for 4 slots in 1.5U chassis

## ORDERING INFORMATION

- RACK-235 [C] / ACE-890A / [B]
- 1.5U rackmount chassis with ACE-890A power supply & B backplane
- [C] Color Code : B: Black W: White [B]: PCI-4SD or PCI-4SD2 Backplane