

## 1.5 WATT UNREGULATED DC/DC CONVERTER

### PWR1726A/PWR1726A1



#### FEATURES

- 8000V ISOLATION TEST VOLTAGE
- NO EXTERNAL PARTS REQUIRED
- SYNCHRONIZABLE
- REMOTE ON/OFF
- LOW-BARRIER CAPACITANCE

#### APPLICATIONS

- BIOMEDICAL DATA ACQUISITION
- INDUSTRIAL PROCESS EQUIPMENT
- DATA ACQUISITION
- TEST EQUIPMENT
- PORTABLE EQUIPMENT

#### DESCRIPTION

The PWR1726A/PWR1726A1 is a single-channel, dual-output DC/DC/ converter designed for those applications where high-isolation voltage and low-barrier capacitance are critical for system reliability and integrity.

Calculated mean-time-to-failure (MTTF) is in excess of 100 years at an ambient temperature of +25°C and at rated output power. The performance of the PWR1726A/PWR1726A1 is not derated over its entire specified temperature range of -25°C to +85°C.

Synchronization of the PWR1726A/PWR1726A1 may be

accomplished simply by connecting the sync pin of one unit to the sync pin of another unit. In this manner, up to eight converters may be ganged together.

The PWR1726A/PWR1726A1 provides a plus and minus output voltage that is approximately equal to the magnitude of the input voltage. The unit operates over an input voltage range of 7VDC to 16VDC.

Each PWR1726A/PWR1726A1 isolation barrier is tested per the method set forth by UL544, VDE750, and CSA C22.2.

Power Electronics Division, United States  
3400 E Britannia Drive, Tucson, Arizona 85706  
Phone: 800.547.2537  
Fax: 520.770.9369

C&D Technologies, (NCL)  
Tanners Drive Blakelands North  
Milton Keynes MK14 5BU UK  
Tel: +44 (0)1908 615232 Fax: +44 (0)1908 617545

Any data, prices, descriptions or specifications presented herein are subject to revision by C&D Technologies, Inc. without notice. While such information is believed to be accurate as indicated herein, C&D Technologies, Inc. makes no warranty and hereby disclaims all warranties, express or implied, with regard to the accuracy or completeness of such information. Further, because the product(s) featured herein may be used under conditions beyond its control, C&D Technologies, Inc. hereby disclaims all warranties, either express or implied, concerning the fitness or suitability of such product(s) for any particular use or in any specific application or arising from any course of dealing or usage of trade. The user is solely responsible for determining the suitability of the product(s) featured herein for user's intended purpose and in user's specific application. C&D Technologies, Inc. does not warrant or recommend that any of its products be used in any life support or aviation or aerospace applications.


# COMMON SPECIFICATIONS

Specifications typical at  $T_A = +25^\circ\text{C}$ ,  $V_{IN} = 15\text{VDC}$ ,  $I_{LOAD} = \pm 50\text{mA}$  and in free-running mode unless otherwise noted.

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
<b>INPUT</b>					
Rated Voltage			12		V <sub>DC</sub>
Voltage Range		7		16	V <sub>DC</sub>
Input Current	$I_{LOAD} = 0$		30		mA
	$I_{LOAD} = \text{Rated Load}$		145	165	mA
	Short Circuit		115		mA
Ripple Current	$I_{LOAD} = \text{Rated Load}$		15		mAp-p
<b>ISOLATION</b>					
Voltage Rated Continuous		3500			V <sub>rms</sub>
AC, 60Hz		5000			V <sub>DC</sub>
DC		8000			V <sub>pk</sub>
Test Voltage	60sec, 60Hz				GΩ
Resistance			10		pF
Capacitance			10		μA
Leakage Current	$V_{ISO} = 240\text{VAC}, 60\text{Hz}$		1	2	
<b>OUTPUT</b>					
Rated Voltage	$I_{LOAD} = \text{Rated Load}$		±15		V <sub>DC</sub>
Voltage Range	$I_{LOAD} = \text{Rated Load}$	±14.25		±15.75	V <sub>DC</sub>
	$I_{LOAD} = 0\text{mA}$	±16.0		±18.0	V <sub>DC</sub>
Rated Current	Balanced Loads		±50		mA
Current Range	Balanced Loads	0		±90	mA
	Single Ended	0		180	mA
Line Regulation	$7\text{VDC} < V_{IN} < 18\text{VDC}$		1.16		mV/mV
Load Regulation	No Load $< I_{OUT} < \pm 50\text{mA}$			0.3	%/mA
Ripple Voltage	BW = DC to 10MHz				mVp-p
	$I_{LOAD} = 0$		15		mVp-p
	$I_{LOAD} = \text{Rated Load}$		50		mVp-p
Sync Out (PWR1726-A1 only)	$V_{IN} = 12\text{VDC}, V_{OUT} = \text{Rated, Balanced}$		30		Vp-p
					(referenced to common)
<b>GENERAL</b>					
MTTF	Calculated per MIL - HDBK - 217 Rev. E Ground, Benign 25° C		1.2		MHr
Switching Frequency			120		kHz
<b>TEMPERATURE</b>					
Specification		-25	+25	+85	°C
Operation		-40		+100	°C
Storage		-55		+110	°C

NOTE: Other input and output voltages may be available upon request. Please consult the factory.

## MECHANICAL



## ABSOLUTE MAXIMUM RATINGS

Input Voltage .....	18Vdc
Output Short-Circuit Duration .....	Continuous
Internal Power Dissipation .....	2W
Lead Temperature (soldering, 10 seconds max) .....	+300°C


## ORDERING INFORMATION

Device Family _____	<b>PWR</b>	<b>1726A</b>	<b>1</b>
PWR indicates DC/DC converter			
Model Number _____			
Sync Out _____			


## TYPICAL PERFORMANCE CURVES

TA=+25°C, Rated Input Voltage, Rated Output Current unless otherwise noted


### OUTPUT VOLTAGE VS. OUTPUT CURRENT



### OUTPUT VOLTAGE VS. INPUT VOLTAGE



## REMOTE ON/OFF CONTROL



If no connection is made to "Remote ON/OFF" pin, the converter will operate normally.

## SYNCHRONIZATION INFORMATION

The unit may be synchronized to an external clock. Recommended frequency is a minimum of 110KHz and a maximum of 250KHz. The sync signal must be a square wave pulse with a peak of 7.5V min to 12.0V max, the amplitude being referenced to -Vin.

