


IG5497

IGB3005-APOG/US-100-DPO

Inductive sensors



Made in Germany

Product characteristics

Inductive sensor
Metal thread M18 x 1
Connector
Sensing range 5 mm; [f] flush mountable

Electrical data

Electrical design	DC PNP
Operating voltage [V]	18...36 DC
Current consumption [mA]	< 15 (24 V)
Protection class	II
Reverse polarity protection	no

Outputs

Output function	normally closed
Voltage drop [V]	< 2.5
Current rating [mA]	150 (...50 °C) / 125 (...80 °C)
Short-circuit protection	no
Overload protection	no
Switching frequency [Hz]	500

Range

Sensing range [mm]	5
Real sensing range (Sr) [mm]	5 ± 10 %
Operating distance [mm]	0...4.05

Accuracy / deviations

Correction factors	mild steel = 1 / stainless steel approx. 0.7 / brass approx. 0.4 / Al approx. 0.3 / Cu approx. 0.2
Hysteresis [% of Sr]	1...15
Switch-point drift [% of Sr]	-10...10

Environment

Ambient temperature [°C]	-25...80
Protection	IP 67

Tests / approvals

EMC	EN 60947-5-2 EN 55011: class B
MTTF [Years]	3077

Mechanical data

Mounting	flush mountable
Housing materials	brass white bronze coated; active face: PC (polycarbonate)
Weight [kg]	0.049

IG5497

IGB3005-APOG/US-100-DPO

Inductive sensors


Displays / operating elements

Output status indication	LED	yellow
--------------------------	-----	--------

Electrical connection

Connection	M12 connector
------------	---------------

Wiring



Accessories

Accessories (included)	2 lock nuts
------------------------	-------------

Remarks

Pack quantity	[piece]	1
---------------	---------	---