

EFR-4302



- The world's best solution for Heavy-duty Network system
- Dual AC input for redundancy safety
- Hot- Pluggable capability and easy maintain
- Front panel LEDs for AC input and DC output power status
- Internal Oring Diodes provide high reliabilitties.
- Gold-plated Connector provide perfect transit
- Auto Ranging AC input
- Standard PC connection/ wiring interface
- Single wire current sharing on: +5V +3.3V +12V output
- Standard ATX voltage
- Remote DC sense for specified cable drop
- Power fault alarm system
- UL,CUL,TUV,CE
- 2 years warranty
- MTBF \geq 100,000 hours

AC-DC 900+300W

Model NO.

EFR-4302

INPUT	Voltage	Min.	Normal	Max.			
		90 VAC	115 VAC	132 VAC			
		180 VAC	230 VAC	264 VAC			
		Input voltage range set with a 115/230VAC Auto sensing selector					
	Frequency	47-63 MHZ					
	Current	115VAC/20A,230VAC/10A					
DC OUTPUT	Voltage	+5V	+3.3V	+12V	-5V	-12V	5VSB
	Max. Load	90	60	33	1	3	1.5
	Min. Load	3	0	1	0	0	0
	Max. Wattage	Total 860W			5W	36W	7.5W
	Load Reg.	$\pm 3\%$	$\pm 3\%$	$\pm 3\%$	$\pm 10\%$	$\pm 5\%$	$\pm 5\%$
	Cross Reg.	$\pm 3\%$	+3%	$\pm 3\%$	$\pm 10\%$	$\pm 5\%$	$\pm 5\%$
	Line Reg.	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$
	Ripple	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$
	Noise	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$	$\pm 1\%$
	Efficiency	65% Min. at full load					
Holdup Time	20 mS at full load						
Power Good Signal	100 to 500 mS						
Over Current Protection	+5V, +3.3V&-12V:110%-130% +12V:120%-150%						
Over Voltage Protection	+5V: 5.6V-6.9V +3.3V:3.7V-4.5V +12V:13.6V-15.6V						
Over Power Protection	Total output 110% Min. to 130% Max.						
Air flow	14CFM Min.Per Fan						
Temperature	30 to 122°F(0-50°C)						
Humidity	Operating: 20-90% non-condensing						
Safety Standards							
RFI/EMI Standards meet	FCC part 15, class B;CISPR 22(EN55022),class B;VCCI class 2						
Dimension	W x H x D 5x 8.74x 8.93 inch 127 x 222 x 227 mm						
Packing	Consult the sales office						