Portwell, Inc. 3F, No. 90, Nei-Hu Rd. Sec. 1, Taipei 114, Taiwan Tel: +886-2-2799-2020 Fax: +886-2-2799-1010 info@mail.portwell.com.tw

# PRA-1158

1U Rackmount 8-Port KVM Switch with 15" LCD Display



PRA-1158, is an 1U 8-port KVM drawer with 15" LCD display. Designed for 19" rackmount cabinets in a convenient drawer form, it is the most ideal solution to maximize usable cabinet space. The monitor keyboard unit has a built-in slide rail and mounts easily onto any 19" cabinet.

By handling all the different tasks without moving around, you can operate multiple systems via one single drawer. The digital control and on-screen display adjustment help system administrators access the system more efficiently than ever. They no longer need to jump from one system to another for their daily duties.

# **Specifications**

## Construction

· Heavy-duty steel

#### **LCD Display**

- 15" TFT display, 1024x768 resolution
- Pixel Pitch: 0.279 x 0.279
- Effective Display Area: 304.1 x 228.1mm
- Luminance (cd/m2): 230
- Contrast Ratio: 300
- Viewing Angle:
  - $+80^{\circ} \sim -80^{\circ} (L/R)$
  - +80° ~ -80° (U/D)
- Scan Frequencies:
  - 31.47K to 60Khz (horizontal)
  - 60Hz to 75Hz (vertical)

# **Keyboard/Mouse Touch Pad**

- 105-key keyboard with integrated Touch Pad
- Type Force: 60 ± 20g
- Key switch life: 10 Million life cycles
- Mouse Button: two key switches

#### **KVM Function**

- · 8 ports selection
- · Control Type: Digital
- With OSD built-in and auto scanning, operating systems independent
- OSD Adjustment: Contrast, Brightness, H-position, V-position, Phase, Pixel Clock, Color Temperature, Load Values and Auto-adjust
- Front Control (6 Keys): Power on/off Switch, Menu, Select (up, down) and Adjust (+, -)

## **Power Supply**

 Input: 40W 110-240VAC 48-62Hz Auto-switching PSU

## **Dimension**

- PRA-1151:
  483(W) x 515(D) x 44(H) mm
  19"(W) x 20.28"(D) x 1.7"(H)
- PRA-1158: 483(W) x 600(D) x 44(H) mm 19"(W) x 23.62"(D) x 1.7"(H)

#### Weight (Net)

PRA-1151: 18kgPRA-1158: 20kg

# **Environment**

# **Operating Temperature Range**

0 to +45°C

#### **Operating Humidity**

10 to 85% without condensation

## Certification

UL approval

## **EMI**

• FCC class A and CE

# **Ordering Guide**

## **PRA-1151**

19" 1U rack-mount Keyboard/ Mouse drawer with 15" TFT display, Black color

#### **PRA-1158**

19" 1U rack-mount Keyboard/ Mouse drawer with 15" TFT display and 8 ports KVM switch, Black color (8 sets of KVM cables included; length: 1.8m)



▲ Rear Panel of PRA-1158