

PS/2 Power Supplies



PS-500ATX-Z

500 W AC-DC ATX Power Supply with PFC

P/N: PS-500ATX-Z (1757000111)	
Input Range	115 - 240 V _{AC} , 47 - 63 Hz, 8 - 4 A
Outputs	+5 V @ 40 A (3 A min.), -5 V @ 0.8 A, +12 V @ 32 A (1 A min.), -12 V @ 1 A, +3.3 V @ 30 A (1A min.), +5 Vsb @ 2A
MTBF (hrs)	98,000
Safety	UL, TUV, CB, CCC
Compatible with Advantech Chassis	ACP-4000, ACP-4320, ACP-4362, IPC-610, IPC-611, IPC-615, IPC-622 (P/N: 1757000162), IPC-623 (P/N: 1757000133), IPC-630, IPC-6608, IPC-6908, IPC-7143, IPC-7220



PS-400ATX-ZB

400 W AC-DC ATX Power Supply with PFC

P/N: PS-400ATX-ZB (1757000108)	
Input Range	100 - 240 V _{AC} , 63 - 47 Hz, 8 - 4 A
Outputs	+5 V @ 35 A (3 A min.), -5 V @ 0.8 A, +12 V @ 30 A (1 A min.), -12 V @ 1 A, +3.3 V @ 25 A (1 A min.), +5 Vsb @ 2 A
MTBF (hrs)	91,000
Safety	UL, TUV, CB, CCC
Compatible with Advantech Chassis	ACP-4000, ACP-4320, ACP-4362, IPC-610, IPC-611, IPC-615, IPC-622 (P/N: 1757000193), IPC-623 (P/N: 1757000131), IPC-630, IPC-6608, IPC-6908, IPC-7143, IPC-7220



PS-300ATX-DC48

300 W DC-DC ATX Power Supply

P/N: PS-300ATX-DC48 (1757000103)	
Input Range	36 - 72 V _{dc} , 15A
Outputs	+5 V @ 30 A (0.3 A min.), -5 V @ 0.3 A, +12 V @ 15 A (0.2 A min.), -12 V @ 0.8 A, +3.3 V @ 28 A (0.3 A min.), +5 Vsb @ 2 A
MTBF (hrs)	100,000
Safety	UL, TUV, CB, CCC
Compatible with Advantech Chassis	ACP-2000, ACP-4000, ACP-4320, ACP-4362, IPC-602, IPC-610, IPC-611, IPC-615, IPC-630, IPC-6606, IPC-6608, IPC-6908, IPC-7143, IPC-7220



PS-300ATX-ZB

300 W AC-DC ATX Power Supply with PFC

P/N: PS-300ATX-ZB (1757930070)	
Input Range	100 - 240 V _{AC} , 50 - 60 Hz, 10 A
Outputs	+5 V @ 30 A (0.1 A min.), -5 V @ 0.3 A, +12 V @ 15 A, -12 V @ 0.8 A, +3.3 V @ 28 A (0.3 A min.), +5 Vsb @ 2 A
MTBF (hrs)	100,000
Safety	UL, TUV, CB, CCC
Compatible with Advantech Chassis	ACP-2000, ACP-4000, ACP-4320, ACP-4362, IPC-602, IPC-610, IPC-611, IPC-615, IPC-630, IPC-6606, IPC-6608, IPC-6908, IPC-7143, IPC-7220



PS-250ATX-Z

250 W AC-DC ATX Power Supply with PFC

P/N: PS-250ATX-Z (1757000117)	
Input Range	115/230 V _{AC} , 60/50 Hz, 10/5 A
Outputs	+5 V @ 27 A (0.5 A min.), -5 V @ 0.3 A, +12 V @ 13 A (1 A min.), -12 V @ 0.8 A, +3.3 V @ 20 A (0.3 A min.), +5 Vsb @ 2 A
MTBF (hrs)	100,000
Safety	UL, TUV, CB, CCC
Compatible with Advantech Chassis	ACP-2000, IPC-602, IPC-610, IPC-611, IPC-615, IPC-6606, IPC-6608, IPC-6908