

5.7" Standard Display Module

This module make integration easy. Each unit comes with an LCD, controller board, backlight driver, and touch screen, integrated and ready to go. The module form factor is designed to ensure long-term product availability.

The 5.7-inch standard unit features:

- QVGA resolution (320x240).
- High-brightness TFT panel.
- High-efficiency LED backlighting.
- Available with or without resistive touch screen.
- USB connectivity for additional flexibility.
- Two RS232 serial ports, one 3.3V CMOS serial port.
- LCD conforms to an industry standard form factor specifically chosen for multi-sourced long lifetime availability.
- Steel bracket makes display easy to mount.
- Powered by the SLCD6 controller.

Download mechanical drawings, panel specifications, controller and software reference manuals, and other resources in the Reach Download Center (www.reachtech.com/support/downloads/).

Get Started with a Development Kit

To get started with a 5.7-inch development kit order product number 52-0101-1X which includes module, cables, sample images, sample code, power supply, and technical support.

Visit our, "How can I get started?" webpage, call 510-770-1417, or email sales@reachtech.com for more information or to order.

Reach Technology, Inc. reserves the right to make changes in design or specification at any time and without notice.



5.7-inch Prime View Display Module, front view

Product Specifications

Product Part Number	51-0101-1X
Reach Board Model	SLCD6
Display Manufacturer	Prime View
Display Size and Type	5.7" TFT
Colors	65,536
Display Viewing Area (mm)	86.4 (H) x 115.2 (W)
Horizontal Viewing Angle (degrees)	120 (typ.)
Vertical Viewing Angle (degrees)	50 (Top) 40 (Bottom) (typ.)
Screen Resolution	320x240
Screen Type	QVGA
Display Brightness (cd/m2)	560 (typ.), with touch
Touch Panel Type	Resistive
Operating Temperature	-20°C to 70°C
Storage Temperature	-40°C to 70°C
Supply Voltage	5VDC±10%
Power Requirement	850mA max.
Interface Connector	Molex 53261 series
Serial Interface	RS232 / 3.3V CMOS
Backlight Display	LED
Number of Serial Ports	3
USB Port	Yes
SD Card Slot	No
Microprocessor	16/32 bit CISC
Flash Memory	4MB
RoHS	Yes