



Features

- Supports Socket 370 based Intel® Celeron® Processor
- C&T 69000/69030 LCD controller supports 36-bit TFT Panels
- One 10/100Base-T Fast Ethernet
- Supports DiskOnChip® up to 1GB
- PC/104 expansion connector



Specifications

System

- **CPU** Socket 370 based Celeron® Processor (.25 μ) up to 533MHz (with system bus frequencies of 66MHz)
- **System Memory** SDRAM DIMM x 1, Max. 256MB
- **Chipset** Intel® 443BX
- **I/O Chipset** Winbond W83977TF. Fully 16-bit I/O decoded
- **BIOS** Award 256KB FLASH BIOS
- **Ethernet** Realtek RTL8139X, 10/100Base-T RJ-45 connector x 1
- **SSD** Supports DiskOnChip® up to 1GB
- **Watchdog Timer** Generate a system reset, NMI
- **Expansion Interface** ISA interface, PC/104 connector x 1
- **Battery** Lithium battery
- **DMA** 7 DMA channels (8237 equivalent)
- **Interrupt** 15 interrupt levels (8259 equivalent)
- **H/W status monitoring** Winbond W83781D supports power supply voltages, CPU fan rotation and temperature monitoring
- **Power supply voltage** +5V (4.75V to 5.25V), +12V (11.4V to 12.6V), AT
- **Size/ Weight** 7.3" (L) x 4.8" (W) (185 mm x 122 mm), 0.66lb. (0.3Kg)
- **Operating temperature** 32°F to 140°F (0°C to 60°C)

I/O

- **MIO** IDE (UDMA33) x 1, FDD x 1, KB+Mouse x 1, RS-232 x 1, RS-232/422/485 x 1, Parallel x1
- **IrDA** One IrDA Tx/Rx header
- **USB** One 5x2 pin header supports 2 USB 1.1 ports

Display

- **Chip** C&T 69000/69030
- **Memory Size** Built-in 2MB SDRAM
- **Resolution** 1024 x 768 @ 16bpp colors
- **LCD Interface** 36-bit TFT/DSTN/MONO LCD panel

Packing List

- IDE cable 1701440500
- FDD cable 1701340600
- COM Port cable kit (1 parallel, 1 serial) 1701010302
- KB/Mouse cable 1700060192
- Short copper and support 9657000300
- Jumper Cap 9657666600
- Quick Installation Guide
- Utility CD