


## » pITX-SP 2.5" SBC «




### 2.5" SBC with Intel® Atom™ CPU up to 1.6GHz on Pico-ITX™



- » Pico-ITX™ Small Form Factor 100 x 72 mm
- » Intel® Atom™ Z510 / Z530 processor
- » Intel® Chipset US15W
- » Dual SATA, PATA44 and bootable microSD support
- » High performance combined with lowest power consumption - perfect for ultrasmall and ultramobile applications!

### Technical Information

<b>Processor</b>	Intel® Atom™ Z510 / Z530 1.1 / 1.6 GHz
<b>Chipset</b>	Intel® Chipset Hub US15W
<b>Memory</b>	1x DDR2 SO-DIMM up to 2GB
<b>Ethernet</b>	Intel® 82574L Gigabit Ethernet
<b>Graphics</b>	DirectX 9.0e, OpenGL 2.0, Shader based 2D and 3D dual independent graphics
<b>Graphics Controller</b>	Integrated decoders in Intel® Chipset US15W for MPG2 and H.264 / MPEG-4 AVC
<b>Mass Storage</b>	2x SATA II, 1x PATA 44 Master / Slave
<b>USB</b>	6x USB 2.0 (2x front panel, 4x internal)
<b>Audio</b>	HD Audio analog / SPDIF
<b>I/O Features</b>	8 Bit GPI/O, SDIO
<b>Dimensions (H x W x D)</b>	100 x 72mm (Pico-ITX)
<b>Special Features</b>	TPM 1.2, 1 x microSD socket
<b>Temperature</b>	Operating 0°C - 60°C (32°F ~140°F)
<b>Power Supply / Consumption</b>	5V DC, 5W typical



pITX-SP incl. mounted Heatspreader



### Ordering Information

Article	Part.-No.	Description
<i>pITX-SP 1.1 GHz standard</i>	03001-0000-11-2	pITX-SP 2.5" SBC, with Intel® Atom™ Z510 processor 1.1 GHz, Chipset US15W, Dual SATA, 6 x USB, JILI30 LVDS Support, Backlight Support, HD Audio, 1 x DDR2 SO-DIMM socket, micro-SD-Support, 5V DC, incl. passive cooling solution
<i>pITX-SP 1.1 GHz basic</i>	03001-0000-11-1	pITX-SP 2.5" SBC, with Intel® Atom™ Z510 processor 1.1 GHz, Chipset US15W, PATA 44, 2 x USB, HD Audio, 1 x DDR2 SO-DIMM socket, 5V DC, incl. passive cooling solution
<i>pITX-SP 1.6 GHz plus</i>	03001-0000-16-0	pITX-SP 2.5" SBC, with Intel® Atom™ Z530 processor 1.6 GHz, Chipset US15W, Dual SATA, PATA 44, 6 x USB, JILI30 LVDS Support, Backlight Support, HD Audio, GPIO, SDIO, TPM 1.2, 1 x DDR2 SODIMM socket, micro-SD-Support, 5V DC, incl. passive cooling solution
<i>pITX-SP 1.6 GHz standard</i>	03001-0000-16-2	pITX-SP 2.5" SBC, with Intel® Atom™ Z530 processor 1.6 GHz, Chipset US15W, Dual SATA, 6 x USB, JILI30 LVDS Support, Backlight Support, HD Audio, 1 x DDR2 SO-DIMM socket, micro-SD-Support, 5V DC, incl. passive cooling solution
<i>pITX-SP Accessory-Kit</i>	03101-0000-00-S3	Extended Accessory-Kit, incl. 1GB DDR2 RAM, 5V power supply (20 W), cables & accessories
<b>Recommended Memory Modules</b>		
<b>DDR2 SODIMM 512MB</b>	825551	DDR2 SODIMM , 512MB, 200p, 667MZ, PC5300
<b>DDR2 SODIMM 1GB</b>	825552	DDR2 SODIMM , 1GB, 200p, 667MZ, PC5300
<b>DDR2 SODIMM 2GB</b>	825553	DDR2 SODIMM , 2GB, 200p, 667MZ, PC5300

### CORPORATE OFFICES

#### Europe, Middle East & Africa

Oskar-von-Miller-Str. 1  
85386 Eching/Munich  
Germany  
Tel.: +49 (0)8165/ 77 777  
Fax: +49 (0)8165/ 77 279  
info@kontron.com

#### North America

14118 Stowe Drive  
Poway, CA 92064-7147  
USA  
Tel.: +1 888 294 4558  
Fax: +1 858 677 0898  
info@us.kontron.com

#### Asia Pacific

17 Building,Block #1,ABP.  
188 Southern West 4th Ring Road  
Beijing 100070, P.R.China  
Tel.: + 86 10 63751188  
Fax: + 86 10 83682438  
info@kontron.cn



#pITX-SP# 08092010PDL  
All data is for information purposes only and not guaranteed for legal purposes. Subject to change without notice. Information in this datasheet has been carefully checked and is believed to be accurate; however, no responsibility is assumed for inaccuracies. All brand or product names are trademarks or registered trademarks of their respective owners.