

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_QN-50-3-1/133\_N

Rev.: C 

### Description

Straight cable plug

Interface Standards  
QN QLF compliant



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$		
Interface frequency max.	11 GHz		
Frequency range	DC to 3 GHz	3 to 4 GHz	4 to 6 GHz
Return loss	$\geq 32$ dB	$\geq 28$ dB	$\geq 20$ dB

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.016 kg

#### Environmental Data

Operating Temperature	-40 °C to 125 °C
2002/95/EC (RoHS)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	EPDM	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

#### Related Documents

Outline drawing	DOU-00007368
Catalogue drawing	DOU-00007043
Assembly instruction	DOC-0000181765

#### Ordering Information

Single package	11_QN-50-3-1/133_NE
----------------	---------------------

#### Additional Information

Suitable cables	ENVIROFLEX_142, RG_223_/U, RG_142_B/U
-----------------	---------------------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**