Terminal box, type *KBD*

appliance TERMINALS

Material:

Insulating part: melamine type 150, tracking resistant clamping body and cover mounting screws: nickel-plated brass clamping screws: steel, zinc-plated and dichromated wire protection: phosphor bronze

T = (Number of poles -1) x 12
G = T + 30





Type KBD

with wire protection up to 2.5 mm²/fine-stranded

EN 60998-1/-2-1		500 V; 32 A;
Rated cross section	solid	4 mm²
Rated cross section	fine-stranded	2.5 mm²
Approvals		SEV

	Poles	G	Type	Part No.	Std. Pack
with female terminals and	2	42	KBD 1/ 2 KR	28.121.0240.0	50
wire protection	3	54	KBD 1/ 3 KR	28.121.0340.0	40
	4	66	KBD 1/ 4 KR	28.121.0440.0	30
	5	78	KBD 1/ 5 KR	28.121.0540.0	25
	6	90	KBD 1/ 6 KR	28.121.0640.0	20
	7	102	KBD 1/ 7 KR	available on request	20
	8	114	KBD 1/ 8 KR	28.121.0840.0	20
	10	138	KBD 1/10 KR	28.121.1040.0	15
	12	162	KBD 1/12 KR	28.121.1240.0	15

Subject to change without further notice